



AX308

sniper rifle

The highly advanced, new generation AX308 bolt action sniper rifle from Accuracy International is based on the DNA of the battle proven AW series. Inheriting the toughness, reliability, superb accuracy and ease of maintenance of it's celebrated predecessor, the AX action retains the same flat-bottom design with a compact and reliable double stack 10-round magazine. Simply perfection.





Butt pad

A fixed bolt-on pad with 10mm (0.4") and 20mm (0.8") spacers are fitted as standard. Additional spacers are available to customize the length of pull. Further adjustment is possible with the optional target adjustable butt plate or quick adjust butt plate in conjunction with the quick adjust cheekpiece.

2 Adjustable Cheekpiece

The standard adjustable cheekpiece adjusts left/ right as well as for height to obtain optimum cheek position when using night vision equipment or telescopic sights with large objective lenses. A spring loaded quick adjust cheekpiece is also available in conjunction with the quick adjust butt plate.

The extendable spike enables the user to for extended periods with minimal fatigue. Designed with quick a maximum extended length of 115mm (4.5").

3 Butt spike

observe the target area and fine adjustment to

design

The new external stock design greatly improves the user's ability to carry and move with the rifle. A shorter rear stock makes shooting easier in bulky body armour.

5 Pistol grip

Optional ergonomically advanced pistol grip or traditional thumbhole stock.

4 New stock 6 Folding chassis 7 Sling points

For use when travelling in vehicles or for parachute insertions, this option reduces overall length by 210mm (8") when folded and adds 0.2kg (0.4lb). Locked in the folded position for security and the avoidance of noise. the stock is released by pulling firmly on the butt. The wear compensated hinge ensures total rigidity

in the extended position.

Two sling attachment points are mounted on each side as standard. The two forward sling points can be moved according to user preference. Available as standard AI sling points or flush cups.

0

8 Bonded action

Superior to a traditional action/stock interface, the proprietary high grade steel flat bottom action is permanently bonded and bolted to the chassis. Coupled with a full width machined-in recoil lug, this totally rigid assembly ensures zero is maintained in all conditions.

9 Trigger assembly

Fitted as standard with adjustable pull weights of 1.5-2.0kg (3.3-4.4lb), the battle proven two stage mechanism allows a large sear engagement to be maintained until the first stage is taken up. A new trigger shoe, adjustable fore and aft by 13mm (0.5") is optional. The assembly is easily removed for cleaning by undoing the two socket head cap screws.

The rifle has a threeposition safety mechanism. Position 1 (rear) blocks the firing pin and locks the bolt in the closed position. Position 2 (mid) blocks the firing pin, but allows the bolt to be operated so a live round may be safely removed from the chamber. Position 3 (forward) allows the weapon to be fired. The safety will only operate when the bolt is cocked.

10 Safety

mechanism

11 Bolt

The 20mm (0.75") diameter steel close fitting bolt features an integral short throw bolt handle (60°) with large bolt knob which lies close to the stockside just above the trigger to minimise movement of the user's hand. The bolt can be field stripped without tools for cleaning.

12 Picatinny rail

This option is pinned and screwed to the action providing a standard interface for many optical systems. Available in flat, 20 MOA and 30 MOA cants.

13 Barrel

15262

The match grade free floating barrel is threaded deep into the action with a large diameter thread. Optional barrel lengths, twists, and muzzle breaks are available.

Suppressor assembly

threaded muzzle break.

The AX308 is shown here fitted with a sound and

The suppressor screws securely onto the tactical

recoil reducing short aluminium tactical suppressor.

14 Magazine

Surface toughened, and finished with a multi-part anti-corrosive, anti-friction coating, the compact 10-round double row, military grade steel magazine combined with the revised chassis design makes loading faster and more positive without lifting the rifle.

15 Forend rail system

Free floating tube forend in either 406mm (16") or 330mm (13") featuring a keyhole slot system for quickly and securely attaching modular rail sections on to which a virtually unlimited variety of optical, ranging, support and carry options can be fitted. Full length picatinny rails in flat, 20 MOA or 30 MOA options to match the action rail.

Accuracy

All rifles are shot and function tested before leaving the factory.

4X308

sniper rifle



Calibre	0.308 Win (7.62x51mm)		
Weight*	6.1kg (13.5lb) with 20" barrel		
Overall length	1020mm (40") with 20" barrel		
Action	One-piece, machined from high grade steel		
Trigger	Two-stage adjustable, set at 1.5-2.0kg (3.3-4.4lbs) Adjustable trigger shoe option		
Safety lever	Three position safety: 1st position blocks the firing pin and locks the bolt; 2nd (mid) position blocks the firing pin, but allows the bolt to be removed; 3rd (forward) position allows the weapon to be fired		
Barrel	Stainless steel match grade in various lengths. Various twist rates available to suit specific ammunition types. Fitted with a high efficiency muzzle brake. Muzzle brake and suppressor option		
Chassis	Adjustable cheekpiece, rear support leg, sling loops, moveable forward accessory rails and sight rail extensions to MIL-STD 1913		
Rear support leg	Height adjustable design featuring both quick and fine adjustment		
Magazine	New detachable box type containing ten rounds		
Carriage	Four sling attachment points - two adjustable forward mounts		
Stockside colour**	BLACK	GREEN	DARK EARTH

^{*}including empty magazine, Q/A Cheekpiece, Q/A Butt, minus telescopic sight



^{**}Barrels and actions are black