



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Rubber Cement

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Not applicable
Use of the substance/mixture : Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

The Gorilla Glue Company
2101 E. Kemper Road
Sharonville, OH 45241
513-271-3300
www.gorillatough.com

1.4. Emergency telephone number

Emergency number : 1-800-420-7186 (ProPharma)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :
H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) :
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fume or vapors
P264 - Wash hands and other exposed areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection
P301+P310 - If swallowed: Immediately call a poison center/doctor
P302+P352 - If on skin: Wash with plenty of water



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P331 - Do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use foam, dry powder, carbon dioxide, water spray, sand to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local, state, and federal regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	80-90*

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
---------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip clean-up crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No smoking. Use only non-sparking tools. Avoid breathing fume and vapors. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Naphtha, petroleum, hydrotreated light (64742-49-0)

Not Applicable

8.2. Exposure controls

Appropriate engineering controls : Ensure that adequate ventilation is provided.



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not normally required

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Off White
Odor	: Characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 98 °C
Flash point	: <-6 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Not miscible.
Log Pow	: No data available
Auto-ignition temperature	: 215 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 2500 - 4000 cP
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids, strong bases..

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h
ATE US (gases)	73680 ppmV/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Rubber Cement

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Rubber Cement

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local, regional, national and international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)



In accordance with DOT

Transport document description	: UN1133 Adhesives, 3, II
UN-No.(DOT)	: UN1133
Proper Shipping Name (DOT)	: Adhesives
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Rubber Cement

SARA Section 311/312 Hazard Classes	Flammable Skin corrosion or irritation Specific target organ toxicity Aspiration hazard
-------------------------------------	--------------------------------------------------------------------------------------------------

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory



Safety Data Sheet – Gorilla Glue – Rubber Cement

Date Revised: NEW
Date Issued: 01/20/2020

Version: 1.0

FOR CHEMICAL EMERGENCY:
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

15.3. US State regulations

Not applicable

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.