

ECO-SOL MAX2, ESL4-CY ECO-SOL MAX2, ESL4-4CY 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-CY ECO-SOL MAX2, ESL4-4CY

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: + 81-53-484-1224 FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement: Combustible liquid.



ECO-SOL MAX2, ESL4-CY ECO-SOL MAX2, ESL4-4CY

Version G_7.0 2024/01/09

May be harmful if swallowed. Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

† CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.



4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
 Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
 Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

3

Version G_7.0 2024/01/09



6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

- Derived No-Effect Level (DNEL)
 - Diethylene glycol diethyl ether:
 - [Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.



Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Cyan Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

9.2 Other information

No information.

Version G_7.0

2024/01/09

5



10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether



ECO-SOL MAX2, ESL4-CY ECO-SOL MAX2, ESL4-4CY

Version G_7.0 2024/01/09

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:

Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)



	ECO-SOL MAX2, ESL4-CY ECO-SOL MAX2, ESL4-4CY	Version G_7.0 2024/01/09
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous wast contain or are contaminated by dangerous substances or special wastes)	ie -
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.	2
14. Transport information)n	
14.1 UN Class/UN Number		
ADR/ADG/DOT, IMDG, o	or IATA: Not regulated	
14.2 UN proper shipping nam		
ADR/ADG/DOT, IMDG, o	or IATA: Not regulated	
14.3 Transport hazard class(e ADR/ADG/DOT, IMDG, c		
14.4 Packing group ADR/ADG/DOT, IMDG, o	or IATA: Not regulated	
14.5 Environmental hazards ADR/ADG/DOT, IMDG, o	or IATA: Not regulated	
14.6. Special precautions for u ADR/ADG/DOT, IMDG, o	user or IATA : Transport and storage of the product in accordance with general preca and instructions mentioned in this SDS.	outions
14.7. Transport in bulk accord	ding to Annex II of MARPOL 73/78 and IBC code: Not regulated	
15. Regulatory informati		

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)





16. Other information

List of relevant H-Statements:

- (Reference for Section 3. "Composition/information on ingredients")
- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.



Roland DG Corporation



ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Category 4
Category 5
Category 2
Category 1
Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement: Combustible liquid.



ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG

Version G_7.0 2024/01/09

May be harmful if swallowed. Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

† CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.



ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG

4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
 Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
 Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

3

Version G_7.0 2024/01/09



6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

- Derived No-Effect Level (DNEL)
 - Diethylene glycol diethyl ether:
 - [Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.



Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Magenta Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

9.2 Other information

No information.

Version G_7.0 2024/01/09



10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether



ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG

Version G_7.0 2024/01/09

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:

Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)



	ECO-SOL MAX2, ESL4-MG ECO-SOL MAX2, ESL4-4MG	Version G_7.0 2024/01/09
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous was contain or are contaminated by dangerous substances or special wastes)	
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must b disposed of in the same way as the substance.	e
14. Transport information	I	
14.1 UN Class/UN Number		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.2 UN proper shipping name		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.3 Transport hazard class(es)		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.4 Packing group		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.5 Environmental hazards		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.6. Special precautions for us	er	
ADR/ADG/DOT, IMDG, or	IATA : Transport and storage of the product in accordance with general preca and instructions mentioned in this SDS.	autions
14.7. Transport in bulk accordi	ng to Annex II of MARPOL 73/78 and IBC code: Not regulated	
15. Regulatory informatio	n	
	afety Assessment according to (EC)1907/2006	

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B



16. Other information

List of relevant H-Statements:

- (Reference for Section 3. "Composition/information on ingredients")
- H302: Harmful if swallowed.
- -H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- -H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is a ined. Roland DG does not warrant the com leteness or accurace of the information contained herein.





ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement: Combustible liquid.



ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE

Version G_7.0 2024/01/09

May be harmful if swallowed. Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

† CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.



ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE

4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
 Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
 Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

3

Version G_7.0 2024/01/09



4

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

- Derived No-Effect Level (DNEL)
 - Diethylene glycol diethyl ether:
 - [Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.



Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Yellow Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

9.2 Other information

No information.

Version G_7.0

2024/01/09



10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether



ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE

Version G_7.0 2024/01/09

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:

Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

7



	ECO-SOL MAX2, ESL4-YE	/ersion G_7.0 2024/01/09
	ECO-SOL MAX2, ESL4-4YE	
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)	5
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.	:
14. Transport information	1	
14.1 UN Class/UN Number		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.2 UN proper shipping name		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.3 Transport hazard class(es)		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.4 Packing group		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.5 Environmental hazards		
ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.6. Special precautions for us	er	
ADR/ADG/DOT, IMDG, or	IATA : Transport and storage of the product in accordance with general precau and instructions mentioned in this SDS.	utions
14.7. Transport in bulk accordi	ing to Annex II of MARPOL 73/78 and IBC code: Not regulated	
15. Regulatory informatio	n	
0	afety Assessment according to (EC)1907/2006	

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B



ECO-SOL MAX2, ESL4-YE ECO-SOL MAX2, ESL4-4YE

Version G_7.0 2024/01/09

16. Other informat

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.

- -H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.





2024/01/09

ECO-SOL MAX2, ESL4-BK ECO-SOL MAX2, ESL4-4BK

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-BK ECO-SOL MAX2, ESL4-4BK

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: + 81-53-484-1224 FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Category 4
Category 5
Category 2
Category 1
Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement: Combustible liquid.



ECO-SOL MAX2, ESL4-BK ECO-SOL MAX2, ESL4-4BK

Version G_7.0 2024/01/09

May be harmful if swallowed. Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	This product contains Carbon black.IARC evaluated printing ink as a Group 3.(IARC
	Group 3: Not classifiable as to carcinogenicity to humans)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Carbon Black	1333-86-4	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	< 20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

† CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.



4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
- Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
- Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray. Unsuitable extinguishing media: Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate

Roland DG Corporation



personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

- Carbon Black:

[Long term exposure] no hazard identified

[Short term exposure] no hazard identified

- Diethylene glycol diethyl ether:
 - [Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

 $-\gamma$ -butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European



ECO-SOL MAX2, ESL4-BK ECO-SOL MAX2, ESL4-4BK

Version G_7.0 2024/01/09

Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Black Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	> 71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limi	ts: No data available
Vapor pressure:	No data available
Vapor pressure: Vapor density:	No data available > 1
* *	
Vapor density:	> 1
Vapor density: Relative density:	> 1 0.9-1.0
Vapor density: Relative density: Solubility(ies):	> 1 0.9-1.0 soluble
Vapor density: Relative density: Solubility(ies): Partition coefficient: n-octanol/water:	> 1 0.9-1.0 soluble No data available
Vapor density: Relative density: Solubility(ies): Partition coefficient: n-octanol/water: Auto-ignition temperature:	> 1 0.9-1.0 soluble No data available No data available
Vapor density: Relative density: Solubility(ies): Partition coefficient: n-octanol/water: Auto-ignition temperature: Decomposition temperature:	> 1 0.9-1.0 soluble No data available No data available No data available
Vapor density: Relative density: Solubility(ies): Partition coefficient: n-octanol/water: Auto-ignition temperature: Decomposition temperature: Viscosity:	 > 1 0.9-1.0 soluble No data available



Version G_7.0

2024/01/09

Volatile organic compounds (VOC) content: 920 grams/L

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation: no data available.

Germ cell mutagenicity:



7

no data available.

Reproductive toxicity:

May damage fertility or the unborn child. • bis(2-(2-methoxy)ethyl) ether

Carcinogenicity:

This product contains Carbon black. IARC evaluated printing ink as a Group 3. (IARC Group 3: Not classifiable as to carcinogenicity to humans)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness. • γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available



13. Disposal considerations

13.1. Waste treatment methods

Product:	Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.
Recommended waste code:	08 03 12* (waste ink containing dangerous substances)
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

8

2024/01/09



International Information:

This product contains Carbon black.

IARC evaluated printing ink as a Group 3.

(IARC Group 3: Not classifiable as to carcinogenicity to humans

16. Other information

List of relevant H-Statements:

- (Reference for Section 3. "Composition/information on ingredients")
- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.





Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-4LC

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG CorporationAddress:1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103Phone: + 81-53-484-1224FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement:

Combustible liquid. May be harmful if swallowed. Causes skin irritation. Causes serious eye damage.



May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — **Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Stelltar Health Effects.		
Eyes:	Causes severe eye injury which may persist for several days.	
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.	
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired	
	fertility and irritate nose, throat/respiratory system.	
Ingestion:	May cause injury of mouth, throat, and stomach.	
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.	
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)	
Others:	No information.	

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Phthalocyanine blue	147-14-8	0-1	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

+ CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures



ECO-SOL	MAY2	EST A AT C	٦
ECO-SOL	MAA2.	ESL4-4LC	_

Eyes:	In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open
	during flushing. Call a physician.
Skin:	In case of contact, immediately flush with plenty of water while removing contaminated clothing and

- shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
- Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.



6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:



Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Cyan Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	>1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

9.2 Other information

No information.

10. Stability and reactivity



10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation. • Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:



ECO-SOL MAX2, ESL4-4LC

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness. • γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:	Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.
Recommended waste code:	08 03 12* (waste ink containing dangerous substances)
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)

Roland DG Corporation



Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.
14. Transport informatio	n
14.1 UN Class/UN Number	
ADR/ADG/DOT, IMDG, o	r IATA: Not regulated
14.2 UN proper shipping name	e
ADR/ADG/DOT, IMDG, o	r IATA: Not regulated
14.3 Transport hazard class(es	8)
ADR/ADG/DOT, IMDG, o	r IATA: Not regulated
14.4 Packing group	
ADR/ADG/DOT, IMDG, o	r IATA: Not regulated
14.5 Environmental hazards	
ADR/ADG/DOT, IMDG, o	r IATA: Not regulated
14.6. Special precautions for u	ser
ADR/ADG/DOT, IMDG, o	r IATA : Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.
14.7. Transport in bulk accord	ling to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.



ECO-SOL MAX2, ESL4-4LC

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.



1

Version G_7.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-4LM

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG CorporationAddress:1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103Phone: + 81-53-484-1224FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement:

Combustible liquid. May be harmful if swallowed. Causes skin irritation. Causes serious eye damage.



May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Stennar Health Effects:		
Eyes:	Causes severe eye injury which may persist for several days.	
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.	
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired	
	fertility and irritate nose, throat/respiratory system.	
Ingestion:	May cause injury of mouth, throat, and stomach.	
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.	
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)	
Others:	No information.	

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	<1	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	10-20	Not classified as hazardous

+ CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures



ECO-SOL MAX2, ESL4-4LM

Eyes:	In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open
	during flushing. Call a physician.
Skin:	In case of contact, immediately flush with plenty of water while removing contaminated clothing and
	shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give
	oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and
	irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.



4

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:



Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Magenta Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

9.2 Other information

No information.

10. Stability and reactivity



Version G_7.0

ECO-SOL MAX2, ESL4-4LM

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation. • Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:



ECO-SOL MAX2, ESL4-4LM

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness. • γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:	Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.
Recommended waste code:	08 03 12* (waste ink containing dangerous substances)
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)

Roland DG Corporation



Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.
14. Transport informati	on
14.1 UN Class/UN Number	
ADR/ADG/DOT, IMDG,	or IATA: Not regulated
14.2 UN proper shipping nam	ne
ADR/ADG/DOT, IMDG,	or IATA: Not regulated
14.3 Transport hazard class(es)
ADR/ADG/DOT, IMDG,	or IATA: Not regulated
14.4 Packing group	
ADR/ADG/DOT, IMDG,	or IATA: Not regulated
14.5 Environmental hazards	
ADR/ADG/DOT, IMDG,	or IATA: Not regulated
14.6. Special precautions for	user
ADR/ADG/DOT, IMDG,	or IATA : Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.
14.7. Transport in bulk accou	rding to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)



16. Other information

List of relevant H-Statements:

- (Reference for Section 3. "Composition/information on ingredients")
- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is ained. Roland DG does not warrant the com leteness or accurace of the information contained herein.





1

Version G_7.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-4LK

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: + 81-53-484-1224 FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Hazard Statement:

Combustible liquid. May be harmful if swallowed.



Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	This product contains Carbon black.IARC evaluated printing ink as a Group 3.(IARC
	Group 3: Not classifiable as to carcinogenicity to humans)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Carbon Black	1333-86-4	0-1	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	40-50	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Dialkylene glycol dialkyl ether	CBI	15-25	Not classified as hazardous

† CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.



4. First aid measures

4.1. Description of first aid measures

Eyes:	In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open
	during flushing. Call a physician.
Skin:	In case of contact, immediately flush with plenty of water while removing contaminated clothing and
	shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give
	oxygen. Call a physician.
Ingestion:	If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.	
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.	
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and	
	irritate nose, throat/respiratory system.	
Ingestion:	May cause injury of mouth, throat, and stomach.	

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.



6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Carbon Black:

[Long term exposure] no hazard identified

[Short term exposure] no hazard identified

- Diethylene glycol diethyl ether:
 - [Long term exposure] 50.05 mg/m³
 - [Short term exposure] no hazard identified
- γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).



Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

1 0 1	1
Appearance:	Black Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	920 grams/L

5

2024/01/09



Version G_7.0

2024/01/09

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50(oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.



Version G_7.0

2024/01/09

Reproductive toxicity:

May damage fertility or the unborn child. • bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

This product contains Carbon black. IARC evaluated printing ink as a Group 3. (IARC Group 3: Not classifiable as to carcinogenicity to humans)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods



		ECO-SOL MAX2, ESL4-4LK	2024/0
]	Product:	Dispose as hazardous waste. Packaging with product residues must be disposed under the same conditions as the product itself.	l of
]	Recommended waste code:	08 03 12* (waste ink containing dangerous substances)	
1	Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)	;
]	Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.	
14.]	Fransport information	1	
14.1	UN Class/UN Number		
A	ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.2	UN proper shipping name		
A	ADR/ADG/DOT, IMDG, or	IATA : Not regulated	
14.3	Transport hazard class(es)		
	ADR/ADG/DOT, IMDG, or		
14.4	Packing group		
A	ADR/ADG/DOT, IMDG, or	IATA: Not regulated	
14.5	Environmental hazards		
I	ADR/ADG/DOT, IMDG, or	IATA : Not regulated	
14.6.	Special precautions for us	er	
I	ADR/ADG/DOT, IMDG, or	IATA : Transport and storage of the product in accordance with general precau and instructions mentioned in this SDS.	itions
14.7.	Transport in bulk accord	ing to Annex II of MARPOL 73/78 and IBC code: Not regulated	

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

This product contains Carbon black. IARC evaluated printing ink as a Group 3. (IARC Group 3: Not classifiable as to carcinogenicity to humans



16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.



1

Version G_7.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-WH

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103 Phone: + 81-53-484-1224 FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Skin corrosion/irritation	Category 2

2.2. GHS label elements, including precautionary statements

Pictgram(s)

Warning

Signal Word:

Hazard Statement:

Combustible liquid. Causes skin irritation.

Precautionary statements — Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.



Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing.

Precautionary statements — Storage:

Store in a well-ventilated place. Keep cool.

2.3. Other hazards

•	Other nazarus	
	Potential Health Effects:	
	Eyes:	Contact with eye will be irritating.
	Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
	Inhalation:	Exposure to vapors (mist) will cause respiratory irritation and anesthesia.
	Ingestion:	May cause injury of mouth, throat, and stomach.
	Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
	Carcinogenicity:	This product contains Titanium dioxide.IARC evaluated printing ink as a Group 3.(IARC
		Group 3: Not classifiable as to carcinogenicity to humans)
	Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Titanium dioxide	13463-67-7	10-20	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	50-60	Skin Irrit. 2: H315
Dialkylene glycol dialkyl ether	CBI	10-20	Not classified as hazardous

+ CBI: Confidential Business Information

‡ For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
- Skin:In case of contact, immediately flush with plenty of water while removing contaminated clothing and
shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
- Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Contact with eye will be irritating.



ECO-SOL MAX2, ESL4-WH

Skin:Contact with skin may cause irritation, swelling or redness, allergic sensitization.Inhalation:Exposure to vapors (mist) will cause respiratory irritation and anesthesia.Ingestion:May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection



wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

Titanium dioxide:

[Long term exposure] no hazard identified

[Short term exposure] no hazard identified

Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³ [Short term exposure] no hazard identified

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.



Environmental exposure control: Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	White Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	>1
Relative density:	1.0-1.1
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	800 grams/L

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

Version G_7.0 2024/01/09

5



10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity: None of the ingredients in this ink is classified as acute toxicant.

Serious eye damage/eye irritation:

no data available.

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

no data available.

Carcinogenicity:

This product contains Titanium dioxide. IARC evaluated printing ink as a Group 3. (IARC Group 3: Not classifiable as to carcinogenicity to humans)

Specific target organ toxicity - single exposure, (STOT-SE):

no data available.

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.



12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

- **12.3. Bioaccumulative potential:** No data available
- 12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:	Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.
Recommended waste code:	08 03 12* (waste ink containing dangerous substances)
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)



ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

International Information:

This product contains Titanium dioxide. IARC evaluated printing ink as a Group 3. (IARC Group 3: Not classifiable as to carcinogenicity to humans

16. Other information

List of relevant H-Statements: (Reference for Section 3. "Composition/information on ingredients") — H315: Causes skin irritation.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is ained. Roland DG does not warrant the com leteness or accurac of the information contained herein.



1

Version G_7.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX2, ESL4-MT

1.2. Relevant identified uses of the substance or mixture and uses advised against Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG CorporationAddress:1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103Phone: + 81-53-484-1224FAX: + 81-53-484-1226

E-mail: Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids	Category 4
Acute toxicity (oral)	Category 5
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

Hazard Statement:

Combustible liquid. May be harmful if swallowed. Causes skin irritation. Causes serious eye damage.



May damage fertility or the unborn child.

Precautionary statements — Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Stelltar Health Effects.	
Eyes:	Causes severe eye injury which may persist for several days.
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.
Inhalation:	Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired
	fertility and irritate nose, throat/respiratory system.
Ingestion:	May cause injury of mouth, throat, and stomach.
Chronic Health Hazards:	Repeated skin contact may cause a persistent irritation or dermatitis.
Carcinogenicity:	None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)
Others:	No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Diethylene glycol diethyl ether	112-36-7	70-80	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	1-10	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360

* For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures

- Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
- Skin:In case of contact, immediately flush with plenty of water while removing contaminated clothing and
shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.



ECO-SOL MAX2, ESL4-MT

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes:	Causes severe eye injury which may persist for several days.	
Skin:	Contact with skin may cause irritation, swelling or redness, allergic sensitization.	
Inhalation:	: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and	
	irritate nose, throat/respiratory system.	
Ingestion:	May cause injury of mouth, throat, and stomach.	

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray. Unsuitable extinguishing media: Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.



4

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

 $-\gamma$ -butyrolactone:

[Long term exposure] 130 mg/m³ [Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:



Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

1 0 1	-
Appearance:	Silver Liquid
Odour:	Slightly odour
Odour threshold:	Not defined
pH:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point:	>71deg.C
Evaporation rate:	No data available
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	> 1
Relative density:	0.9-1.0
Solubility(ies):	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Volatile organic compounds (VOC) content:	930 grams/L

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:



6

Version G_7.0 2024/01/09

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

 γ -butyrolactone

LD50 (oral) : 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

γ-butyrolactone

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child. • bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.



• γ -butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

- **12.1. Toxicity:** No data available.
- **12.2. Persistence and degradability:** No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product:	Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.
Recommended waste code:	08 03 12* (waste ink containing dangerous substances)
Uncleaned packaging:	15 01 10* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)
Recommendation:	Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.

7



14. Transport information

14.1 UN Class/UN Number ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.2 UN proper shipping name ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.4 Packing group ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.5 Environmental hazards ADR/ADG/DOT, IMDG, or IATA : Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use,



ECO-SOL MAX2, ESL4-MT

2024/01/09

processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.