



MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards and European Union Standards

PART I What is the material and what do I need to know in an emergency?

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):

VIAL FLUID 2 (360 VIALS)

CHEMICAL NAME/CLASS:

Synthetic Isoparaffinic Hydrocarbon Mixture

PRODUCT USE:

Fluid in Leveling Vials

MANUFACTURER'S NAME:

STANLEY WORKS

ADDRESS:

480 Myrtle Street

New Britain, CT 06053

1-800-262-2161

Stanley Europe

BUSINESS PHONE:

Egide Walschaertsstraat 14-16

SUPPLIER/IMPORTER'S NAME (Europe):

Mechelen, 2800

Belgium

BUSINESS PHONE:

32 (0)15/47.37.00

EMERGENCY PHONE:

800-424-9300 (CHEMTREC) U.S., Canada, Puerto Rico. U.S. Virgin Islands

01-703-527-3887 (outside areas above, call collect)

DATE OF PREPARATION:

June 21, 2007

2. COMPOSITION and INFORMATION ON INGREDIENTS

NOTE: This product is an "Article" under the U.S. Federal OSHA Hazard Communication Standard (29 CFR 1910.1200), EU Directives, and the Canadian Workplace Hazardous Materials Standard. Refer to Section 15 (Regulatory Information) for specific regulatory citations. As articles, these products present negligible health and physical hazards under reasonably anticipated circumstances of use. Subsequently, a Material Safety Data Sheet is not required for this product under Standards cited above. This document is prepared to provide persons using these products with additional safety information. The fluid contained inside the vial may be released if the vial is cracked or broken, and although negligible physical and health hazards are possible due to the small quantity of the liquid in each vial, this MSDS has been prepared to address potential flammability and health hazards should a large quantity of fluid be released from a large quantity of vials at the same time.

EU LABELING/CLASSIFICATION: As an Article, this product does not meet the definition of any hazard class as defined by the European Union Council Directives. The fluid in the vials meets the definition of Toxic as defined by the European Union Council Directive 67/548/EEC or subsequent Directives.

EU CLASSIFICATION: Carcinogenic Category 2: T [Toxic]

EU RISK PHRASES: R: 45 [May cause cancer.]; R: 65 [Harmful; may cause lung damage if swallowed.]

CHEMICAL NAME	CAS #	EINECS #	% w/w	EU CLASSIFICATION FOR COMPONENTS
Petroleum Naphtha, Hydrotreated, Heavy	64742-48-9	265-150-3	Proprietary	Hazard Classification: Carcinogenic Category 2; T [Toxic] Risk Phrases: R: 45; R: 65 Safety Phrases: S: 45; S: 53

NOTE: ALL Canadian WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the CPR. All European Union required information is included.

See Section 16 for full text of Ingredient Risk and Safety Phrases

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: Product Description: This product is a clear, light yellow liquid, with an odor characteristic of naphtha that is contained inside a clear, sealed vial. The volume of the liquid in the vial is 1.4-2.9 mL. **Health Hazards:** Due to containment of the liquid in a sealed vial, exposure via all routes is unlikely unless the vials are cracked or broken. Due to the small volume of liquid contained in the vial, no significant health hazard is anticipated if released. Release of a large quantity of liquids may be harmful if ingested. Prolonged skin contact may cause dermatitis. Inhalation of high concentration of mists or sprays may be irritating and/or cause adverse central nervous system effects. **Flammability Hazards:** This fluid in these vials is combustible. Due to the small volume of liquid in each vial, a significant fire hazard is not anticipated unless a large quantity of vials is involved. If involved in a fire, the fluid can ignite and produce toxic gases and compounds such as carbon oxides. **Reactivity Hazards:** This product presents no reactivity hazard. **Environmental Hazards:** Release of a single vial does not pose a significant hazard to the environment. Release of a large quantity of the liquid may be harmful to contaminated plant, animal, and aquatic life. **Emergency Recommendations:** Emergency responders must wear the personal protective equipment suitable for the situation to which they are responding.

EU LABELING/CLASSIFICATION: As an Article, this product does not meet the definition of any hazard class as defined by the European Union Council Directives. The fluid in the vials meets the definitions of Toxic as defined by the European Union Council Directive 67/548/EEC or subsequent Directives.

EU CLASSIFICATION: Carcinogenic Category 2: T [Toxic]

EU RISK PHRASES: R: 45 [May cause cancer.]; R: 65 [Harmful; may cause lung damage if swallowed.]

3. HAZARD IDENTIFICATION (Continued)

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: Since the fluid in these vials is sealed, exposure via all routes is unlikely. If the vials are cracked or broken, health hazards are minimal due to the small quantity of liquid in each vial (1.4-2.9) mL. In event of exposure to a large quantity of liquid, the most significant routes of exposure are inhalation and contact with skin and eyes. The symptoms of overexposure to the liquid in this event are described below.

INHALATION: Inhalation of the liquid or vapors is unlikely during routine use and handling of this product. In the unlikely event that vapors and liquid of this product are inhaled, irritation of the respiratory system may occur. Symptoms may include coughing, sneezing or brief difficulty in breathing. Inhalation of high concentration of vapors or prolonged inhalation may cause depression of the central nervous system, with symptoms of headache, nausea, vomiting, dizziness and incoordination. Prolonged inhalation exposure to high concentration of vapors can cause visual disturbances.

CONTACT WITH SKIN or EYES: Contact with the liquid in these vials is unlikely during normal use and handling. In the unlikely event that contact with the skin or eyes occurs, the liquid may cause mild irritation to the skin. Prolonged or repeated skin contact may cause dermatitis with symptoms of dry, red, cracked skin. Direct eye contact with the liquid will cause immediate irritation, redness and watering of the eyes. Contact with vapors or mists may cause mild irritation.

SKIN ABSORPTION: The liquid can be absorbed via intact skin. Repeated exposure via skin absorption may cause adverse effects to the kidneys.

INGESTION: Ingestion is not anticipated to be a likely route of occupational exposure to this product. In the unlikely event that ingestion does occur, irritation of the mouth, throat, esophagus, and other tissues of the digestive system may occur. If large quantity of the liquid is ingested, symptoms of such over-exposure can include nausea, vomiting, diarrhea and depression of the central nervous system. Ingestion of this liquid can lead to aspiration into the lungs should vomiting occur. Aspiration into the lungs can cause chemical pneumonia and pulmonary edema and may be fatal.

INJECTION: In the unlikely event that the liquid is injected into the skin (as may occur if skin is punctured by a contaminated object) irritation in addition to the wound may occur.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms. In the event of overexposure, the following symptoms may be observed:

ACUTE: Acute exposure to the liquid in this product is unlikely unless the sealed vials are cracked or broken. Exposure to small quantities of the liquid is not likely to cause significant health effects by any route of exposure. Eye contact with the liquid will cause irritation. Inhalation of a high concentration of vapors or mists may cause respiratory irritation and adverse effects on the central nervous system. Ingestion of large quantities may be harmful and may lead to aspiration into the lungs.

CHRONIC: Repeated skin contact with the liquid may cause dermatitis (dry, red, scaly skin). Repeated inhalation exposure may cause adverse effects to the respiratory system.

TARGET ORGANS: IN EVENT OF EXPOSURE TO THE LIQUID: ACUTE: Skin, eyes, gastrointestinal system. CHRONIC: Skin, respiratory system.

PART II What should I do if a hazardous situation occurs?

4. FIRST-AID MEASURES

Contaminated individuals must be taken for medical attention if any adverse effects occur. Rescuers should be taken for medical attention if necessary. Take a copy of label and MSDS to health professional with the contaminated individual.

SKIN EXPOSURE: If the liquid contaminates the skin, immediately begin decontamination with copious amounts of running water. Minimum flushing is for 15 minutes. Remove exposed or contaminated clothing, taking care not to contaminate eyes. The contaminated individual must seek immediate medical attention if any adverse health effect continues after flushing.

EYE EXPOSURE: If liquid enters the eyes, open the contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have the contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Contact medical personnel if adverse effect persists after flushing.

INHALATION: If mists or sprays of the liquid are inhaled, remove the contaminated individual to fresh air. If necessary, use artificial respiration to support vital functions. Remove or cover gross contamination to avoid exposure to rescuers. The contaminated individual should seek immediate medical attention if any adverse effects occur.

FOR FLUID IN VIALS

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD	(BLUE)		1
FLAMMABILITY HAZARD	(RED)		2
PHYSICAL HAZARD	(ORANGE)		0
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8

For Routine Industrial Use and Handling Applications

Hazard Scale: **0** = Minimal **1** = Slight **2** = Moderate
3 = Serious **4** = Severe * = Chronic hazard

4. FIRST-AID MEASURES (Continued)

INGESTION: If the liquid in this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Have victim rinse mouth with water or drink several cupfuls of water, if conscious. Never induce vomiting or give a diluent (e.g., water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting respiratory problems, dermatitis, and other skin disorders may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: 49°C (140°F)

AUTOIGNITION TEMPERATURE: 349-350.4°C (660-689°F)

FLAMMABLE LIMITS (in air by volume, %):


Lower (LEL): 0.6% @ 77°C
Upper (UEL): 7.0% @ 77°C

FIRE EXTINGUISHING MATERIALS:

Water Spray: YES	Carbon Dioxide: YES
Foam: YES	Dry Chemical: YES
Halon: YES	Other: Any "ABC" Class.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product is a combustible liquid. If involved in a fire, this product can decompose and produce irritating and toxic materials such as oxides of carbon.

NFPA RATING



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe

Explosion Sensitivity to Mechanical Impact: Not sensitive.
Explosion Sensitivity to Static Discharge: May be sensitive. In event of a release of large volume of the liquid, formation of an explosive air/vapor mixture.

SPECIAL FIRE-FIGHTING PROCEDURES: Structural fire-fighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. Water fog or spray can also be used by trained fire-fighters to disperse this product's vapors and to protect personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. Rinse contaminated equipment thoroughly before returning such equipment to service.

6. ACCIDENTAL RELEASE MEASURES

RELEASE RESPONSE: In case of a release, clear the affected area and protect people. Appropriately trained personnel in proper personal protective equipment should respond to uncontrolled releases using pre-planned procedures. The proper personal protective equipment for incidental releases (e.g., single vial) should be rubber gloves and goggles. For large spills, eliminate all sources of ignition before cleanup begins. Use non-sparking tools. In the event that cleanup will generate excessive splashes, a face-shield, and body protection should also be worn. In the event of a non-incident release (e.g., several gallons released in a poorly ventilated area), minimum Personal Protective Equipment should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), Tyvek or other appropriate body protection and boots, hard-hat, and Self-Contained Breathing Apparatus. Absorb spilled liquid with non-combustible absorbent materials. Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations or those of Canada and its Provinces and EU Member States (see Section 13, Disposal Considerations).

PART III How can I prevent hazardous situations from occurring?

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors or mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: All employees who handle this material should be trained to handle it safely. Keep away from heat, sparks, and other sources of ignition. Use non-sparking tools. Open containers slowly on a stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers. Storage areas should be made of fire resistant materials. Have appropriate extinguishing equipment in the storage area (e.g., sprinkler system, portable fire extinguishers). Keep container tightly closed when not in use. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Refer to NFPA 30, *Flammable and Combustible Liquids Code* for additional information on storage.

7. HANDLING and STORAGE (Continued)

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely, if necessary. Collect all rinsates and dispose of according to applicable U.S. Federal, State, and local procedures or appropriate Canadian standards and those of the European Union and its member states.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: None normally needed.

EXPOSURE LIMITS/GUIDELINES:

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR						
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELs		OTHER
		TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³	IDLH mg/m ³
Petroleum Naphtha, Hydrotreated, Heavy Exposure limits are for VM & P Naphtha	64742-48-9	1370	NE	1350 (vacated 1989 PEL)	1800 (vacated 1989 PEL)	350	1800 (ceiling) 15 minutes	NE Exxon OEL: TWA = 300 ppm Carcinogen: TLV-A3

NE = Not Established.

See Section 16 for Definitions of Terms Used.

INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS: Currently, there are no international exposure limits are established for components of this product.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), equivalent standards of Canada (including CSA Standard Z94.4-02 and CSA Standard Z94.3-02), standards of EU member states (including EN 529:2005 for respiratory PPE, CEN/TR 15419:2006 for hand protection, and CR 13464:1999 for face/eye protection). Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: None needed under normal conditions of use and handling. Maintain airborne contaminant concentrations below exposure limits listed above if applicable. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian CSA Standard Z94.3-02, or the European Standard CR 13464:1999. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

EYE PROTECTION: None needed under normal use and handling. Wear safety goggles if mists, sprays or other particulates are present. If necessary refer to U.S. OSHA 29 CFR 1910.133, Canadian CSA Standard Z94.3-02, or the European Standard CR 13464:1999.

HAND PROTECTION: None needed under normal conditions of use and handling. Wear appropriate glove for work being done. Resistance of specific materials can vary from product to product. Evaluate resistance under conditions of use and maintain gloves carefully. Use triple gloves for spill response, as stated in Section 6 (Accidental Release Measures) of this MSDS. If necessary, refer to U.S. OSHA 29 CFR 1910.138, appropriate Standards of Canada and the European Standard CEN/TR 15419:2006.

BODY PROTECTION: Use body protection appropriate for task. Full-body chemical protective clothing is recommended for emergency response procedures. If necessary, refer to the OSHA Technical Manual (Section VII: Personal Protective Equipment) appropriate Standards of Canada, or the European Standard CEN/TR 15419:2006. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136 and the Canadian CSA Standard Z195-02, *Protective Footwear*.

9. PHYSICAL and CHEMICAL PROPERTIES

The following values are for the liquid in the vials:

POUR POINT: <-18°C (< 0°F)

RELATIVE VAPOR DENSITY (air = 1): > 5.0

SPECIFIC GRAVITY (water = 1): 0.76

SOLUBILITY IN WATER: < 0.1%

SOLUBILITY IN ORGANIC SOLVENTS: 100%

VAPOR PRESSURE @ 20°C: ~0.78 mmHg

MOLECULAR FORMULA: Not available.

ODOR THRESHOLD: Not applicable.

APPEARANCE, ODOR AND COLOR: This product is a clear, light yellow liquid, with an odor characteristic of petroleum naphthalate that is contained inside a clear, sealed vial.

HOW TO DETECT THIS SUBSTANCE IN EVENT OF ACCIDENTAL SPILL (warning properties): The odor and color may be a method of identification in event the fluid is spilled.

VOLATILITY: 100%

EVAPORATION RATE (n-BuAc = 1): 0.1

MELTING/FREEZING POINT: < -62.73°(< -81°F)

BOILING POINT: 169-193°C (336-379°F)

VISCOSITY [dynamic] @ 25°C: 1.29 cP

pH: Not available.

MOLECULAR WEIGHT: Unspecified

DECOMPOSITION TEMPERATURE: 349-350.4°C (660-689°F)

10. STABILITY and REACTIVITY

STABILITY: Normally stable.

DECOMPOSITION PRODUCTS: Thermal decomposition of this product can produce oxides of carbon.

10. STABILITY and REACTIVITY (Continued)

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: The vial fluid is not compatible with strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid exposure to or contact with light, extreme temperatures, and incompatible chemicals.

PART IV Is there any other useful information about this material?

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: Currently, the following toxicity data are available for the Petroleum Naphtha, Hydrotreated, Heavy component:

LD₅₀ (Oral-Rat) > 5000 mg/kg

LD₅₀ (Skin-Rabbit) > 2000 mg/kg

LD₅₀ (Skin-Rabbit) > 316 gm/kg

SUSPECTED CANCER AGENT: The full range naphthas are listed by agencies tracking the carcinogenic potential of chemical compounds, as follows: ACGIH TLV-A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans) This component is not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, and CAL/OSHA and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies.

IRRITANCY OF PRODUCT: The fluid in the vials may be mildly irritating to the eyes. Prolonged or repeated skin contact may dermatitis.

SENSITIZATION TO THE PRODUCT: No information is available on human skin or respiratory sensitization.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of this material on the human reproductive system.

Mutagenicity: The components of this product are not reported to cause mutagenic effects in humans.

Embryotoxicity: The components of this product are not reported to cause embryotoxic effects in humans.

Teratogenicity: The components of this product are not reported to cause teratogenic effects in humans.

Reproductive Toxicity: The components of this product are not reported to cause reproductive effects in humans.

A mutagen is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance that interferes in any way with the reproductive process.

ACGIH BIOLOGICAL EXPOSURE INDICES: Currently, there are no ACGIH Biological Exposure Indices (BEIs) determined for the components of this product.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: Hydrocarbons present in Hydrotreated naphthas such as present in the vial fluid are not susceptible to hydrolysis under environmental conditions. Hydrotreated naphthas are not readily biodegradable in non-adapted, activated domestic sludge. At a concentration of 2 mg/L these substances biodegraded 10% after 28 days.

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Log Pow = 2.1-6.0 (calc.)

EFFECT OF MATERIAL ON PLANTS or ANIMALS: Not tested. Large quantities of the vial fluid may be acutely harmful to contaminated plant and animal life.

EFFECT OF CHEMICAL ON AQUATIC LIFE: Aquatic toxicity data are available for the Petroleum Naphtha, Hydrotreated Heavy :

LC₅₀ (*Pimephales promelas* fathead minnow) 96 hours = 2200 mg/L

LC₅₀ (*Crangon crangon*) 96 hours = 4.3 mg/L

LC₅₀ (*Chaetogammarus marinus*) 96 hours = 2.6 mg/L

NOEL (*Chaetogammarus marinus*) 96 hours = 32 mg/L

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or with regulations of Canada. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

U.S. EPA WASTE NUMBER: Wastes of the vial fluid should be tested to see if they meet the criteria for D001 (Waste-Characteristic Flammability).

EUROPEAN EWC CODE: Wastes Not Otherwise Specified: 16 10 99

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION 49 CFR 172.101: The fluid in these vials is NOT classified as Dangerous Goods, per DOT regulations.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: The fluid in these vials is NOT classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): The fluid in these vials is NOT classified as dangerous goods under rules of IATA.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: The fluid in these vials is NOT classified as Dangerous Goods by the International Maritime Organization.

14. TRANSPORTATION INFORMATION (Continued)

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD

(ADR): The fluid in these vials is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: Components of this product are on the TSCA Inventory.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): The components of this product are not on the California Proposition 65 lists.

LABELING (Precautionary Statements) ANSI LABELING (Z129.1): These are manufactured articles; no label information is required under OSHA 29 CFR 1910.1200 or ANSI Z400.1 to address the chemical hazards.

ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: The Petroleum Naphtha, Hydrotreated Heavy component of this product is on the DSL Inventory.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: The components of this product are not on the CEPA Priority Substances Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Not applicable for sealed vials.

For the fluid in the vials: Class B3 (Combustible Liquid)



EUROPEAN UNION INFORMATION:

EU LABELING/CLASSIFICATION: As an Article, this product does not meet the definition of any hazard class as defined by the European Union Council Directives. The fluid in the vials meets the definition of Toxic as defined by the European Union Council Directive 67/548/EEC or subsequent Directives.

EU CLASSIFICATION: Carcinogenic Category 2: T [Toxic]

EU RISK PHRASES: R: 45 [May cause cancer.]; R: 65 [Harmful; may cause lung damage if swallowed.]

EU SAFETY PHRASES: [S: 45]: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). [S: 53]: Avoid exposure - obtain special instructions before use.

EUROPEAN UNION ANNEX II HAZARD SYMBOL: Carcinogenic Category 2: T [Toxic]



16. OTHER INFORMATION

PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.
PO Box 36519, La Mesa, CA 91944-3519
(800) 441-3365

DATE OF PRINTING:

June 28, 2007

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Stanley Works assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Stanley Works assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on an MSDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAK Germ Cell Mutagen Categories: **1:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances which have been shown to induce genetic damage in germ cells of human animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances which are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but which are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH-Immediately Dangerous to Life and Health: This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

MAK: Federal Republic of Germany Maximum Concentration Values in the workplace.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL-Permissible Exposure Limit: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule ([Federal Register](#): 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL-Short Term Exposure Limit: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV-Threshold Limit Value: An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA-Time Weighted Average: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD:

0 (Minimal Hazard): No significant health risk, irritation of skin or eyes not anticipated. **Skin Irritation:** Essentially non-irritating. PII or Draize = "0". **Eye Irritation:** Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. Draize = "0". **Oral Toxicity LD₅₀ Rat:** < 5000 mg/kg. **Dermal Toxicity LD₅₀ Rat or Rabbit:** < 2000 mg/kg. **Inhalation Toxicity 4-hrs LC₅₀ Rat:** < 20 mg/L; **1 (Slight Hazard):** Minor reversible injury may occur; slightly or mildly irritating. **Skin Irritation:** Slightly or mildly irritating. **Eye Irritation:** Slightly or mildly irritating. **Oral Toxicity LD₅₀ Rat:** > 500-5000 mg/kg. **Dermal Toxicity LD₅₀ Rat or Rabbit:** > 1000-2000 mg/kg. **Inhalation Toxicity LC₅₀ 4-hrs Rat:** > 2-20 mg/L; **2 (Moderate Hazard):** Temporary or transitory injury may occur. **Skin Irritation:** Moderately irritating; primary irritant; sensitizer. PII or Draize > 0, < 5. **Eye Irritation:** Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. Draize > 0, ≤ 25. **Oral Toxicity LD₅₀ Rat:** > 50-500 mg/kg. **Dermal Toxicity LD₅₀ Rat or Rabbit:** > 200-1000 mg/kg. **Inhalation Toxicity LC₅₀ 4-hrs Rat:** > 0.5-2 mg/L; **3 (Serious Hazard):** Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

HEALTH HAZARD (continued):

3 (continued): Skin Irritation: Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns, dermal necrosis. PII or Draize > 5-8 with destruction of tissue. **Eye Irritation:** Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. **Oral Toxicity LD₅₀ Rat:** > 1-50 mg/kg. **Dermal Toxicity LD₅₀ Rat or Rabbit:** > 20-200 mg/kg. **Inhalation Toxicity LC₅₀ 4-hrs Rat:** > 0.05-0.5 mg/L; **4 (Severe Hazard):** Life-threatening; major or permanent damage may result from single or repeated exposure. **Skin Irritation:** Not appropriate. Do not rate as a "4", based on skin irritation alone. **Eye Irritation:** Not appropriate. Do not rate as a "4", based on eye irritation alone. **Oral Toxicity LD₅₀ Rat:** ≤ 1 mg/kg. **Dermal Toxicity LD₅₀ Rat or Rabbit:** ≤ 20 mg/kg. **Inhalation Toxicity LC₅₀ 4-hrs Rat:** ≤ 0.05 mg/L.

FLAMMABILITY HAZARD:

0 (Minimal Hazard): Materials that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.; **1 (Slight Hazard):** Materials that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, Including: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.]; **2 (Moderate Hazard):** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, Including: Liquids having a flash-point at or above 37.8°C [100°F]; Solid materials in the form of coarse dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); **3 (Serious Hazard):** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] (e.g. OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides.]; **4 (Severe Hazard):** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] (e.g. OSHA Class IA; Material that ignites spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric]).

PHYSICAL HAZARD:

0 (Water Reactivity): Materials that do not react with water. **Organic Peroxides:** Materials that are normally stable, even under fire conditions and will not react with water. **Explosives:** Substances that are Non-Explosive. **Unstable Compressed Gases:** No Rating. **Pyrophorics:** No Rating. **Oxidizers:** No "0" rating allowed. **Unstable Reactives:** Substances that will not polymerize, decompose, condense or self-react.); **1 (Water Reactivity):** Materials that change or decompose upon exposure to moisture. **Organic Peroxides:** Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. **Explosives:** Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. **Compressed Gases:** Pressure below OSHA definition. **Pyrophorics:** No Rating. **Oxidizers:** Packaging Group III; **Solids:** any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. **Liquids:** any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. **Unstable Reactives:** Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors.); **2 (Water Reactivity):** Materials that may react violently with water. **Organic Peroxides:** Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. **Explosives:** Division 1.4 – Explosive substances where the explosive effect are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. **Compressed Gases:** Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. **Pyrophorics:** No Rating. **Oxidizers:** Packing Group II **Solids:** any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. **Liquids:** any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chloride solution (40%)/cellulose mixture and the criteria for Packing Group I are not met.

DEFINITIONS OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

PHYSICAL HAZARD (continued):

2 (continued): Unstable Reactives: Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature); **3 (Water Reactivity:** Materials that may form explosive reactions with water. **Organic Peroxides:** Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or materials that react explosively with water. **Explosives:** Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. **Compressed Gases:** Pressure \geq 514.7 psi absolute at 21.1°C (70°F) [500 psig]. **Pyrophorics:** No Rating. **Oxidizers:** Packing Group I **Solids:** any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. **Liquids:** Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. **Unstable Reactives:** Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.); **4 (Water Reactivity:** Materials that react explosively with water without requiring heat or confinement. **Organic Peroxides:** Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. **Explosives:** Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. **Compressed Gases:** No Rating. **Pyrophorics:** Add to the definition of Flammability '4'. **Oxidizers:** No "4" rating. **Unstable Reactives:** Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion.).

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 (materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 2000 mg/kg. Materials that are essentially non-irritating to the respiratory tract, eyes and skin. **1** (materials that, under emergency conditions, can cause significant irritation): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 10 mg/L but less than or equal to 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 500 mg/kg but less than or equal to 2000 mg/kg. Materials that cause slight to moderate irritation to the respiratory tract, eyes and skin. **2** (materials that, under emergency conditions, can cause temporary incapacitation or residual injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 3,000 ppm but less than or equal to 5,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 2 mg/L but less than or equal to 10 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 200 mg/kg but less than or equal to 1000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. **Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure.** Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lacrymators. Materials that are primary skin irritants or sensitizers. **3** (materials that, under emergency conditions, can cause serious or permanent injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 1,000 ppm but less than or equal to 3,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 5 mg/kg but less than or equal to 50 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. **Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause frostbite and irreversible tissue damage.** Materials that are respiratory irritants. Cryogenic gases that cause frostbite and irreversible tissue damage. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials that are corrosive to the skin. **4** (materials that, under emergency conditions, can be lethal): Gases and vapors whose LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand: Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. Liquids, solids and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the Method of Testing for Sustained Combustibility, per 49 CFR 173, Appendix H or the UN Recommendation on the Transport of Dangerous Goods, Model Regulations (current edition) and the related Manual of Tests and Criteria (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85 percent by weight. Liquids that have no fire point when tested by ASTM D 92 Standard Test Method for Flash and Fire Points by Cleveland Open Cup, up to a boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed up flash point of the solvent. Most ordinary combustible materials. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air: Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures in air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that, on account of their physical form or environmental conditions, can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with a representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily: Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures.

DEFINITIONS OF TERMS (Continued)

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

FLAMMABILITY LIMITS IN AIR: Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point** - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. **Autoignition Temperature:** The minimum temperature required to initiate combustion in air with no other source of ignition. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

ECOLOGICAL INFORMATION:

EC is the effect concentration in water. **BCF** = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. **TL_m** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K_{ow}** or **log K_{oc}** and is used to assess a substance's behavior in the environment.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TD_{Lo}**, the lowest dose to cause a symptom and **TCL_o** the lowest concentration to cause a symptom; **TD_o**, **LD_{Lo}**, and **LD_o**, or **TC**, **T_{Co}**, **LCL_o**, and **L_{Co}**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REGULATORY INFORMATION:

U.S. and CANADA:

ACGIH: American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. **Occupational Safety and Health Administration (OSHA)**. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration.