

SAFETY DATA SHEET

5533

Section 1. Identification

Product name : KRYLON® COLORmaxx™
Gloss Purple

Product code : 5533

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against
Paint or paint related material.

Manufacturer : Krylon Products Group
101 W. Prospect Avenue
Cleveland, OH 44115

Emergency telephone number of the company : US / Canada: (216) 566-2917
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number : US / Canada: (800) 457-9566
Mexico: Not Available

Transportation Emergency Telephone Number : US / Canada: (216) 566-2917
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 17% (oral), 17% (dermal), 18.6% (inhalation)

GHS label elements

Hazard pictograms :



Signal word : Danger

Date of issue/Date of revision : 5/17/2024

Date of previous issue : 4/19/2024

Version : 23

1/20

5533

KRYLON® COLORmaxx™
Gloss Purple

SHW-85-NA-GHS-US

Section 2. Hazards identification

- Hazard statements** : Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May damage fertility or the unborn child.
- Precautionary statements**
- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Avoid breathing dust or mist. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Pressurized container: Do not pierce or burn, even after use.
- Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
- Hazards not otherwise classified** : DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.
- CAS number/other identifiers**

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
Acetone	≥25 - ≤50	67-64-1
Propane	≥10 - ≤25	74-98-6
Butane	≤10	106-97-8
n-Butyl Acetate	≤10	123-86-4
2-Propoxyethanol	≤3	2807-30-9
2-methoxy-1-methylethyl acetate	≤3	108-65-6
Titanium Dioxide	≤1	13463-67-7
Zirconium 2-Ethylhexanoate	≤0.3	22464-99-9
Light Aromatic Hydrocarbons	≤0.3	64742-95-6
Methyl Ethyl Ketoxime	≤0.3	96-29-7
Cobalt 2-Ethylhexanoate	≤0.3	136-52-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.

Section 4. First aid measures

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
 - carbon dioxide
 - carbon monoxide
 - nitrogen oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Remark** : Flammable aerosol.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Acetone	67-64-1	ACGIH TLV (United States, 7/2023). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. NIOSH REL (United States, 10/2020). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours.
Propane	74-98-6	NIOSH REL (United States, 10/2020). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. ACGIH TLV (United States, 7/2023). Oxygen Depletion [Asphyxiant]. Explosive potential.
Butane	106-97-8	NIOSH REL (United States, 10/2020). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 7/2023). [Butane] Explosive potential. STEL: 1000 ppm 15 minutes.
n-Butyl Acetate	123-86-4	NIOSH REL (United States, 10/2020). TWA: 150 ppm 10 hours.

Date of issue/Date of revision

: 5/17/2024

Date of previous issue

: 4/19/2024

Version : 23

6/20

5533

KRYLON® COLORmaxx™
Gloss Purple

SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

<p>2-Propoxyethanol 2-methoxy-1-methylethyl acetate</p> <p>Titanium Dioxide</p> <p>Zirconium 2-Ethylhexanoate</p> <p>Light Aromatic Hydrocarbons Methyl Ethyl Ketoxime</p> <p>Cobalt 2-Ethylhexanoate</p>	<p>2807-30-9 108-65-6</p> <p>13463-67-7</p> <p>22464-99-9</p> <p>64742-95-6 96-29-7</p> <p>136-52-7</p>	<p>TWA: 710 mg/m³ 10 hours. STEL: 200 ppm 15 minutes. STEL: 950 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 150 ppm 8 hours. TWA: 710 mg/m³ 8 hours. ACGIH TLV (United States, 7/2023). [Butyl acetates] STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.</p> <p>None. OARS WEEL (United States, 4/2022). TWA: 50 ppm 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 7/2023). TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles ACGIH TLV (United States, 7/2023). [Zirconium and compounds] TWA: 5 mg/m³, (as Zr) 8 hours. STEL: 10 mg/m³, (as Zr) 15 minutes. NIOSH REL (United States, 10/2020). [zirconium compounds] TWA: 5 mg/m³, (as Zr) 10 hours. STEL: 10 mg/m³, (as Zr) 15 minutes. OSHA PEL (United States, 5/2018). [Zirconium compounds] TWA: 5 mg/m³, (as Zr) 8 hours.</p> <p>None. OARS WEEL (United States, 4/2022). Skin sensitizer. TWA: 10 ppm 8 hours. ACGIH TLV (United States, 7/2023). [cobalt and inorganic compounds] Skin sensitizer. Inhalation sensitizer. TWA: 0.02 mg/m³, (as Co) 8 hours.</p>
--	---	---

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
acetone	67-64-1	<p>CA Alberta Provincial (Canada, 3/2023). OEL: 1200 mg/m³ 8 hours. OEL: 1800 mg/m³ 15 minutes. OEL: 500 ppm 8 hours. OEL: 750 ppm 15 minutes.</p> <p>CA British Columbia Provincial (Canada, 8/2023). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes.</p> <p>CA Quebec Provincial (Canada, 7/2023). TWA_{EV}: 250 ppm 8 hours. STEV: 500 ppm 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada,</p>

Section 8. Exposure controls/personal protection

Normal propane	74-98-6	<p>7/2013). STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours. CA Alberta Provincial (Canada, 3/2023). OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2023). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 8/2023). Oxygen Depletion [Asphyxiant]. Explosive potential.</p>
Butane	106-97-8	<p>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential. CA Alberta Provincial (Canada, 3/2023). OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2023). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). [Butane] STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 8/2023). [butane, all isomers] Explosive potential.</p>
n-butyl acetate	123-86-4	<p>STEL: 1000 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). [Butane, All isomers] Explosive potential. STEL: 1000 ppm 15 minutes. CA Alberta Provincial (Canada, 3/2023). OEL: 200 ppm 15 minutes. OEL: 950 mg/m³ 15 minutes. OEL: 150 ppm 8 hours. OEL: 713 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 200 ppm 15 minutes. TWA: 150 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). [butyl acetates, all isomers] STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours. CA British Columbia Provincial (Canada, 8/2023). [butyl acetate, all isomers] STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours. CA Quebec Provincial (Canada, 7/2023). [butyl acetates] STEV: 150 ppm 15 minutes. TWAEV: 50 ppm 8 hours.</p>
2-Propoxyethanol	2807-30-9	<p>CA Ontario Provincial (Canada, 6/2019).</p>

Section 8. Exposure controls/personal protection

Zirconium 2-Ethylhexanoate	22464-99-9	<p>Absorbed through skin. TWA: 110 mg/m³ 8 hours. TWA: 25 ppm 8 hours.</p> <p>CA Alberta Provincial (Canada, 3/2023). [Zirconium and compounds] OEL: 5 mg/m³, (as Zr) 8 hours. OEL: 10 mg/m³, (as Zr) 15 minutes.</p> <p>CA British Columbia Provincial (Canada, 8/2023). [Zirconium and compounds] TWA: 5 mg/m³, (as Zr) 8 hours. STEL: 10 mg/m³, (as Zr) 15 minutes.</p> <p>CA Quebec Provincial (Canada, 7/2023). [Zirconium and compounds] TWA: 5 mg/m³, (as Zr) 8 hours. STEL: 10 mg/m³, (as Zr) 15 minutes.</p> <p>CA Ontario Provincial (Canada, 6/2019). [Zirconium and compounds] STEL: 10 mg/m³, (as Zr) 15 minutes. TWA: 5 mg/m³, (as Zr) 8 hours.</p>
Methyl Ethyl Ketoxime	96-29-7	<p>OARS WEEL (United States, 4/2022). Skin sensitizer. TWA: 10 ppm 8 hours.</p>
Cobalt 2-Ethylhexanoate	136-52-7	<p>CA British Columbia Provincial (Canada, 8/2023). [cobalt and inorganic compounds (inhalable)] Skin sensitizer. Inhalation sensitizer. Notes: No British Columbia exposure limit at this time</p> <p>CA British Columbia Provincial (Canada, 8/2023). [Cobalt and inorganic compounds] Skin sensitizer. Inhalation sensitizer. TWA: 0.02 mg/m³, (as Co) 8 hours. Form: Total</p> <p>CA Quebec Provincial (Canada, 7/2023). [Cobalt elemental, and inorganic compounds] Skin sensitizer. Inhalation sensitizer. TWA: 0.02 mg/m³, (as Co) 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). [Cobalt and inorganic compounds] TWA: 0.02 mg/m³, (as Co) 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). [Cobalt and inorganic compounds] STEL: 0.06 mg/m³, (measured as Co) 15 minutes. TWA: 0.02 mg/m³, (measured as Co) 8 hours.</p>

[Occupational exposure limits \(Mexico\)](#)

Section 8. Exposure controls/personal protection

	CAS #	Exposure limits
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.
n-Butyl Acetate	123-86-4	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.
Zirconium 2-Ethylhexanoate	22464-99-9	NOM-010-STPS-2014 (Mexico, 4/2016). [Circonio y compuestos] TWA: 5 mg/m ³ , (as Zr) 8 hours. STEL: 10 mg/m ³ , (as Zr) 15 minutes.
Cobalt 2-Ethylhexanoate	136-52-7	NOM-010-STPS-2014 (Mexico, 4/2016). [Cobalto y compuestos inorgánicos] TWA: 0.02 mg/m ³ , (as Co) 8 hours.

Biological exposure indices (United States)

Ingredient name	Exposure indices
Acetone	ACGIH BEI (United States, 7/2023) BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
Cobalt 2-Ethylhexanoate	ACGIH BEI (United States, 7/2023) [cobalt and inorganic compounds including cobalt oxides] BEI: 15 µg/l, not combined with tungsten carbide - cobalt [in urine]. Sampling time: end of shift at end of workweek. BEI: Nonquantitative: Biological monitoring should be considered for this compound based on the review; however, a specific BEI® could not be determined due to insufficient data., cobalt with tungsten carbide - cobalt [in urine]. Sampling time: end of shift at end of workweek.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Acetone	Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift.
Cobalt 2-Ethylhexanoate	Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical

Section 8. Exposure controls/personal protection

substances. (Mexico, 6/2012) [cobalt and its compounds]
 BEI: 1 µg/l [Basal level. The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the value; semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], cobalt [in blood]. Sampling time: at the end of the shift at the end of the work week.
 BEI: 15 µg/l [Basal level. The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the value], cobalt [in urine]. Sampling time: at the end of the shift at the end of the work week.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Purple.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability** : Flammable aerosol.
- Lower and upper explosion limit/flammability limit** : Lower: 1.26%
Upper: 15.8%
- Vapor pressure** : 101.3 kPa (760 mm Hg)
- Relative vapor density** : 1.55 [Air = 1]
- Relative density** : 0.74
- Solubility(ies)** :

Media	Result
cold water	Not soluble

- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
- Type of aerosol** : Spray
- Heat of combustion** : 28.022 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetone	LD50 Oral	Rat	5800 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
n-Butyl Acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
2-Propoxyethanol	LD50 Oral	Rat	3089 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
Zirconium 2-Ethylhexanoate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
Light Aromatic Hydrocarbons	LD50 Oral	Rat	8400 mg/kg	-
Methyl Ethyl Ketoxime	LD50 Oral	Rat	930 mg/kg	-
Cobalt 2-Ethylhexanoate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	1.22 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
n-Butyl Acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
2-Propoxyethanol	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750 ug	-
	Skin - Mild irritant	Guinea pig	-	24 hours 1 MI	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 mg	-

Section 11. Toxicological information

Light Aromatic Hydrocarbons	Eyes - Mild irritant	Rabbit	-	ug l 24 hours 100	-
Methyl Ethyl Ketoxime	Eyes - Severe irritant	Rabbit	-	uL 100 uL	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-
Cobalt 2-Ethylhexanoate	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Acetone	Category 3	-	Respiratory tract irritation
n-Butyl Acetate	Category 3	-	Narcotic effects
2-Propoxyethanol	Category 3	-	Narcotic effects
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
Light Aromatic Hydrocarbons	Category 3	-	Respiratory tract irritation
Methyl Ethyl Ketoxime	Category 3 Category 1	-	Narcotic effects upper respiratory tract
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Methyl Ethyl Ketoxime	Category 2	-	blood system

Aspiration hazard

Name	Result
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Section 11. Toxicological information

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 - pain or irritation
 - watering
 - redness
- Inhalation** : Adverse symptoms may include the following:
 - respiratory tract irritation
 - coughing
 - nausea or vomiting
 - headache
 - drowsiness/fatigue
 - dizziness/vertigo
 - unconsciousness
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 - irritation
 - redness
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure



- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. 
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : May damage the unborn child. 
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : May damage fertility.

Section 11. Toxicological information

[Numerical measures of toxicity](#)

[Acute toxicity estimates](#)

Route	ATE value
Oral	157203.06 mg/kg
Dermal	55980.37 mg/kg

Section 12. Ecological information

[Toxicity](#)

Product/ingredient name	Result	Species	Exposure
Acetone	Acute EC50 7200000 µg/l Fresh water	Algae - <i>Selenastrum sp.</i>	96 hours
	Acute LC50 4.42589 ml/L Marine water	Crustaceans - <i>Acartia tonsa</i> - Copepodid	48 hours
	Acute LC50 7460000 µg/l Fresh water	Daphnia - <i>Daphnia cucullata</i>	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - <i>Poecilia reticulata</i>	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - <i>Daphniidae</i>	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
n-Butyl Acetate	Chronic NOEC 5 µg/l Marine water	Fish - <i>Gasterosteus aculeatus</i> - Larvae	42 days
	Acute LC50 32 mg/l Marine water	Crustaceans - <i>Artemia salina</i>	48 hours
Titanium Dioxide	Acute LC50 18000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
Methyl Ethyl Ketoxime	Acute LC50 843000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours

[Persistence and degradability](#)

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
n-Butyl Acetate	-	-	Readily
Light Aromatic Hydrocarbons	-	-	Readily

[Bioaccumulative potential](#)

Product/ingredient name	LogP _{ow}	BCF	Potential
Zirconium 2-Ethylhexanoate	-	2.96	Low
Light Aromatic Hydrocarbons	-	10 to 2500	High
Methyl Ethyl Ketoxime	-	2.5 to 5.8	Low
Cobalt 2-Ethylhexanoate	-	15600	High

[Mobility in soil](#)

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Emergency schedules F-D, S-U Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Section 14. Transport information

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

- Australia inventory (AIIIC):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (CSCL):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory (KECI):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Thailand inventory:** Not determined.
- Turkey inventory:** Not determined.
- Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		4
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	On basis of test data On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

History

Date of printing : 5/17/2024

Date of issue/Date of revision : 5/17/2024

Date of previous issue : 4/19/2024

Version : 23

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

▣ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

