

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name:	Blend Stick - All Colors	Revision Date:	4/12/2022
Product UPC Number:	070798040809, 070798040830, 070798040854, 070798041011, 070798041028, 070798041035	Supercedes Date:	12/29/2021
Manufacturer:	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723	Product Use/Class: SDS No:	Wood Putty 3010101
	888-327-8477 (non - emergency matters)	Preparer:	Regulatory and Environmental Affairs
	SDS Coordinator: MSDS@dap.com		, mano
	Emergency Telephone:		
	Transportation: 1-800-535 -5053		
	1-352-323-3500		
	Poison Control: 1-800-222-1222		

2. Hazards Identification

EMERGENCY OVERVIEW: Under normal use conditions, this product is not expected to cause adverse health effects.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word Not a hazardous substance or mixture.

Possible Hazards

74% of the mixture consists of ingredients of unknown acute toxicity

3. Composition/Information on Ingredients

SAP Number:

<u>Chemical Name</u>	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
Microcrystalline wax	CASRN NOT AVAILABLE	30-60	No Information	No Information
Tall oil, polymer with maleic anhydride and pentaerythritol	68512-86-7	10-30	No Information	No Information
Hydrogenated soybean oil	8016-70-4	10-30	No Information	No Information
Petroleum wax	CASRN NOT AVAILABLE	10-30	No Information	No Information
Oxidized ethene homopolymer	68441-17-8	10-30	No Information	No Information
Bone black	8021-99-6	7-13	No Information	No Information
Carnauba Wax	CASRN NOT AVAILABLE	7-13	No Information	No Information
Stearic acid	57-11-4	7-13	No Information	No Information
Polyethylene	9002-88-4	5-10	No Information	No Information
1-Hexadecanol	36653-82-4	3-7	GHS06	H330
Stearyl alcohol	112-92-5	3-7	No Information	No Information
Ethene, homopolymer, oxidized, potassium salt	68441-73-6	3-7	No Information	No Information
Talc (non-asbestiform)	14807-96-6	1-5	No Information	No Information
Umber	12713-03-0	1-5	No Information	No Information
C.I. pigment yellow 42	51274-00-1	1-5	No Information	No Information
Barium sulfate	7727-43-7	1-5	GHS07	H312
Magnesite	546-93-0	0.5-1.5	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: No health hazards are known to exist. In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Use in well ventilated area. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling.

STORAGE: Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Expos Chemical Name	ure Limits ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
Microcrystalline wax Tall oil, polymer with maleic anhydride and pentaerythritol	N.E. N.E.	N.E. N.E.	N.E. N.E.	N.E. N.E.
Hydrogenated soybean oil Petroleum wax	N.E. N.E.	N.E. N.E.	N.E. N.E.	N.E. N.E.

SDS Number: 3010101	SAP Nun	nber:	R	evision Date: 4/12/2022
Oxidized ethene homopolymer Bone black Carnauba Wax Stearic acid	N.E. N.E. 10 mg/m3 TWA inhalable particulate matter Stearates, 3 mg/m3 TWA respirable particulate matter Stearates	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.
Polyethylene 1-Hexadecanol Stearyl alcohol Ethene, homopolymer, oxidized, potassium salt	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.
Talc (non-asbestiform)	2 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	N.E.	N.E.	N.E.
Umber C.I. pigment yellow 42 Barium sulfate Magnesite	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.	N.E. N.E. N.E. N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Wear gloves with repeated or prolonged use.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: No special protective equipment required.



HYGIENIC PRACTICES: General industrial hygiene practice.

9. Physical and Chemical Properties

Appearance: Odor: Density, g/cm3: Freeze Point, °C: Solubility in Water: Decomposition Temperature, °C: Boiling Range, °C: Minimum Flash Point, °C: Evaporation Rate: Vapor Density: Combustible Dust: Colored Slight 0.88 - 1.01 Not Established Not Established N.A. - N.A. N.A. Not Applicable Not Applicable Does not support combustion Physical State: Odor Threshold: pH: Viscosity (mPa.s): Partition Coeff., n-octanol/water: Explosive Limits, %: Auto-Ignition Temperature, °C Vapor Pressure, mmHg: Flash Method: Flammability, NFPA: Solid Not Established Not Applicable Not Aplicable Not Established N.A. - N.A. Not Established Not Established Not Applicable Non-Flammable

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Not expected to cause skin problems under normal use conditions.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Not expected to cause eye problems under normal use conditions.

EFFECT OF OVEREXPOSURE - INGESTION: Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. If ingested, may cause depressed respiration.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Under normal use conditions, this product is not expected to cause adverse health effects. Constituents of this product include crystalline silica which ,if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 63231-60-7	<u>Chemical Name</u> Microcrystalline wax	<u>Oral LD50</u> ≥5000 mg/kg Rat	<mark>Dermal LD50</mark> ≥3600 mg/kg Rabbit	<u>Vapor LC50</u> N.I.
68512-86-7	Tall oil, polymer with maleic anhydride and pentaerythritol	N.I.	N.I.	N.I.
8016-70-4	Hydrogenated soybean oil	>5000 mg/kg Rat	N.I.	N.I.
64742-43-4	Petroleum wax	>5000 mg/kg Rat	>3600 mg/kg Rabbit	N.I.
68441-17-8	Oxidized ethene homopolymer	>2000 mg/kg Rat	N.I.	N.I.
8021-99-6	Bone black	N.I.	N.I.	N.I.

SDS Number: 3010101 Revision Date: 4/12/2022 SAP Number: N.I. 8015-86-9 Carnauba Wax N.I. N.I. 57-11-4 Stearic acid 4600 mg/kg Rat >2000 mg/kg Rabbit N.I. 9002-88-4 Polyethylene >5000 mg/kg Rat >2000 mg/kg Rabbit >20 mg/L 1-Hexadecanol 5000 mg/kg Rat 8000 mg/kg Rabbit 36653-82-4 >1.5 mg/L Rat 112-92-5 Stearyl alcohol >5000 mg/kg Rat 8000 mg/kg Rabbit N.I. 68441-73-6 Ethene, homopolymer, oxidized, potassium N.I. N.I. N.I. salt 14807-96-6 N.I. N.I. N.I. Talc (non-asbestiform) 12713-03-0 Umber N.I. N.I. N.I. 51274-00-1 C.I. pigment yellow 42 10000 mg/kg Rat N.I. N.I. S~BA~C 364000 mg/kg Rat 2000 mg/kg Rat Barium sulfate N.I. 546-93-0 Magnesite >2000 mg/kg Rat N.I. N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name: DOT Technical Name:	Not Regulated N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

Revision Date:	4/11/20	22	Supersedes Date: 12/29/2021	
Reason for revision:	Substar Substar 01 - Pru 08 - Ex	Substance Hazardous Flag Changed Substance Hazard Threshold % Changed Substance and/or Product Properties Changed in Section(s): 01 - Product Information 08 - Exposure Controls/Personal Protection Substance Regulatory CAS Number Changed		
Datasheet produced HMIS Ratings:	by:	Regulatory Department		
Health:	Flammability:	Reactivity:	Personal Protection:	
1	0	0	х	

VOC Material, g/L: 8

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.10

VOC Actual, Wt/Wt%: 0.8

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H312 Harmful in contact with skin. H330 Fatal if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.