

Skidding



Specially shaped to grab and hold poles and logs for skidding and dragging operations.

Upset forged from round steel to position additional steel at critical stress areas. Points are fine ground to assure long lasting sharpness.

Tong sizes 3/4 and 1 inch are supported by a special Tong Shut. Tong sizes 1 1/4 and 1 1/2 inches use screw pin anchor shackles.

Two configurations are available.



Item #	Material Diameter		Opening Minimum	Opening Maximum	Approx. Weight	Pack
Ring Only		Ring Size				
40005	3/4"	1/2" x 2 1/2"	3 9/16"	16"	7.0 lbs.	3
42315	1"	5/8" x 2 3/4"	4"	20"	12.8 lbs.	3
40225	1"	5/8" x 2 3/4"	4 1/2"	25"	14.3 lbs.	3
40455	1 1/4"	7/8" x 3 1/4"	7"	32"	28.8 lbs.	1
40555	1 1/2"	1" x 4"	8"	36"	48.0 lbs.	1
Swivel Grab		Hook Size				
40004	3/4"	3/8"	3 9/16"	16"	7.9 lbs.	3
42314	1"	3/8"	4"	20"	13.3 lbs.	3
40224	1"	3/8"	4 1/2"	25"	15.3 lbs.	3
40454	1 1/4"	1/2"	7"	32"	29.7 lbs.	1

Warning: Skidding tongs are designed for pulling or dragging. They are not load rated and should not be used for overhead lifting. Do not heat tong points to sharpen them.

