


## **DROP FORGED SWIVELS**

Drop forged steel – all threaded components are heat treated. All swivels are hot galvanized. Jaws (jaw and eye type) supplied with flat head pin and cotter. Vertical loads are based on a safety factor of 5 to 1.




#### EYE AND EYE

| Part    |       |        | Working Load | Weight |         |       |          |              |         |
|---------|-------|--------|--------------|--------|---------|-------|----------|--------------|---------|
| No.     | Size  | Α      | В            | C      | D       | M     | R        | Limit (Tons) | Per 100 |
| 21505 3 | 1/4"  | 1-1/4" | 5/8"         | 3/4"   | 1-1/16" | 5/16" | 2-15/16" | .43          | 20.2    |
| 21510 7 | 5/16" | 1-5/8" | 3/4"         | 1"     | 1-1/4"  | 3/8"  | 3-9/16"  | .63          | 36.5    |
| 21515 2 | 3/8"  | 2"     | 7/8"         | 1-1/4" | 1-1/2"  | 1/2"  | 4-5/16"  | 1.1          | 70      |
| 21520 6 | 1/2"  | 2-1/2" | 1-3/16"      | 1-1/2" | 2"      | 5/8"  | 5-3/8"   | 1.8          | 141     |
| 21525 1 | 5/8"  | 3"     | 1-1/2"       | 1-3/4" | 2-3/8"  | 3/4"  | 6-5/8"   | 2.6          | 249.5   |
| 21530 5 | 3/4"  | 3-1/2" | 1-5/8"       | 2"     | 2-5/8"  | 7/8"  | 7-3/8"   | 3.5          | 413.5   |


### CHAIN





| Part    |       |        | Working Load | Weight |        |         |          |              |         |
|---------|-------|--------|--------------|--------|--------|---------|----------|--------------|---------|
| No.     | Size  | Α      | В            | C      | D      | E       | R        | Limit (Tons) | Per 100 |
| 21705 7 | 1/4"  | 1-1/4" | 5/8"         | 3/4"   | 1/2"   | 1"      | 2-7/16"  | .26          | 14      |
| 21710 1 | 5/16" | 1-5/8" | 3/4"         | 1"     | 5/8"   | 1-1/4"  | 2-15/16" | .46          | 27      |
| 21715 6 | 3/8"  | 2"     | 7/8"         | 1-1/4" | 3/4"   | 1-1/2"  | 3-9/16"  | .62          | 47.5    |
| 21720 0 | 1/2"  | 2-1/2" | 1-1/4"       | 1-1/2" | 1"     | 2"      | 4-9/16"  | 1.1          | 100     |
| 21725 5 | 5/8"  | 3"     | 1-9/16"      | 1-3/4" | 1-1/4" | 2-5/16" | 5-5/8"   | 1.6          | 169     |
| 21730 9 | 3/4"  | 3-1/2" | 1-3/4"       | 2"     | 1-1/2" | 2-3/4"  | 6-1/8"   | 2.0          | 268     |

### JAW AND EYE



|   | Part    |       |        | Working Load | Weight |          |        |       |         |              |         |
|---|---------|-------|--------|--------------|--------|----------|--------|-------|---------|--------------|---------|
|   | No.     | Size  | Α      | В            | C      | N        | K      | P     | R       | Limit (Tons) | Per 100 |
| : | 21605 0 | 1/4"  | 1-1/4" | 5/8"         | 3/4"   | 25/32"   | 15/32" | 1/4"  | 2-1/2"  | .43          | 18.5    |
|   | 21610 4 | 5/16" | 1-5/8" | 3/4"         | 1"     | 27/32"   | 1/2"   | 5/16" | 2-7/8"  | .63          | 35      |
|   | 21615 9 | 3/8"  | 2"     | 7/8"         | 1-1/4" | 1-1/16"  | 5/8"   | 7/16" | 3-1/2"  | 1.1          | 67.5    |
|   | 21620 3 | 1/2"  | 2-1/2" | 1-1/4"       | 1-1/2" | 1-15/32" | 7/8"   | 1/2"  | 4-9/16" | 1.8          | 131     |
|   | 21625 8 | 5/8"  | 3"     | 1-9/16"      | 1-3/4" | 1-17/32" | 1"     | 5/8"  | 5-5/16" | 2.6          | 240     |
|   | 21630 2 | 3/4"  | 3-1/2" | 1-3/4"       | 2"     | 1-3/4"   | 1-1/8" | 3/4"  | 6"      | 3.5          | 360     |

## **SAFETY SWIVEL HOOKS**



Drop forged steel. Hook is heat treated. Latch, spring, machine screw and nut are stainless steel.

| Part    |        |         | Working Load | Weight  |        |         |          |      |              |         |
|---------|--------|---------|--------------|---------|--------|---------|----------|------|--------------|---------|
| No.     | Α      | В       | C            | D       | F      | L       | R        | S    | Limit (Tons) | Per 100 |
| 21905 1 | 2"     | 15/16"  | 1-1/4"       | 2-7/8"  | 7/8"   | 5-9/16" | 4-15/32" | 3/8" | .75          | 91      |
| 21910 5 | 2-1/2" | 1-5/16" | 1-1/2"       | 3-3/16" | 31/32" | 6-5/8"  | 5-9/32"  | 1/2" | 1            | 148     |

# **WESTECH RIGGING S**

Call Toll Free: 800-442-7475 Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific



#### Visit Us Online at: www.WestechRigging.com

4140 West 11th Avenue Eugene, Oregon 97402

2439 McGilchrist St SE Salem, Oregon 97302



