

4 TON KIT (Forged Adapters)
MK4

FEATURES

- Pump gauge included to enable pump user to know tonnage being applied
- "Quick-Lock" design for fast and easy assembly and disassembly
- Long handle provides ease of pumping
- Thick walled extension tubes for added strength and longer life
- Roto-molded plastic case for organized component storage and ease of carrying
- Flexible hydraulic hose with spring guards at both ends
- Forged steel adapters for added strength and durability
- **Kit Weight:** 41 lbs.



CAUTION! **MAX. 50%**

When cylinders are used w/ maintenance set attachments or components, the maximum system pressure must be limited to half the rated pressure (5,000 P.S.I.).

4 Ton Kit Includes:

- PLASTIC CASE
- 10,000 P.S.I. PUMP w/ GAUGE
- 6' HOSE
- 4" STROKE RAM
- WEDGE RAM (1/2 TON CAP.)
- 4", 8", 12" AND 16" EXTENSION TUBES
- TUBE CONNECTOR
- SERRATED SADDLE
- RUBBER HEAD
- WEDGE HEAD
- RAM TOE
- PLUNGER TOE
- RUBBER FACED FLAT BASE
- 90 DEGREE "V" BASE

10 TON KIT (Forged Adapters)
MK10

FEATURES

- All the same features found in the 4 ton kit
- **Kit Weight:** 83 lbs.



10 Ton Kit Includes:

- WHEELED PLASTIC CASE
- 10,000 P.S.I. PUMP w/ GAUGE
- 6' HOSE
- 6" STROKE RAM
- WEDGE RAM (1/2 TON CAP.)
- 5", 10", 14" AND 19" EXTENSION TUBES
- TUBE CONNECTOR
- SERRATED SADDLE
- RUBBER HEAD
- WEDGE HEAD
- 90 DEGREE "V" BASE
- FLAT BASE
- RAM TOE
- PLUNGER TOE

20 TON KIT (Forged Adapters)
MK20

INTENDED USE

A deluxe kit for repairing heavy equipment, industrial machinery, mining equipment and some heavy construction applications.

FEATURES

- Two steel cases with carrying handles share the weight for easier handling of kit
- Two-speed pump w/ gauge quickly raises ram to load and secondary pump provides powerstroke
- Pump gauge included to enable pump user to know tonnage being applied
- **Kit Weight:** 153 lbs.

20 Ton Kit Includes:

- STEEL CASE (1 OF 2)
- 2-SPEED PUMP w/ GAUGE
- 5' HOSE
- RAM, 5" STROKE
- 3-1/2" DIA. SADDLE (2)
- THREADED COUPLER (3)
- TOE LIFT
- WEDGE HEAD
- "V" HEAD
- STEEL CASE (2 OF 2)
- 3" EXTENSION TUBE (2)
- 5" EXTENSION TUBE
- 10" EXTENSION TUBE
- 20" EXTENSION TUBE
- 27-1/2" EXTENSION TUBE
- 6-1/2" DIA. BASE (2)



CAUTION! **MAX. 50%**

When cylinders are used w/ maintenance set attachments or components, the maximum system pressure must be limited to half the rated pressure (5,000 P.S.I.).