



Distributed By

WESTECH RIGGING SUPPLY

Visit Us Online at: www.WestechRigging.com

Call Us Toll Free at: 800-442-7475

Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302

GRADE 30

Proof Coil



CHAIN SIZE	WORKING LOAD LIMIT (LBS)	MAX INSIDE LENGTH	MIN INSIDE WIDTH	APPROXIMATE WEIGHT PER 100 FT (LBS)
3/16"	800	0.98"	0.30"	40
1/4"	1,300	1.24"	0.38"	66
5/16"	1,900	1.29"	0.44"	86
3/8"	2,650	1.38"	0.55"	142
1/2"	4,500	1.79"	0.72"	242
5/8"	6,900	2.20"	0.79"	357
3/4"	10,600	2.76"	0.98"	560

General-purpose, low-carbon chain for industrial and agricultural applications - including guard rails, logging, and load securement. Available in self-colored, zinc-plated and hot dip galvanized finishes. **Not to be used for overhead lifting.**

ALL DIMENSIONS AND WEIGHTS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR VARIATIONS DURING THE MANUFACTURING PROCESS.