



Distributed By

WESTECH RIGGING SUPPLY

Visit Us Online at: www.WestechRigging.com

Call Us Toll Free at: 800-442-7475

Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302

GRADE 70

Transport



CHAIN SIZE	WORKING LOAD LIMIT (LBS)	INSIDE LENGTH	INSIDE WIDTH	APPROXIMATE WEIGHT PER 100 FT (LBS)
1/4"	3,150	0.84"	0.47"	76
5/16"	4,700	1.10"	0.50"	97
*3/8"	6,600	1.38"	0.60"	137
**3/8"	6,600	1.19"	0.55"	154
1/2"	11,300	1.56"	0.73"	270

*Standard Link

**Imported

Transport chain is considered the chain of choice for load binding and tie down applications. It is a heat-treated carbon steel chain that is stronger than both Grade 30 and Grade 43 chains (approximately 20% stronger than Grade 43). Easily identifiable gold color. **Not to be used for overhead lifting.**

ALL DIMENSIONS AND WEIGHTS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR VARIATIONS DURING THE MANUFACTURING PROCESS.