Helical Screw Auger Anchors



Distributed By

Visit Us Online at: www.WestechRigging.com Call Us Toll Free at: 800-442-7475

Eugene, Oregon 97402 2439 McGilchrist St SE Salem, Oregon 97302

Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific

Helix15-4

- •Helix OD: 4"
- •Length: 15"
- •Rod OD: 1/2"
- Finish: Painted Red
- Approx. Dense Soil

Holding Capacity 800 lbs.*

Helix48-6

- •Helix OD: 6"
- •Length: 48"
- •Rod OD: 5/8"
- Finish: Painted Red
- Approx. Dense Soil

Holding Capacity 4,000 lbs.*

Helix8-66

- Helix OD: 8"
- Length: 66"
- Rod OD: 1"
- Finish: Galvanized

Approx. Holding Capacities (see Soil

- Classifications):
- Class 5: 11,000 lbs.
- Class 6: 9,000 lbs.
- Class 7: 6,000 lbs.

Helix30-4

- •Helix OD: 4"
- •Length: 30"
- •Rod OD: 1/2"
- Finish: Painted Red
- •Approx. Dense Soil

Holding Capacity 2,400 lbs.*

Helix4-54

- Helix OD: 4"
- Length: 54"
- Rod OD: 3/4"
- Finish: Galvanized

Approx. Holding Capacities (see Soil

- Classifications):
- Class 5: 4,500 lbs.
- Class 6: 3,000 lbs.
- Class 7: 1,500 lbs.

Helix10-66

- Helix OD: 10"
- Length: 66"
- Rod OD: 1-1/4"
- Finish: Galvanized

Approx. Holding Capacities (see Soil

- Classifications):
- Class 5: 13,000 lbs.
- Class 6: 10,000 lbs.
- Class 7: 7,000 lbs.

- Helix OD: 6
- Finish: Painted Red
- Approx. Dense Soil

Holding Capacity 3,500 lbs *

Helix6-66

- •Helix OD: 6"
- •Length: 66"
- •Rod OD: 3/4"
- Finish: Galvanized

Approx. Holding Capacities (see Soil

- Classifications):
- Class 5: 6,500 lbs.
- Class 6: 5,000 lbs.
- Class 7: 2,500 lbs.

Helix10-96

- Helix OD: 10"
- Length: 96"
- Rod OD: 1-1/4"
- Finish: Galvanized

Approx. Holding Capacities (see Soil

- Classifications):
- Class 5: 13,000 lbs.
- Class 6: 10,000 lbs.
- Class 7: 7,000 lbs.





- •Length: 40"
- •Rod OD: 5/8"









