▼						
			REVISION HISTORY			
		REV.	DESCRIPTION	DATE	APPROVED	
		1	REDRAW & NOTES	9-16-09	AD	
		1	ISSUED FOR CONSTRUCTION	10-13-09	AD	
		2	GENERAL NOTES UPDATES	04-14-22	RL	
(1-1/2") $(1-1/2")$	R 2-1/16''		Ø 1–3/8" DRILL THRU XXX XXX XXXX XX XXX XXX XX XXX XXX	— STAMP SERIAL # AND CAPACITY		

GENERAL NOTES:

- WELDING PER AWS D1. 1.
- ENSURE BASE STRUCTURE IS CAPABLE OF HANDLING FORCES APPLIED BY PADEYE. 2.
- ORIENT PADEYE IN DIRECTION OF SLING TO MINIMIZE SIDE LOAD. 3.
- PADEYE TO BE WELDED USING A MIN. 70 KSI YIELD ELECTRODE. 4
- 5. PADEYE MATERIAL IS GROUP II DESIGNATION AS PER AWS D1. 1.
- 6. FINAL LOAD TEST SHALL BE PERFORMED TO 2.0 X RATED CAPACITY AFTER WELDUP IS COMPLETE.
- 100% MAGNETIC PARTICLE INSPECTION FOR FILLET WELDS AND 100% ULTRASONIC WELD INSPECTION FOR PENETRATION WELDS TO BE 7. COMPLETED AFTER LOAD TEST IN ACCORDANCE WITH ASME SPECIFICATIONS.
- BREAK ALL EDGES AND CORNERS UNLESS OTHERWISE SPECIFIED, CHAMFER EDGES APPROX. 1/8". 8
- 9. THIS PADEYE MEETS OR EXCEEDS ANSI/ASME B30.20 BELOW THE HOOK LIFTING DEVICES REQUIREMENTS.
- 10. COATING SYSTEM SHALL BE COLD GALVANIZED.
- 11. DESIGN TEMP. -20 DEG F TO 150 DEG F.
- 12. REQUEST ALL MTR'S W/ CHEMISTRY, MECHANICAL & TESTING REPORTS.

