

Stainless Steel

SS Quick Link T316



Part #	Trade Size (in)	Working Load Limit (lbs)	Weight Ea (lbs)
LNKQSS1/8	1/8	275	.03
LNKQSS3/16	3/16	400	.05
LNKQSS1/4	1/4	880	.08
LNKQSS5/16	5/16	1,700	.18
LNKQSS3/8	3/8	2,100	.30
LNKQSS1/2	1/2	2,500	.52

SS Spring Snap Link T316



Part #	Trade Size (in)	Working Load Limit (lbs)	Weight Ea (lbs)
LNKSPGSS1/8	1/8	80	.03
LNKSPGSS3/16	3/16	120	.04
LNKSPGSS1/4	1/4	180	.06
LNKSPGSS5/16	5/16	280	.15
LNKSPGSS3/8	3/8	400	.27
LNKSPGSS1/2	1/2	900	.78

Stainless Steel Chain T316



Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Approx Weight per 100 ft (lbs)
1/8	500	2,000	0.25	0.94	25
3/16	930	3,730	0.30	0.98	42
1/4	1,570	6,280	0.30	1.24	65
5/16	2,400	9,600	0.38	1.29	86
3/8	3,550	14,200	0.55	1.38	140
1/2	6,500	26,000	0.62	1.79	260
5/8	9,800	39,200	0.79	2.20	358
3/4	15,000	60,000	0.98	2.85	560

Made with high percentages of nickel, chrome and molybdenum
Not for Overhead Lifting

WESTECH RIGGING SUPPLY

Call Toll Free: 800-442-7475

Call Us or Visit Our Stores:
Monday - Friday, 8:00am - 5:30pm Pacific



Distributed By

Visit Us Online at: www.WestechRigging.com

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302