


**TPXCF – Twin-Path® Extra Covermax® with Check-Fast®**
**Features:**

- The lightest and strongest sling on the market today, and repairable
- Heavy duty bulked nylon, 2 ply, 2 path, outer cover with superior abrasion resistance
- Check-Fast® Inspection Overload Indicators, and optional Fiber Optic Inspection add-on
- Red inner cover provides an early warning safety alert
- 10% the weight of a wire rope sling of comparable length and capacity
- 1% stretch at rated capacity
- Proof tested to 2X rated capacity, Design factor 5 to 1

**How to order:**

- Combine model and length X (\*)

| Part Number |        | Rated Capacities in Lbs. |         |               |               |               | Approx.<br>Weight per foot<br>(bearing to<br>bearing) | Nominal Body<br>Width |
|-------------|--------|--------------------------|---------|---------------|---------------|---------------|-------------------------------------------------------|-----------------------|
| Model       | Length | Vertical                 | Choker  | 90°<br>Basket | 60°<br>Basket | 45°<br>Basket |                                                       |                       |
| TPXCF 1000  | X *    | 10,000                   | 8,000   | 20,000        | 17,320        | 14,140        | .40                                                   | 1.5 - 3"              |
| TPXCF 1500  | X *    | 15,000                   | 12,000  | 30,000        | 25,980        | 21,210        | .45                                                   | 1.5 - 3"              |
| TPXCF 2000  | X *    | 20,000                   | 16,000  | 40,000        | 34,640        | 28,280        | .51                                                   | 1.5 - 3"              |
| TPXCF 2500  | X *    | 25,000                   | 20,000  | 50,000        | 43,300        | 35,350        | .57                                                   | 2.0 - 4"              |
| TPXCF 3000  | X *    | 30,000                   | 24,000  | 60,000        | 51,960        | 42,420        | .71                                                   | 2.0 - 4"              |
| TPXCF 4000  | X *    | 40,000                   | 32,000  | 80,000        | 69,280        | 56,560        | .83                                                   | 2.0 - 4"              |
| TPXCF 5000  | X *    | 50,000                   | 40,000  | 100,000       | 86,600        | 70,700        | 1.14                                                  | 2.5 - 5"              |
| TPXCF 6000  | X *    | 60,000                   | 48,000  | 120,000       | 103,920       | 84,840        | 1.27                                                  | 2.5 - 5"              |
| TPXCF 7000  | X *    | 70,000                   | 56,000  | 140,000       | 121,240       | 98,980        | 1.39                                                  | 2.5 - 5"              |
| TPXCF 8500  | X *    | 85,000                   | 68,000  | 170,000       | 147,220       | 120,190       | 1.65                                                  | 3.0 - 6"              |
| TPXCF 10000 | X *    | 100,000                  | 80,000  | 200,000       | 173,200       | 141,400       | 1.84                                                  | 3.0 - 6"              |
| TPXCF 12500 | X *    | 125,000                  | 100,000 | 250,000       | 216,500       | 176,750       | 2.35                                                  | 4.0 - 8"              |
| TPXCF 15000 | X *    | 150,000                  | 120,000 | 300,000       | 259,800       | 212,100       | 2.66                                                  | 4.0 - 8"              |
| TPXCF 17500 | X *    | 175,000                  | 140,000 | 350,000       | 303,100       | 247,450       | 3.14                                                  | 4.0 - 8"              |
| TPXCF 20000 | X *    | 200,000                  | 160,000 | 400,000       | 346,400       | 282,800       | 3.45                                                  | 5.0 - 10"             |
| TPXCF 25000 | X *    | 250,000                  | 200,000 | 500,000       | 433,000       | 353,500       | 4.07                                                  | 5.0 - 10"             |
| TPXCF 27500 | X *    | 275,000                  | 220,000 | 550,000       | 476,300       | 388,850       | 4.61                                                  | 6.0 - 12"             |
| TPXCF 30000 | X *    | 300,000                  | 240,000 | 600,000       | 519,600       | 424,200       | 4.92                                                  | 6.0 - 12"             |
| TPXCF 40000 | X *    | 400,000                  | 320,000 | 800,000       | 692,800       | 565,600       | 6.54                                                  | 7.0 - 14"             |
| TPXCF 50000 | X *    | 500,000                  | 400,000 | 1,000,000     | 866,000       | 707,000       | 8.15                                                  | 8.0 - 16"             |
| TPXC 60000  | X*     | 600,000                  | 480,000 | 1,200,000     | 1,039,000     | 848,000       | 10.20                                                 | 9.0 - 18"             |

**Note:**

- US Patents found at <https://slingmax.com/patents/>
- Capacities shown include both paths and are for one complete sling
- Sling rating based on fittings of equal or greater capacity
- Conforms to ASME B30.9, Chapter 6, NAVFAC P-307 section 14.7.4.3, and the Cordage Institute Roundsling standard

**⚠ WARNING**

Sling can fail or be damaged, misused or overloaded. Inspect before each use. Damaged sling shall not be used. Use only if trained. Do not exceed the rated capacity. Protect the sling from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperatures over 180°F. DEATH or INJURY can occur from improper maintenance.