Galvanized Cable

All cable is manufactured in accordance with International Standard ASTM A 1023

7 X 7

Weight

per 1000 ft

(lbs)

4.2

7.5

16

28

43

62

83

105

167

236

Breaking

Strength

(lbs)

270480

920

1,700

2,600

3,700

4,800

6,100

9,200

13,100

7 X 19

Weight

per 1000ft

(lbs)

7.5

16

29

45

65

86

110

173

243

360

Breaking

Strength

(lbs)

480

1,050

2,000

2,800

4,200

5,600

7,000

9,800

14,400

19,500

Galvanized Cable

CONSTRUCTION

Diameter

(in.)

3/64

1/16

3/32

1/8

5/32

3/16


7/32

1/4

5/16

3/8

7/16




7 X 7




7 X 19



PVC Coated Galvanized Cable



7 X 7



7 X 19

| i vo ovateu darvanizeu oabie | | | | |
|------------------------------|-----------------------------|-----------------------|-------------------------------|--------------------------------|
| Cable Diameter (in) | Coating Diameter (in) | Cable Construction | Breaking Strength (lbs) | Weight per 1000 ft (lbs) |
| 1/16 | 3/32 | 7 X 7 | 480 | 9 |
| 3/32 | 1/8 | 7 X 7 | 920 | 18 |
| 1/8 | 3/16 | 7 X 7 | 1,700 | 35 |
| 3/16 | 1/4 | 7 X 7 | 3,700 | 74 |
| 1/8 | 3/16 | 7 X 19 | 2,000 | 36 |
| 3/16 | 1/4 | 7 X 19 | 4,200 | 77 |
| 1/4 | 5/16 | 7 X 19 | 7,000 | 123 |
| 5/16 | 3/8 | 7 X 19 | 9,800 | 197 |
| 3/8 | 7/16 | 7 X 19 | 14,400 | 270 |

Other cable and coating sizes available upon request

Galvanized Cable, normally referred to as "aircraft cable", is not intended for aircraft use. It is not certified to MIL-W-83420 because our cable does not go through all the testing requirements, notably the cycle test that is required to be on the federal governments QPL. All other testing and certifications are valid. Mill test certificates are provided upon request.