



Specialty Wire Rope

IMPACT® Swaged offers you

- Longer Service
- Greater Strength
- Greater Flexibility
- Improved Drum Spooling
- Resistance to Drum Crushing
- Resistance to Pig Tailing & Kinking




6X26 IWRC Impact® Swaged

Size (in)	Approx Wt (lbs/ft)	Breaking Strength (lbs)	
		IPS	EIPS
1/2	0.62	34,000	36,800
9/16	0.79	43,200	46,700
5/8	0.97	54,100	58,400
3/4	1.40	76,200	82,400
7/8	1.91	104,000	110,000
1	2.49	136,000	144,000
1+1/8	3.16	165,000	176,000
1+1/4	3.90	206,500	220,000
1+1/2	5.62	292,700	293,000

19X19 IWRC Compacted

Size (in)	Approx Wt (lbs/ft)	Breaking Strength (lbs)	
		IPS	EIPS
1/2	0.510	27,550	29,760
9/16	0.647	34,800	37,500
5/8	0.809	43,600	47,000
11/16	0.968	52,100	56,200
3/4	1.14	61,400	66,300
7/8	1.56	83,700	90,800
1	2.04	109,400	118,000
1+1/8	2.59	138,761	150,000
1+1/4	3.24	173,700	186,000



6X19/37 IWRC Swaged

Size (in)	NORMAL TYPE			SUPER TYPE		
	Approx Weight (lbs/ft)	Breaking Load (lbs)		Approx Weight (lbs/ft)	Breaking Load (lbs)	
		IPS	EIPS		IPS	EIPS
3/8	0.330	16,100	18,500	0.350	17,700	20,400
7/16	0.420	21,100	24,300	0.460	23,100	26,600
1/2	0.550	27,700	31,000	0.610	30,300	34,800
9/16	0.710	34,800	40,000	0.780	38,100	43,800
5/8	0.870	42,600	49,000	0.965	47,000	54,000
11/16	1.05	51,300	59,000	1.16	65,000	74,800
3/4	1.25	60,900	69,000	1.38	67,000	77,000
7/8	1.70	82,600	95,000	1.87	90,400	104,000
1	2.22	107,000	124,000	2.44	115,700	133,000
1-1/8	2.81	133,000	153,000	3.09	138,300	159,000
1-1/4	3.47	161,700	186,000	3.82	169,600	195,000
	4.20	193,000	222,000	4.62	203,500	234,000

- Higher Strength than Standard Ropes
- Greater Durability
- Longer Service
- Resistant to Drum Crushing



Distributed By

WESTECH RIGGING SUPPLY

Visit Us Online at: www.WestechRigging.com

Call Us Toll Free at: 800-442-7475

Call Us or Visit Our Stores: Monday - Friday, 8:00am - 5:30pm Pacific

4140 West 11th Avenue
Eugene, Oregon 97402

2439 McGilchrist St SE
Salem, Oregon 97302

