## **Declaration of Conformity**

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #	B0401174c	Declaration Date	4/1/2022

Tradesman Pro 3D Construction Belted FBH, Large/XLarge, TB Legs/QC Chest

**Additional Items Conforming Under this Declaration:** 

7078CSM SC7078CLX 7078C2X3X SC7078C2X3X SC7078CSM 7078CXS

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

## **ANSI Z359.11-2021**

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1 Level 2 X Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

**Level 2**: FallTech Lab Within the Scope of ISO/IEC Standard 17025:2005 **Level 3**: Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2005

Supporting PC-2537 Documentation

**Authorized Signature** 

Name Zachary Winters Title Engineering Manager Date 4/30/2024

International Accreditation Service, Inc 3060 Saturn St, Ste 100 ACCREDITED Brea, CA 92821 +1 562-364-8201 FallTech Lab - TL-594 ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech





1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-2537	Rpt. Date	4/1/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden   Test Specification(s)   ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				5, 4.3.6		
Part No.	7078CLX			Part No. Re	vision	Α	
Part Description	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest						
Test Request No.	PC-2537 <b>Date Complete</b> 3/30/2022			·			
Test Operator(s)	perator(s) Yesbet Sierra / Jay Sponholz						

Material/Sample Identification				
Sample ID	Description			
6342463	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342475	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342474	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342467	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342469	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342479	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342476	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342477	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342471	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342462	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342465	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342464	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342473	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342472	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			
6342478	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest			

Test Summary							
Test Specification	Tes	st Criteria	Test Result	Pass/Fail			
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3633.7 Lbf	Pass			
ANSI Z359.11-2021	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
4.3.5	Adjuster Slippage	Slippage ≤ 1"	00"	Pass			
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass			
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass			
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	Minute 3640 Lbf				
ANSI Z359.11-2021	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass			
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass			
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass			
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3655.6 Lbf	Pass			
ANSI Z359.11-2021	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass			
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass			
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass			







1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-2537	Rpt. Date	4/1/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden Test Specification(s)			ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	7078CLX			Part No. Re	evision	Α	
Part Description	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest						
Test Request No.	PC-2537			Date Comp	lete	3/30/2022	

Test Summary Continued						
Test Specification	Tes	t Criteria	Test Result	Pass/Fail		
	Static Strength (Side D-rings)	3600 Lbf ≥ 1 Minute	3656.4 Lbf	Pass		
ANSI Z359.11-2021	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass		
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass		
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass		
	Static Strength (Side D-rings)	3600 Lbf ≥ 1 Minute	3672.5 Lbf	Pass		
ANSI Z359.11-2021	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass		
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass		
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass		
	Static Strength (Side D-rings)	3600 Lbf ≥ 1 Minute	3693.7 Lbf	Pass		
ANSI Z359.11-2021	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso  Did Not Release		Pass		
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass		
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass		
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	' 5307 4 l ht			
ANSI Z359.11-2021	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass		
4.3.3	Post Drop Angle	Angle at Rest ≤ 30°	1.7°	Pass		
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass		
	Harness Stretch	Shall Not Exceed 18"	8.3"	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4870.1 Lbf	Pass		
ANSI Z359.11-2021	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass		
4.3.3	Post Drop Angle	Angle at Rest ≤ 30°	2.7°	Pass		
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass		
	Harness Stretch	Shall Not Exceed 18"	9.2"	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4997.6 Lbf	Pass		
ANSI Z359.11-2021	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass		
4.3.3	Post Drop Angle	Angle at Rest ≤ 30°	2.0°	Pass		
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass		
	Harness Stretch	Shall Not Exceed 18"	9.4"	Pass		



## **FallTech Testing Laboratory**

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-2537	Rpt. Date	4/1/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden Test Specification(s) ANSI			ANSI Z35	I Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6		
Part No.	7078CLX			Part No. Re	evision	Α	
Part Description	Tradesman Pro 3D Construction Belted FBH, Large/Xlarge, TB Legs/QC Chest						
Test Request No.	PC-2537			Date Comp	lete	3/30/2022	

Test Summary Continued					
Test Specification	Test	Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact > 3,600 Lbf or 72" Free Fall	72" Free fall 1906.2 Lbf	Pass	
4.3.4	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass	
	Post Drop Angle	Angle at Rest ≤ 30°	1.4°	Pass	
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass	
ANSI Z359.11-2021	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact <u>&gt;</u> 3,600 Lbf or 72" Free Fall	72" Free fall 1682.3 Lbf	Pass	
4.3.4	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass	
	Post Drop Angle	Angle at Rest ≤ 30°	2.3°	Pass	
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass	
ANSI Z359.11-2021	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact > 3,600 Lbf or 72" Free Fall	72" Free fall 1832.6 Lbf	Pass	
4.3.4	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass	
	Post Drop Angle	Angle at Rest ≤ 30°	3.4°	Pass	
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass	
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass	
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass	
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass	

## Conclusion

Based upon the samples provided to the Lab: FallTech P/N 7078CLX Rev. A meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval					
Lab Quality Manager	Jay Sponholz	Date	4/1/2022		