## **Declaration of Conformity**

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

| Declaration # | B0605193 | Declaration Date | 6/5/2023 |
|---------------|----------|------------------|----------|
|---------------|----------|------------------|----------|

Journeyman Flex Retrieval Non-belted FBH UniFit Steel
1D+SD TB Legs QC Chest, w/ Trauma Pack

**Additional Items Conforming Under this Declaration:** 

 7027XS
 70273X
 7027C2X

 7027XL
 7027C
 7027CXS

70272X 7027CXL

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

## Conformity Assessment Method in accordance with ANSI/ISEA 125-2014 Level 1 Level 2 X Level 3

Level 1: FallTech LabLevel 2: FallTech LabLevel 3: Independent 3rd Party LabOutside the Scope ofWithin the Scope ofaccredited toISO/IEC Standard 17025:2005ISO/IEC Standard 17025:2005ISO/IEC Standard 17025:2005

Supporting PC-2850 Documentation

**Authorized Signature** 

Name Zachary Winters Title Engineering Manager Date 6/5/2023

International Accreditation Service, Inc 3060 Saturn St, Ste 100 ACCREDITED Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594 ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech





1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

| FallTech Test Report |  |           |             |           |          |           |  |
|----------------------|--|-----------|-------------|-----------|----------|-----------|--|
| Test Report No.      | PC-2850  | Rpt. Date | 5/30/2023   | Rpt. Rev  |          | Rev Date  |  |
| Report Prepared For  | repared For FallTech   |           |             |           |          |           |  |
| Initiated By         | Zachary Winters <b>Test Specification(s)</b> ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6 |           |             |           | 5, 4.3.6 |           |  |
| Part No.             | 7027   |           | Part No. Re | evision   | Н        |           |  |
| Part Description     | Description Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest   |           |             |           |          |           |  |
| Test Request No.     | PC-2850  |           |             | Date Comp | lete     | 5/26/2023 |  |
| Test Operator(s)     | Yesbet Sierra / Jay Sponh  | nolz      |             |           |          |           |  |

| Material/Sample Identification |  |  |  |  |
|--------------------------------|--|--|--|--|
| Sample ID                      | Description  |  |  |  |
| 6974312                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974304                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974317                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974305                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974296                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974302                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974318                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974333                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974330                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974316                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974300                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974314                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974302                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974296                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |
| 6974305                        | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |  |  |  |

| Test Summary               |                                    |                            |                      |           |  |  |
|----------------------------|------------------------------------|----------------------------|----------------------|-----------|--|--|
| Test Specification         | Те                                 | st Criteria                | Test Result          | Pass/Fail |  |  |
|                            | Static Strength<br>(Dorsal D-ring) | 3600 Lbf ≥ 1 Minute        | 3648.3 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021          | Hold Test Torso                    | Shall Not Release Torso    | Did Not Release      | Pass      |  |  |
| 4.3.5                      | Adjuster Slippage                  | Slippage ≤ 1"              | 0.0"                 | Pass      |  |  |
|                            | Tear Distance (Buckle)             | Shall Not Tear > 1"        | Did Not Tear Through | Pass      |  |  |
|                            | Tearing (Straps)                   | Shall Not Show Any Tearing | Did Not Tear         | Pass      |  |  |
| ANSI Z359.11-2021          | Static Strength<br>(Dorsal D-ring) | 3600 Lbf ≥ 1 Minute        | 3636.2 Lbf           | Pass      |  |  |
|                            | Hold Test Torso                    | Shall Not Release Torso    | Did Not Release      | Pass      |  |  |
| 4.3.5                      | Adjuster Slippage                  | Slippage < 1"              | 0.0"                 | Pass      |  |  |
|                            | Tear Distance (Buckle)             | Shall Not Tear > 1"        | Did Not Tear Through | Pass      |  |  |
|                            | Tearing (Straps)                   | Shall Not Show Any Tearing | Did Not Tear         | Pass      |  |  |
| ANSI Z359.11-2021<br>4.3.5 | Static Strength<br>(Dorsal D-ring) | 3600 Lbf ≥ 1 Minute        | 3661.6 Lbf           | Pass      |  |  |
|                            | Hold Test Torso                    | Shall Not Release Torso    | Did Not Release      | Pass      |  |  |
|                            | Adjuster Slippage                  | Slippage <u>&lt;</u> 1"    | 0.0"                 | Pass      |  |  |
|                            | Tear Distance (Buckle)             | Shall Not Tear > 1"        | Did Not Tear Through | Pass      |  |  |
|                            | Tearing (Straps)                   | Shall Not Show Any Tearing | Did Not Tear         | Pass      |  |  |





1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

| FallTech Test Report |  |           |           |   |         |           |  |
|----------------------|--|-----------|-----------|---|---------|-----------|--|
| Test Report No.      | PC-2850  | Rpt. Date | 5/30/2023 | Rpt. Rev                                      |         | Rev Date  |  |
| Report Prepared For  | FallTech   |           |           |   |         |           |  |
| Initiated By         | Zachary Winters Test Specification(s)  |           |           | ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6 |         |           |  |
| Part No.             | 7027   |           |           | Part No. Re                                   | evision | Н         |  |
| Part Description     | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |           |           |   |         |           |  |
| Test Request No.     | PC-2850  |           | •         | Date Comp                                     | lete    | 5/26/2023 |  |

|                    | Test Summary Continued                         |                              |                      |           |  |  |
|--------------------|--|------------------------------|----------------------|-----------|--|--|
| Test Specification | Tes  | t Criteria                   | Test Result          | Pass/Fail |  |  |
|                    | Static Strength<br>(Shoulder D-rings)          | 3600 Lbf ≥ 1 Minute          | 3631.4 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021  | Hold Test Torso                                | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.5              | Adjuster Slippage                              | Slippage ≤ 1"                | 0.0"                 | Pass      |  |  |
|                    | Tear Distance (Buckle)                         | Shall Not Tear > 1"          | Did Not Tear Through | Pass      |  |  |
|                    | Tearing (Straps)                               | Shall Not Show Any Tearing   | Did Not Tear         | Pass      |  |  |
|                    | Static Strength<br>(Shoulder D-rings)          | 3600 Lbf ≥ 1 Minute          | 3643.3 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021  | Hold Test Torso                                | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.5              | Adjuster Slippage                              | Slippage ≤ 1"                | 0.0"                 | Pass      |  |  |
|                    | Tear Distance (Buckle)                         | Shall Not Tear > 1"          | Did Not Tear Through | Pass      |  |  |
|                    | Tearing (Straps)                               | Shall Not Show Any Tearing   | Did Not Tear         | Pass      |  |  |
|                    | Static Strength<br>(Shoulder D-rings)          | 3600 Lbf <u>≥</u> 1 Minute   | 3639.7 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021  | Hold Test Torso                                | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.5              | Adjuster Slippage                              | Slippage ≤ 1"                | 0.0"                 | Pass      |  |  |
|                    | Tear Distance (Buckle)                         | Shall Not Tear > 1"          | Did Not Tear Through | Pass      |  |  |
|                    | Tearing (Straps)                               | Shall Not Show Any Tearing   | Did Not Tear         | Pass      |  |  |
|                    | Dynamic Performance Dorsal D-ring (Feet First) | Peak Impact Load  > 3600 Lbf | 4506.4 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021  | Fall Arrest                                    | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.3              | Post Drop Angle                                | Angle at Rest ≤ 30°          | 3.2°                 | Pass      |  |  |
|                    | Impact Indicator                               | One Indicator Shall Deploy   | Permanently Deployed | Pass      |  |  |
|                    | Harness Stretch                                | Shall Not Exceed 18"         | 10.8"                | Pass      |  |  |
|                    | Dynamic Performance Dorsal D-ring (Feet First) | Peak Impact Load  > 3600 Lbf | 4474.6 Lbf           | Pass      |  |  |
| ANSI Z359.11-2021  | Fall Arrest                                    | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.3              | Post Drop Angle                                | Angle at Rest ≤ 30°          | 2.6°                 | Pass      |  |  |
|                    | Impact Indicator                               | One Indicator Shall Deploy   | Permanently Deployed | Pass      |  |  |
|                    | Harness Stretch                                | Shall Not Exceed 18"         | 11.4"                | Pass      |  |  |
|                    | Dynamic Performance Dorsal D-ring (Feet First) | Peak Impact Load  > 3600 Lbf | . A1/2 8 l hf        |           |  |  |
| ANSI Z359.11-2021  | Fall Arrest                                    | Shall Not Release Torso      | Did Not Release      | Pass      |  |  |
| 4.3.3              | Post Drop Angle                                | Angle at Rest ≤ 30°          | 1.6°                 | Pass      |  |  |
|                    | Impact Indicator                               | One Indicator Shall Deploy   | Permanently Deployed | Pass      |  |  |
|                    | Harness Stretch                                | Shall Not Exceed 18"         | 12.0"                | Pass      |  |  |



## **FallTech Testing Laboratory**

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

| FallTech Test Report |  |           |             |   |      |           |  |
|----------------------|--|-----------|-------------|---|------|-----------|--|
| Test Report No.      | PC-2850  | Rpt. Date | 5/30/2023   | Rpt. Rev                                      |      | Rev Date  |  |
| Report Prepared For  | FallTech   |           |             |   |      |           |  |
| Initiated By         | Zachary Winters Test Specification(s)  |           |             | ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6 |      |           |  |
| Part No.             | 7027   |           | Part No. Re | evision                                       | Н    |           |  |
| Part Description     | Journeyman Flex Retrieval Non-belted FBH UniFit Steel 1D+SD TB Legs QC Chest |           |             |   |      |           |  |
| Test Request No.     | PC-2850  |           | •           | Date Comp                                     | lete | 5/26/2023 |  |

| Test Summary Continued     |   |   |                                     |           |  |  |
|----------------------------|---|---|-------------------------------------|-----------|--|--|
| Test Specification         | Test  | t Criteria  | Test Result                         | Pass/Fail |  |  |
| ANSI Z359.11-2021          | Dynamic Performance<br>Dorsal D-ring (Head First) | Peak Impact > 3,600 Lbf<br>or 72" Free Fall           | 72" Free fall<br>2289.2 Lbf         | Pass      |  |  |
| 4.3.4                      | Fall Arrest                                       | Shall Not Release Torso                               | Did Not Release                     | Pass      |  |  |
|                            | Post Drop Angle                                   | Angle at Rest ≤ 30°                                   | 16.9°                               | Pass      |  |  |
|                            | Impact Indicator                                  | One Indicator Shall Deploy                            | Permanently Deployed                | Pass      |  |  |
| ANSI Z359.11-2021          | Dynamic Performance<br>Dorsal D-ring (Head First) | Peak Impact <u>&gt;</u> 3,600 Lbf<br>or 72" Free Fall | 72" Free fall<br>3374.1 Lbf         | Pass      |  |  |
| 4.3.4                      | Fall Arrest                                       | Shall Not Release Torso                               | Did Not Release                     | Pass      |  |  |
|                            | Post Drop Angle                                   | Angle at Rest ≤ 30°                                   | 10.3°                               | Pass      |  |  |
|                            | Impact Indicator                                  | One Indicator Shall Deploy                            | Permanently Deployed                | Pass      |  |  |
| ANSI Z359.11-2021          | Dynamic Performance Dorsal D-ring (Head First)    | Peak Impact <u>&gt;</u> 3,600 Lbf<br>or 72" Free Fall | 72" Free fall<br>4285.8 Lbf         | Pass      |  |  |
| 4.3.4                      | Fall Arrest                                       | Shall Not Release Torso                               | Did Not Release                     | Pass      |  |  |
|                            | Post Drop Angle                                   | Angle at Rest ≤ 30°                                   | 7.2°                                | Pass      |  |  |
|                            | Impact Indicator                                  | One Indicator Shall Deploy                            | Permanently Deployed                | Pass      |  |  |
| ANSI Z359.11-2021<br>4.3.6 | Fall Arrest Indicator Test<br>(Doral D-ring)      | At Least One Fall Arrest<br>Indicator Shall Deploy    | Visibly and Permanently<br>Deployed | Pass      |  |  |
| ANSI Z359.11-2021<br>4.3.6 | Fall Arrest Indicator Test<br>(Doral D-ring)      | At Least One Fall Arrest<br>Indicator Shall Deploy    | Visibly and Permanently<br>Deployed | Pass      |  |  |
| ANSI Z359.11-2021<br>4.3.6 | Fall Arrest Indicator Test<br>(Doral D-ring)      | At Least One Fall Arrest<br>Indicator Shall Deploy    | Visibly and Permanently<br>Deployed | Pass      |  |  |

## Conclusion

Based upon the samples provided to the Lab:
FallTech P/N 7027 Rev. H meets the requirements of ANSI Z359.11-2021

| Report Signatories and Approval |              |      |           |  |
|---------------------------------|--------------|------|-----------|--|
| Lab Quality Manager             | Jay Sponholz | Date | 5/30/2023 |  |