

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0708156b

Declaration Date

8/6/2024

Tested Item #

81293DQCM

FT-One Fit FBH 3D Standard Non-Belted, Medium, QC  
Legs/QC Chest

## Additional Items Conforming Under this Declaration:

81293DQCXS	81293DQCXL	8129QCXS	8129QCL	8129QC3X	81294DQCM	81294DQC2X
81293DQCS	81293DQC2X	8129QCS	8129QCXL	81294DQCXS	81294DQCL	81294DQC3X
81293DQCL	81293DQC3X	8129QCM	8129QC2X	81294DQCS	81294DQCXL	8049QCXS
8049QCS	8049QCM	8049QCL	8049QCXL	8049QC2X	8049QC3X	

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with  
the requirements of the following product standard(s):

ANSI Z359.11-2021

## Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

☐

Level 2

X

Level 3

☐

Level 1: FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2005

Supporting  
Documentation

PC-2289

Authorized Signature

A handwritten signature in black ink, appearing to read 'Zachary Winters', written over a dashed line.

Name

Zachary Winters

Title

Engineering Manager

Date

8/6/2024



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594

ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

## FallTech Test Report

Test Report No.	PC-2289	Rpt. Date	7/8/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	81293DQCM			Part No. Revision		A	
Part Description	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest						
Test Request No.	PC-2289			Date Complete		7/6/2021	
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
SST1	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
SST2	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
SST3	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
SD1	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
SD2	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
SD3	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
DPT1	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
DPT2	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
DPT3	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
HF1	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
HF2	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
HF3	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
I1	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
I2	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest
I3	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest

### Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3654.4 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.25"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

## FallTech Test Report

Test Report No.	PC-2289	Rpt. Date	7/8/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	81293DQCM			Part No. Revision		A	
Part Description	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest						
Test Request No.	PC-2289			Date Complete		7/6/2021	

### Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3663.3 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.27"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3639.0 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.30"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3648.5 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3644.3 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

## FallTech Test Report

Test Report No.	PC-2289	Rpt. Date	7/8/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	81293DQCM			Part No. Revision		A	
Part Description	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest						
Test Request No.	PC-2289			Date Complete		7/6/2021	

### Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3650.4 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4943.6 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	2.2°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.9"	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	3939.5 Lbf	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	2.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.6"	Pass

## FallTech Test Report

Test Report No.	PC-2289	Rpt. Date	7/8/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	81293DQCM			Part No. Revision		A	
Part Description	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest						
Test Request No.	PC-2289			Date Complete		7/6/2021	

### Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4190.6 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	3.6°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	10.2"	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 3170.9 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	11.2°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 3143.3 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	4.3°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

## FallTech Test Report

Test Report No.	PC-2289	Rpt. Date	7/8/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	81293DQCM			Part No. Revision		A	
Part Description	FT-One Fit FBH 3D Standard Non-belted, Medium, QC Legs/QC Chest						
Test Request No.	PC-2289			Date Complete		7/6/2021	

### Test Summary (Continued)


Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 3022.1 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq$ 30°	1.8°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

### Conclusion

Based upon the samples provided to the Lab:

FallTech P/N 81293DQCM Rev. A meets the requirements of ANSI Z359.11-2021

### Report Signatories and Approval

Lab Quality Manager		Date	7/8/2021
Witnessed by	Not Required	Date	N/A