

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0817162d

Declaration Date

6/6/2024

Tested Item #

8144FDM

FT-Iron FBH 3D+FD Construction Climbing, Medium, TB
Legs/QC Chest

Additional Items Conforming Under this Declaration:

8144FDXS	8144FDXL	8143BFDXS	8143BFDL	8143BFD3X	8143FDM	8143FD2X
8144FDS	8144FD2X	8143BFDS	8143BFDXL	8143FDXS	8143FDL	8143FD3X
8144FDL	8144FD3X	8143BFDM	8143BFD2X	8143FDS	8143FDXL	8143CFDXS
8142CFDXS	8142CFDSM	8142CFDLXL	8142CFD2X	8143FDSM	8143FDLXL	8143CFDSM
8143CFDLXL	8143CFD2X	8142CFD2X3X	8143CFD2X3X			

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with
the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

☐

Level 2

X

Level 3

☐

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2328

Authorized Signature

A handwritten signature in black ink, appearing to read 'Zachary Winters', written over a dashed line.

Name

Zachary Winters

Title

Engineering Manager

Date

6/6/2024



International Accreditation Service, Inc
3060 Saturn St, Ste 100

FallTech Lab - TL-594
ISO/IEC 17025:2017

FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
SST1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SST2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SST3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTS1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTS2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTS3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTH1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTH2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
SSTH3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPT1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPT2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPT3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
HF1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
HF2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
HF3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPTS1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPTS2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
DPTS3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
I1	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
I2	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest
I3	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest

Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3628.0 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3631.8 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.20"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3632.6 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.13"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3632.2 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.26"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3646.9 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.33"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3649.8 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.27"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-ring)	3600 Lbf $\geq$ 1 Minute	3640.6 Lbf	Pass
	Static Strength (Side D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.33"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-ring)	3600 Lbf $\geq$ 1 Minute	3652.2 Lbf	Pass
	Static Strength (Side D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-ring)	3600 Lbf $\geq$ 1 Minute	3636.5 Lbf	Pass
	Static Strength (Side D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4596.0 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	2.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.7"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4857.8 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	1.3°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	12.9"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4631.1 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	1.8°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	12.1"	Pass

FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2522.2 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq 30^\circ$	2.3°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2874.3 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq 30^\circ$	5.7°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2685.6 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq 30^\circ$	3.3°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4135.4 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	33.8°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.5"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3857.1 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	13.6°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	17.8"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4334.8 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	36.8°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	10.5"	Pass



FallTech Test Report

Test Report No.	PC-2328	Rpt. Date	8/17/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144FDM			Part No. Revision		A	
Part Description	FT-Iron FBH 3D + FD Construction Climbing, Medium, TB Legs/QC Chest						
Test Request No.	PC-2328			Date Complete		8/16/2021	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8144FDM Rev. A meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval

Lab Quality Manager		Date	8/17/2021
Witnessed by	Not Required	Date	N/A