

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B1020144

Declaration Date

10/20/2020

Tested Item #

8142QCSM

FT-Iron Full Body Harness 3D Standard Non-belted,
Dual Size S/M, QC Legs/QC Chest

Additional Items Conforming Under this Declaration:

8142QCXS 8142QCLXL 8142QC2X3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2014

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2040

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

10/21/2020



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017
Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2040	Rpt. Date	10/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	8142QCISM	Part No. Revision	A				
Part Description	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2040	Date Complete	10/19/2020				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
5569803	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569799	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569798	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569808	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569800	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569802	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569809	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569796	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569804	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569811	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569805	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569797	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569807	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569801	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest
5569806	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3646.4 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.31"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3658.5 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.28"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



FallTech Test Report

Test Report No.	PC-2040	Rpt. Date	10/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	8142QCSCM	Part No. Revision	A				
Part Description	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2040	Date Complete	10/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3660.7 Lbf Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.27" Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3648.3 Lbf Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.0" Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3642.1 Lbf Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.0" Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3648.4 Lbf Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.0" Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear Pass



FallTech Test Report

Test Report No.	PC-2040	Rpt. Date	10/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	8142QCSCM	Part No. Revision	A				
Part Description	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2040	Date Complete	10/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4671.2 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.6°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.0"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4928.0 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	2.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	10.9"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4863.7 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	2.7°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.7"	Pass

FallTech Test Report

Test Report No.	PC-2040	Rpt. Date	10/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	8142QCSCM	Part No. Revision	A				
Part Description	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2040	Date Complete	10/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	1902.3 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.1°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2161.8 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	5.5°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2377.6 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	4.8°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

FallTech Test Report

Test Report No.	PC-2040	Rpt. Date	10/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	8142QCSM	Part No. Revision	A				
Part Description	FT-Iron Full Body Harness 3D Standard Non-belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2040	Date Complete	10/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.7	Lanyard Parking Attachment Element	Disengagement Load ≤ 120 Lbf	Previously Tested and Passed under PC-1897	Pass


Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8142QCSM Rev. A meets the requirements of ANSI Z359.11-2014

Test Exceptions

* Harness has been dynamically tested and subjected to forces of 5,000 Lbs. or more. Energy absorbing properties inherent to the harness prevented residual force readings equal to or greater than the 3,600 Lbs. required by the standard.

Report Signatories and Approval

Lab Quality Manager		Date	10/20/2020
Witnessed by	Not Required	Date	N/A