

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

BC062003j

Declaration Date

6/23/2026

Tested Item #

8077FDQCM

FT-Arc Nomex FBH 1D+FD Climbing Non-Belted, Medium, QC Legs and Chest, Dielectric

Additional Items Conforming Under this Declaration:

8077FDQCXS	8077FDQCXL	8079FDQCXS	8079FDQCL	8079FDQC3X	80774DQCM	80774DQC2X	8048AFM
8077FDQCS	8077FDQC2X	8079FDQCS	8079FDQCXL	80774DQCXS	80774DQCL	80774DQC3X	8048AFL
8077FDQCL	8077FDQC3X	8079FDQCM	8079FDQC2X	80774DQCS	80774DQCXL	8077B4DQCXS	8048AFXL
8077B4DQCS	8077B4DQCM	8077B4DQCL	8077B4DQCXL	8077B4DQC2X	8077B4DQC3X	8048AFS	8048AF2X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

CSA Z259.10-2018

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2017

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2017

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2017

Supporting
Documentation

PC-2601

K-580778-2205H05-R00

Authorized Signature

Name

ZacharyWinters

Title

Director of Product and
Applied Engineering

Date

6/23/2026



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

BC062003j

Declaration Date

6/23/2026

Tested Item #

8077FDQCM

FT-Arc Nomex FBH 1D+FD Climbing Non-Belted, Medium, QC Legs and Chest, Dielectric

Additional Items Conforming Under this Declaration:

8049AFL 8049AFXL 8049AF2X 8049AF3X 8077CFDQCXS 8077CFDQCS 8077CFDQCM 8049AFXS
8077CFDQCL 8077CFDQCXL 8077CFDQC2X 8077CFDQC3X 8079CFDQCXS 8079CFDQCS 8079CFDQCM 8049AFS
8079CFDQCL 8079CFDQCXL 8079CFDQC2X 8079CFDQC3X 8077BFDQCXS 8077BFDQCS 8077BFDQCM 8049AFM
8077BFDQCL 8077BFDQCXL 8077BFDQC2X 8077BFDQC3X 80773DQCXS 80773DQCS 80773DQCM 80773DQCL
80773DQCXL 80773DQC2X 80773DQC3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

CSA Z259.10-2018

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2017

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2017

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2017

Supporting
Documentation

PC-2601

K-580778-2205H05-R00

Authorized Signature

Name

ZacharyWinters

Title

Director of Product and
Applied Engineering

Date

6/23/2026



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

BC062003j

Declaration Date

6/23/2026

Tested Item #

8077FDQCM

FT-Arc Nomex FBH 1D+FD Climbing Non-Belted, Medium, QC Legs and Chest, Dielectric

Additional Items Conforming Under this Declaration:

8079QC2X 8079QC3X 80803DQCXS 80803DQCS 80803DQCM 80803DQCL 80803DQCXL 80803DQC2X
80803DQC3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

CSA Z259.10-2018

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2017

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2017

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2017

Supporting
Documentation

PC-2601

K-580778-2205H05-R00

Authorized Signature

Name

ZacharyWinters

Title

Director of Product and
Applied Engineering

Date

6/23/2026



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2601	Rpt. Date	6/14/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	CSA Z259.10-18: 6.2.2.1, 6.2.2.4, 6.2.2.5, 6.2.6				
Part No.	8077FDQCM	Part No. Revision		A			
Part Description	FT-Arc Nomex FBH 1D+FD Climbing Non-Belted, Medium, QC Legs and Chest, Dielectric						
Test Request No.	PC-2601	Date Complete		6/10/2022			



Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
CSA Z259.10-18 6.2.2.4	Drop Test Class L Ladder Climbing	Peak Impact \geq 3,600 Lbf or 39.4" Free Fall	4275.1 lbs. Fall Height 39.4"	Pass
	Drop Test Class L Ladder Climbing	Test Mass Remain Suspended for: \geq 2 Minutes	2 Minutes	Pass
	Drop Test Class L Ladder Climbing	All Connectors remain connected	All Connected	Pass
CSA Z259.10-18 6.2.6	Fall Arrest Indicator Static	Load to 900 lbs. or Indicator deploys Whichever occurs first	724.4 lbs.	Pass
	Fall Arrest Indicator Static	Verify Fall Arrest Indicator has activated	Visibly and Permanently Deployed	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8077FDQCM Rev. A meets the requirements of CSA Z259.10-18 and * ASTM F-887-18

Report Signatories and Approval

Lab Quality Manager		Date	6/14/2022
Witnessed by	Bob Howey (Element) 	Date	6-14-22



TESTING - EXPOSURE TO AN ELECTRIC ARC

Test Specimen:

FallTech,
Full Body Harness, Style 8077FDQCM,
Webbing: Nylon Black

Requested by:

FallTech
1306 S Alameda St
Compton, CA 90221

Test Standard:

ELECTRIC ARC TESTS: ASTM F887-20

OBSERVATION OF PERSONAL CLIMBING EQUIPMENT EXPOSED TO AN ELECTRIC ARC

Test Report:

K-580778-2205H05-R00

Results:

Based on the test results in Table 4-1 and observations, the product tested meets the requirements criteria of Table 1-1 as per ASTM F887-20 sections 22.6.1-22.6.2. According to ASTM F887-20, Section 25, verification of performance shall include a mechanical integrity (vertical drop test) as soon as possible following the arc exposure.

Sample Received May 9, 2022	Test Date May 16, 2022	Report Date May 27, 2022
--------------------------------	---------------------------	-----------------------------

Prepared by

Approved by

Yosbani
Technologist, HCL
TD Technologies, Kinectrics

Claude Maurice
Technical Specialist, HCL
TD Technologies, Kinectrics

For questions about this test report, please contact testing@arcwear.com



Revision History

Rev	Description		
00	Initial report creation		
	Issue Date	Prepared by	Approved by
	May 27, 2022	Yosbani Guerra	Claude Maurice
Rev	Description		
	Issue Date	Prepared by	Verified by

DISCLAIMER

Kinectrics prepared this report as a work of authorship sponsored by their Client. This report has been prepared solely for the benefit of the Client and may not be used or relied upon in whole or in part by any other person or entity without Client permission or without Kinectrics' permission if required by the Contract between Client and Kinectrics Inc. Neither Kinectrics, their client nor any person acting on behalf of them: (a) makes any warranty or representation whatsoever, express or implied, or assumes any legal liability of responsibility for any third party's use, or the results of such use, with respect to (i) the use of any information, apparatus, method, process, or similar item disclosed in this report including the merchantability or fitness for any particular purpose of any information contained in this report or the respective works or services supplied or performed or (ii) that such use does not infringe on or interfere with privately owned rights, including any party's intellectual property; or (b) assumes responsibility for any damages or other liability whatsoever (including any consequential damages resulting from a third party's selection or use of this report or any information, apparatus, method, process, or similar item disclosed).

Copyright © 2022 Kinectrics Inc. All rights reserved.

QUALITY MANAGEMENT

The arc testing performed to the above mentioned Standard is accredited by the Standards Council of Canada (SCC) to conform to the requirements of CAN-P-4E (ISO/IEC 17025:2017). Accreditation by the Standards Council of Canada (SCC) is a mark of competence and reliability

- The test performed does not apply to electrical contact or electrical shock hazard.
- The test result is applicable only to the Test Specimens delivered to Kinectrics, other material, design or color may have a different response.
- It is the clients' responsibility to provide full and accurate information about the items supplied.
- No test is done to validate the fiber content or composition of the test item.
- Photographs of the test specimens and waveforms of the arc current, voltage and calorimeters with the circuit and arc exposure calibration records are available from Kinectrics and provided to the client separately from this report.



1 Test Standard:

Electrical arc test according to ASTM F887-20, Section 22

Standard Specifications for Personal Climbing Equipment, After Exposure to an Electric Arc Evaluation. Specimens are mounted on mannequins of panels having a distance of 30.5 cm (12 inches) from the centerline of the electrodes. The test standard requires that the finished personal climbing equipment be exposed to a level of $40 \text{ cal/cm}^2 \pm 5 \text{ cal/cm}^2$.

1.1 Test Requirements

Harnesses- The test program requires the specimens be placed on mannequins as normally worn. A minimum of eight samples are tested, four samples with the front facing the arc and four samples with the back side toward the arc.

Harness accessories, loops etc. - Three specimens of each accessory or loop are required to be exposed to the arc.

Energy Absorbing Lanyard - Three specimens of each lanyard are required to be exposed to the arc.

Other effects than the thermal effects of an electric arc like noise, light emissions, pressure rise, hot oil, electric shock, the consequences of physical and mental shock or toxic influences are not covered by this standard.

1.2 Acceptance criteria for products exposed to electrical arc:

The procedure outlined in ASTM F887-20 is followed to verify the electric arc performance of the personal climbing equipment. The product is considered as having passed the visual inspection criteria if the parameters defined in Table 1-1 are met. As proof of performance following the arc exposure, the exposed test specimens shall be subjected to a drop test. This shall be done as soon as practically possible. The samples have been returned to the client as directed to perform the drop test.

Table 1-1: Visual inspection Criteria for Electric Arc Performance of ASTM F887-20

Parameter	Criterion
Arc Energy	Electrical arc exposure of $40 \text{ cal/cm}^2 \pm 5 \text{ cal/cm}^2$
Ignition	No electric arc ignition.
After-flame Time	Less than 5 seconds on load bearing materials and less than 15 seconds for accessories or non-load bearing components.
Melting/Dripping	No melting and dripping of molten materials to the floor of any load bearing material. Accessories are allowed to exhibit melting and dripping provided they are not ignited while dripping.

2 Test Condition:

The following test circuit parameters and conditions were used.

- Electric arc current: 8 kA rms \pm 10%, 60 Hz
- Open circuit voltage: 2500 V rms \pm 10%, 60 Hz
- Nominal Heat Flux Density: 2100 kW/m² (50 cal/cm²·s)
- Arc duration: 0.85 seconds \pm 0.1 s to obtain required incident energy
- Electrode gap: 305 mm (12 inches)
- Distance from mannequin to electrode: 305 mm (12 inches)
- Deviations and abnormalities: None

Note: The measurement uncertainty, MU, for the measured values of this test method are well within the requirements of the test standard and are defined on a 95% confidence interval basis over the full test range, as follows:

- Temperature: \pm 2 °C
- Arc Current: \pm 2.5%
- Time zero reference: \pm 3 ms
- Incident Energy: \pm 1.5%
- Voltage: \pm 2.2%

3 Test Specimen:

The following description of the test sample was provided by the client and confirmed by the identification tag shown in Figure 3.1.

Sample description:	Fall Protection Harness
Sample identification:	Style 8077FDQCM
Manufacturer:	FallTech
Material of webbing:	Nylon, Black
Number of samples tested:	14
Harness Accessories:	None
Notes:	None



Figure 3.1: Identification Tag



4 Test Results:

Arc exposures were performed on the samples as indicated. If the conditions and evaluation of the samples meet the criteria in Table 1-1, the product has passed the electrical arc exposure and is candidate for the mechanical drop test to fully meet the arc performance requirements of ASTM F887-20. Photographs of the samples before and after the arc exposure are shown in Section 6.

Table 4-1: Summary of Test Results

	Trial # 22-0624		Trial # 22-0625	
	A – Front	B – Back	A – Front	B – Back
Mannequin				
Item Serial #	6346681	6346682	6346690	6346680
Incident Energy	44.8	45.9*	39.8	44.0
After-flame	0	0	10	0
Ignition	N	N	N	N
Melting and Dripping	N	N	N	N
Acceptance Criteria	Meets	Meets	Meets	Meets
	Trial # 22-0626		Trial # 22-0627	
	A – Front	B – Back	A – Front	B – Back
Mannequin				
Item Serial #	6346675	6346677	6346679	6346688
Incident Energy	40.7	43.3	42.7	45.6*
After-flame	0	1	0	0
Ignition	N	N	N	N
Melting and Dripping	N	N	N	N
Acceptance Criteria	Meets	Meets	Meets	Meets
	Trial # 22-0628		Trial # 22-0629	
	A – Front	B – Back	A – Front	B – Back
Mannequin				
Item Serial #	6346684	6346674	6346686	6346687
Incident Energy	41.2	41.9	44.4	42.7
After-flame	0	0	0	0
Ignition	N	N	N	N
Melting and Dripping	N	N	N	N
Acceptance Criteria	Meets	Meets	Meets	Meets
	Trial # 22-0630		Trial # 22-0631	
	A – Front	B – Back	A – Front	B – Back
Mannequin				
Item Serial #	No Sample	6346683	No Sample	6346685
Incident Energy		44.7		41.2
After-flame		0		0
Ignition		N		N
Melting and Dripping		N		N
Acceptance Criteria		Meets		Meets

*Incident Energy above 45 cal/cm², test is invalid.
 Additional tests completed to meet acceptance criteria.