Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221

Declaration #	C061705	6b	Dec	laration Date	6.13.17
Tested Item #	8247EA	4½ - 6'	Ironman® En	ergy Absorb	ing Lanyard
Additional Item	s Conforming Und	er this Declaration:			
Alexander A		•	product(s) listed		
		ANSI Z35	9.13-2013		
Co	nformity Assess	ment Method in	accordance with	ANSI/ISEA 125	2014
	Level 1	Level 2	2 X	Level 3	
Level 1: FallTech Lab Outside the Scope of ISO/IEC Standard 17025:2005		Within th	Level 2 : FallTech Lab Within the Scope of ISO/IEC Standard 17025:2005		pendent 3rd Party Lab ccredited to candard 17025:2005
Supporting Documentation	PC-1137	PC-1167			
Aut	horized Signati	ure	4	Marelo-	
Name Mai	rtin Barila	Title	VP of Operation	ns 	Date11.7.17

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com



Testing. Advising. Assuring.

June 15, 2017

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Jay Sponholz

Quality Manager

Subject: Attestation of Witnessing Testing

Exova OCM Job # 370839-6 FallTech P.O.: OPEN Report No.: PC-1137 Base Part No. 8247EA

Description: Y-Leg Energy Absorbing Lanyard

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- Date of Testing:
 - June 8, 2017
- Exova OCM Test Witness:
 - 6/8/17 -Nolan Schatzle
- FallTech Test Operators:
 - Yesbet Sierra/Jay Sponholz
- Specification:

ANSI Z359.13-2013 Sections 4.7.1, 4.7.2, 4.7.3, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3

- Equipment Calibration Interval
 - 1 year, except weights which are 5 years



Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results									
				S1										
				S2										
				S3										
				D1										
				D2										
				D3										
				S1										
				S2	1									
				S3										
				D1										
PC-1137	6/8/17	8247EA	Energy Absorbing Lanyard	D2	Pass									
				D3										
	1			W1										
				W2										
				W3										
				C1										
				C2										
				C3										
				H1										
														H2
				H3										

Test Witness Signature: (Signed for and on behalf of Exova-OCM) **Nolan Schatzle** Technician **Mechanical Laboratory** Approval Signature: (Signed for and on behalf of Exova-OCM) Jim Rutherford **Active Quality Manager**

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.





FallTech Test Report							
Test Report No.	PC-1137	Rpt. Date	6/13/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specif	icanonisi	ANSI Z359. 4.5, 4.6, 4.1		4.13.3	
Part No.	8247EA			Part No. Re	evision	А	
Part Description	12FF Energy Absort	oing Lanyard					
Test Request No.	PC-1137			Date Comp	lete	6/8/2017	
Test Operator(s)	Yesbet Sierra / Jay S	Sponholz					

	Material/Sample Identification					
Sample ID	Description					
S1	12FF Energy Absorbing Lanyard					
S2	12FF Energy Absorbing Lanyard					
S 3	12FF Energy Absorbing Lanyard					
S 1	12FF Energy Absorbing Lanyard					
S2	12FF Energy Absorbing Lanyard					
S 3	12FF Energy Absorbing Lanyard					
W1	12FF Energy Absorbing Lanyard					
W2	12FF Energy Absorbing Lanyard					
W3	12FF Energy Absorbing Lanyard					
C1	12FF Energy Absorbing Lanyard					
C2	12FF Energy Absorbing Lanyard					
C3	12FF Energy Absorbing Lanyard					
H1	12FF Energy Absorbing Lanyard					
H2	12FF Energy Absorbing Lanyard					
Н3	12FF Energy Absorbing Lanyard					







FallTech Test Report							
Test Report No.	PC-1137	Rpt. Date	6/13/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Speci	rication(s)	ANSI Z359. 4.5, 4.6, 4.1		4.13.3	
Part No.	8247EA			Part No. Re	vision	А	
Part Description	12FF Energy Absort	oing Lanyard	t				
Test Request No.	PC-1137			Date Comp	lete	6/8/2017	

		Test Summary		
Test Specification	Test	t Criteria	Test Result	Pass/Fail
ANSI Z359.13-2013 4.5	Arrest Distance	<u><</u> 60"	53.4"	Pass
	Max Arrest Force	<u>≤</u> 1800 Lbf	1176.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	881.4 Lbf	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 60"	55.4"	Pass
ANSI Z359.13-2013 4.5	Max Arrest Force	<u><</u> 1800 Lbf	1191.5 Lbf	Pass
4.5	Avg Arrest Force	≤ 1350 Lbf	f 882.4 Lbf Pass 54.9" Pass f 1173.6 Lbf Pass f 865.6 Lbf Pass f 5022.2 Lbf Pass e 1 Minute Pass	Pass
ANCI 7250 42 2042	Arrest Distance	<u>≤</u> 60"	54.9"	Pass
ANSI Z359.13-2013 4.5	Max Arrest Force	≤ 1800 Lbf	1173.6 Lbf	Pass
4.5	Avg Arrest Force	≤ 1350 Lbf	865.6 Lbf	Pass
ANSI Z359.13-2013	Static Strength	<u>></u> 5000 Lbf	5022.2 Lbf	Pass
4.6	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5023.0 Lbf	Pass
4.6	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013	Static Strength	<u>></u> 5000 Lbf	5030.2 Lbf	Pass
4.6	Hold	≥ 1 Minute	1 Minute	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 60"	48.9"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	<u><</u> 1800 Lbf	1394.4 Lbf	Pass
4.13.1	Avg Arrest Force	<u><</u> 1575 Lbf	1000.0 Lbf	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 60"	48.3"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	≤ 1800 Lbf	1392.1 Lbf	Pass
4.13.1	Avg Arrest Force	<u><</u> 1575 Lbf	939.4 Lbf	Pass
ANGL 7250 42 2042	Arrest Distance	<u><</u> 60"	43.8"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	≤ 1800 Lbf	1327.2 Lbf	Pass
4.13.1	Avg Arrest Force	≤ 1575 Lbf	950.6 Lbf	Pass



1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-1137	Rpt. Date	6/13/2017	Rpt. Rev	Rev Date		
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.13-20 4.5, 4.6, 4.13.1, 4			
Part No.	8247EA			Part No. Revisio	n A		
Part Description	12FF Energy Abs	sorbing Lanyard	ı				
Test Request No.	PC-1137			Date Complete	6/8/2017		

Test Summary (Continued)						
Test Specification	Test (Criteria	Test Result	Pass/Fail		
ANGL 7250 42 2042	Arrest Distance	≤ 60"	44.8"	Pass		
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1277.5 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1575 Lbf	990.7 Lbf	Pass		
ANGI 7250 42 2042	Arrest Distance	≤ 60"	43.0"	Pass		
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1376.0 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1575 Lbf	951.1 Lbf	Pass		
ANG 7250 42 2042	Arrest Distance	≤ 60"	44.2"	Pass		
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1333.8 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1575 Lbf	935.2 Lbf	Pass Pass Pass Pass Pass Pass Pass Pass		
ANG 7250 42 2042	Arrest Distance	≤ 60"	57.4"	Pass		
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	1490.6 Lbf	Pass		
4.15.5	Avg Arrest Force	≤ 1575 Lbf	918.9 Lbf	Pass Pass Pass Pass Pass Pass Pass Pass		
11101 7050 10 0010	Arrest Distance	≤ 60"	53.3"	Pass		
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	1281.9 Lbf	Pass		
4.13.3	Avg Arrest Force	≤ 1575 Lbf	907.7 Lbf	Pass Pass Pass Pass Pass Pass Pass Pass		
ANG 7250 42 2042	Arrest Distance	≤ 60"	50.8"	Pass		
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	1359.4 Lbf	Pass		
4.13.3	Avg Arrest Force	≤ 1575 Lbf	900.7 Lbf	Pass		

FallTe	ech P/N 8247EA Rev. A meets the requirements of	ANSI Z359.13-2013	
	Report Signatories and Appro	val	
Lab Quality Manager	Jay Spondols	Date	6/13/2017

Conclusion

Witnessed by Nolan Schatzle Date 6-(5-(7

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com

EXOVQ OCM

Testing. Advising. Assuring.

July 31, 2017

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Jay Sponholz

Quality Manager

Subject: Attestation of Witnessing Testing

Exova OCM Job # 371118-4
FallTech P.O.: OPEN
Report No.: PC-1167
Base Part No. 8247EA

Description: Ironman 6' Shock Absorbing Lanyard 6' free fall

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- Date of Testing:
 - July 20, 2017
- Exova OCM Test Witness:
 - 7/20/17 -Nolan Schatzle
- FallTech Test Operators:
 - Yesbet Sierra/Jay Sponholz
- Specification:

ANSI Z359.13-2013 Sections 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3

- Equipment Calibration Interval
 - 1 year, except weights which are 5 years



Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
PC-1167	7/20/17	Base Part #	Ironman 6' Shock Absorbing Lanyard 6' free fall	4003105 4003100 4003108 4003105 4003100 4003108 4003104 4003101 4003106 4003099 4003102 4003098 4003103 4003107 4003097	Pass

Test Witness Signature: Nolan Schatzle Technician	(Signed for and on behalf of Exova-OCM)	072 204LITY
Mechanical Laboratory		
Approval Signature:	(Signed for and on behalf of Exova-OCM)	
Victor Mendez Production Manager	Victa Herde	

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.

LABORATORY



FallTech Test Report							
Test Report No.	PC-1167	Rpt. Date	7/26/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Speci	ncanonesi	ANSI Z359.13-2013 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3			
Part No.	8247EA			Part No. Re	vision	А	
Part Description	Ironman 6' Shock Al	bsorbing Lar	nyard 6' free	fall			
Test Request No.	PC-1167			Date Comp	lete	7/20/2017	
Test Operator(s)	Yesbet Sierra / Jay	Sponholz					

Material/Sample Identification				
Sample ID	Description			
4003105	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003100	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003108	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003105	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003100	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003108	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003104	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003101	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003106	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003099	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003102	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003098	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003103	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003107	Ironman 6' Shock Absorbing Lanyard 6' free fall			
4003097	Ironman 6' Shock Absorbing Lanyard 6' free fall			



FallTech Test Report							
Test Report No.	PC-1167	Rpt. Date	7/26/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden Test Specification(s)		ANSI Z359. 4.5, 4.6, 4.1		4.13.3		
Part No.	8247EA			Part No. Re	vision	Α	
Part Description	Ironman 6' Shock Absorbing Lanyard 6' free fall						
Test Request No.	PC-1167			Date Comp	lete	7/20/2017	

		Test Summary		
Test Specification	Test	: Criteria	Test Result	Pass/Fail
ANGL 7250 42 2042	Arrest Distance	<u><</u> 48"	32.5"	Pass
ANSI Z359.13-2013 4.5	Max Arrest Force	≤ 1800 Lbf	1095.4 Lbf	Pass
4.5	Avg Arrest Force	≤ 900 Lbf	856.0 Lbf	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 48"	31.5"	Pass
ANSI Z359.13-2013 4.5	Max Arrest Force	≤ 1800 Lbf	1232.9 Lbf	Pass
4.5	Avg Arrest Force	<u><</u> 900 Lbf	881.5 Lbf	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 48"	30.8"	Pass
ANSI Z359.13-2013 4.5	Max Arrest Force	≤ 1800 Lbf	1201.6 Lbf	Pass
4.5	Avg Arrest Force	<u><</u> 900 Lbf	859.4 Lbf	Pass
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5024.6 Lbf	Pass
4.6	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5041.1 Lbf	Pass
4.6	Hold	≥1 Minute	1 Minute	Pass
ANSI Z359.13-2013	Static Strength	<u>></u> 5000 Lbf	5043.9 Lbf	Pass
4.6	Hold	≥ 1 Minute	1 Minute	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 48"	30.8"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	<u><</u> 1800 Lbf	1515.7 Lbf	Pass
4.15.1	Avg Arrest Force	<u><</u> 1125 Lbf	894.4 Lbf	Pass
ANG 7250 42 2042	Arrest Distance	<u><</u> 48"	31.0"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	≤ 1800 Lbf	1389.3 Lbf	Pass
4.13.1	Avg Arrest Force	≤ 1125 Lbf	885.1 Lbf	Pass
ANGL 7250 42 2042	Arrest Distance	<u><</u> 48"	32.0"	Pass
ANSI Z359.13-2013 4.13.1	Max Arrest Force	≤ 1800 Lbf	1125.8 Lbf	Pass
4.13.1	Avg Arrest Force	<u><</u> 1125 Lbf	878.6 Lbf	Pass



1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report					
Test Report No.	PC-1167	Rpt. Date	7/26/2017	Rpt. Rev	Rev Date
Report Prepared For	FallTech				
Initiated By	Dan Redden	LIEST Specification(S)		ANSI Z359.13-20 4.5, 4.6, 4.13.1, 4	
Part No.	8247EA			Part No. Revisio	n A
Part Description	Ironman 6' Shock Absorbing Lanyard 6' free fall				
Test Request No.	PC-1167		Date Complete	7/20/2017	

	Test Summary (Continued)					
Test Specification	Test	Criteria	Test Result	Pass/Fail		
	Arrest Distance	≤ 48"	28.2"	Pass		
ANSI Z359.13-2013	Max Arrest Force	≤ 1800 Lbf	1231.1 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1125 Lbf	877.4 Lbf	Pass		
ANG 7050 40 0040	Arrest Distance	<u>≤</u> 48"	28.4"	Pass		
ANSI Z359.13-2013	Max Arrest Force	≤ 1800 Lbf	1300.4 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1125 Lbf	875.6 Lbf	Pass		
ANG 7250 12 2012	Arrest Distance	≤ 48"	27.5"	Pass		
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1317.8 Lbf	Pass		
4.13.2	Avg Arrest Force	≤ 1125 Lbf	929.6 Lbf	Pass		
ANG 7250 12 2012	Arrest Distance	≤ 48"	33.3"	Pass		
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	1328.5 Lbf	Pass		
4.15.5	Avg Arrest Force	≤ 1125 Lbf	901.4 Lbf	Pass		
	Arrest Distance	≤ 48"	34.0"	Pass		
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	1246.8 Lbf	Pass		
4.13.3	Avg Arrest Force	≤ 1125 Lbf	873.2 Lbf	Pass		
ANGL 7250 42 2042	Arrest Distance	≤ 48"	32.3"	Pass		
ANSI Z359.13-2013	Max Arrest Force	≤ 1800 Lbf	1332.6 Lbf	Pass		
4.13.3	Avg Arrest Force	≤ 1125 Lbf	899.0 Lbf	Pass		

Fa	IllTech P/N 8247EA Rev. A meets the requirements of	ANSI Z359.13-201	3
	Report Signatories and Approv	/al	
Lab Quality Manager	Jay Sponholz	Date	7/26/2017
Witnessed by	olan Schatzle	Date	7-31-17

Conclusion