

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221

Declaration #

C0917069

Declaration Date

9.14.17

Tested Item #

826073PC

6' SAL Y-Legs Viewpack Urethane Coated

Additional Items Conforming Under this Declaration:

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

ANSI Z359.13-2013

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

X

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-1195

Authorized Signature

Name

Martin Barila

Title

VP of Operations

Date

2.2.18

Exova
3883 East Eagle Drive
Anaheim
California
USA
92807

T: +1 (714) 630-3003
F: +1 (714) 630-4443
E: sales@exova.com
W: www.exova.com



Testing. Advising. Assuring.

September 25, 2017

FallTech Testing Laboratory
1306 S. Alameda Street
Compton, CA 90221

Attention: Jay Sponholz
Quality Manager

Subject: **Attestation of Witnessing Testing**
Exova OCM Job # 371394-3
FallTech P.O.: OPEN
Report No.: PC-1195
Base Part No. 826073PC
Description: 6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:



- Date of Testing:
 - September 12, 2017
- Exova OCM Test Witness:
 - 9/12/17 - Nolan Schatzle
- FallTech Test Operators:
 - Yesbet Sierra/Jay Sponholz
- Specification:


ANSI Z359. 13-2013 Sections: 4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3

- Equipment Calibration Interval
 - 1 year, except weights which are 5 years

Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
PC-1195	9/12/17	826073PC	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks	4018073	Pass
				4018084	
				4018075	
				4018086	
				4018082	
				4018087	
				4018073	
				4018084	
				4018075	
				4018086	
				4018082	
				4018087	
				4018078	
				4018074	
				4018088	
4018083					
4018081					
4018076					
4018077					
4018090					
4018085					

Test Witness Signature: Nolan Schatzle Technician Mechanical Laboratory	<i>(Signed for and on behalf of Exova-OCM)</i>  
---	---

Approval Signature: Victor Mendez Production Manager	<i>(Signed for and on behalf of Exova-OCM)</i> 
---	--

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.



FallTech Test Report

Test Report No.	PC-1195	Rpt. Date	9/14/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3				
Part No.	826073PC	Part No. Revision	A				
Part Description	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks						
Test Request No.	PC-1195	Date Complete	9/12/2017				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
4018073	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018084	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018075	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018086	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018082	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018087	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018073	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018084	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018075	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018086	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018082	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018087	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018078	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018074	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018088	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018083	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018081	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018076	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018077	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018090	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks
4018085	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks



FallTech Test Report

Test Report No.	PC-1195	Rpt. Date	9/14/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3				
Part No.	826073PC	Part No. Revision	A				
Part Description	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks						
Test Request No.	PC-1195	Date Complete	9/12/2017				

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.13-2013 4.7.1, 4.7.2	Static Strength	≥ 5000 Lbf	5020.7 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
	Static Strength	≥ 5000 Lbf	5026.9 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.7.1, 4.7.2	Static Strength	≥ 5000 Lbf	5132.7 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
	Static Strength	≥ 5000 Lbf	5023.2 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.7.1, 4.7.2	Static Strength	≥ 5000 Lbf	5033.0 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
	Static Strength	≥ 5000 Lbf	5021.5 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.7.3	Static Strength	≥ 5000 Lbf	5039.5 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.7.3	Static Strength	≥ 5000 Lbf	5053.7 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.7.3	Static Strength	≥ 5000 Lbf	5045.0 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.8	Arrest Distance	≤ 48"	39.0"	Pass
	Max Arrest Force	≤ 1800 Lbf	991.2 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	730.0 Lbf	Pass
ANSI Z359.13-2013 4.8	Arrest Distance	≤ 48"	40.8"	Pass
	Max Arrest Force	≤ 1800 Lbf	974.1 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	784.3 Lbf	Pass
ANSI Z359.13-2013 4.8	Arrest Distance	≤ 48"	38.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1029.1 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	762.9 Lbf	Pass



FallTech Test Report

Test Report No.	PC-1195	Rpt. Date	9/14/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3				
Part No.	826073PC			Part No. Revision	A		
Part Description	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks						
Test Request No.	PC-1195			Date Complete	9/12/2017		

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.13-2013 4.9	Max Arrest Force	≤ 1800 Lbf	1005.8 Lbf	Pass
ANSI Z359.13-2013 4.9	Max Arrest Force	≤ 1800 Lbf	996.0 Lbf	Pass
ANSI Z359.13-2013 4.9	Max Arrest Force	≤ 1800 Lbf	982.5 Lbf	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	39.4"	Pass
	Max Arrest Force	≤ 1800 Lbf	905.0 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	702.6 Lbf	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	39.3"	Pass
	Max Arrest Force	≤ 1800 Lbf	1103.1 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	779.0 Lbf	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	44.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	950.1 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	759.7 Lbf	Pass
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	32.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1142.0 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	857.1 Lbf	Pass
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	31.8"	Pass
	Max Arrest Force	≤ 1800 Lbf	1133.1 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	864.7 Lbf	Pass
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	30.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1095.0 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	872.3 Lbf	Pass



FallTech Test Report

Test Report No.	PC-1195	Rpt. Date	9/14/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3				
Part No.	826073PC	Part No. Revision	A				
Part Description	6' SAL Y-Legs; Viewpck Urethane Coated with Rebar Hooks						
Test Request No.	PC-1195	Date Complete	9/12/2017				



Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	45.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	999.4 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	732.4 Lbf	Pass
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	44.8"	Pass
	Max Arrest Force	≤ 1800 Lbf	958.6 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	723.7 Lbf	Pass
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	42.6"	Pass
	Max Arrest Force	≤ 1800 Lbf	1005.4 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	754.3 Lbf	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 826073PC Rev. A meets the requirements of ANSI Z359.13-2013

Report Signatories and Approval

Lab Quality Manager		Date	9/14/2017
Witnessed by	Nolan Schatzle 	Date	9-25-17

