# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

**Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619**

| **Declaration #** | C1006107 | **Declaration Date** | 10/6/2026 |
|---|---|---|---|

**Tested Item #** **82608** **6' SAL Y-Legs; ViewPack with Snap Hooks**

**Additional Items Conforming Under this Declaration:**

| | |
|---|---|
| **826073** | **826073A** |
| **8260733FT** | **826084** |
| **8260734** | **826083** |

**Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):**

## ANSI Z359.13-2013 (R2022)

**Conformity Assessment Method in accordance with ANSI/ISEA 125-2014**

| **Level 1** | | **Level 2** | **X** | **Level 3** | |
|---|---|---|---|---|---|

| | | |
|---|---|---|
| **Level 1**: FallTech Lab Outside the Scope of ISO/IEC Standard 17025:2017 | **Level 2**: FallTech Lab Within the Scope of ISO/IEC Standard 17025:2017 | **Level 3**: Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017 |

| **Supporting Documentation** | **PC-3728** |
|---|---|

**Authorized Signature**

**Name** Zachary Winters **Title** Director of Product and Applied Engineering **Date** 10/6/2026

IAS ACCREDITED Testing Laboratory
International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017
Alexander Andrew Inc dba FallTech

**FallTech Testing Laboratory**
1306 S. Alameda Street,
Compton, CA 90221-4803
Tel: (323) 752-0060
www.falltech.com

# FallTech Test Report

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Test Report No.** | PC-3728 | **Rpt. Date** | 7/24/2026 | **Rpt. Rev** | | **Rev Date** | |
| **Report Prepared For** | FallTech | | | | | | |
| **Initiated By** | Zachary Winters | **Test Specification(s)** | | ANSI Z359.13-2013 (R2022)<br>4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3 | | | |
| **Part No.** | 82608 | | | **Part No. Revision** | E | | |
| **Part Description** | 6' SAL Y-Legs; ViewPack with Snap Hooks | | | | | | |
| **Test Request No.** | PC-3728 | | | **Date Complete** | 7/23/2026 | | |
| **Test Operator(s)** | Yesbet Sierra / Jay Sponholz | | | | | | |

## Material/Sample Identification

| Sample ID | Description |
|---|---|
| 9868960 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868957 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868894 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868992 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868896 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868942 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868973 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868959 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868947 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868970 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868939 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868905 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868969 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868948 | 6' SAL Y-Legs; ViewPack with Snap Hooks |
| 9868993 | 6' SAL Y-Legs; ViewPack with Snap Hooks |

## Test Summary

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|---|---|---|---|---|
| ANSI Z359.13-2013<br>4.7.1, 4.7.2<br>Single Leg(s) | Static Strength | ≥ 5000 Lbf | 5032.6 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| | Static Strength | ≥ 5000 Lbf | 5036.1 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| ANSI Z359.13-2013<br>4.7.1, 4.7.2<br>Single Leg(s) | Static Strength | ≥ 5000 Lbf | 5025.1 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| | Static Strength | ≥ 5000 Lbf | 5028.1 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| ANSI Z359.13-2013<br>4.7.1, 4.7.2<br>Single Leg(s) | Static Strength | ≥ 5000 Lbf | 5036.8 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| | Static Strength | ≥ 5000 Lbf | 5033.7 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |

This laboratory is accredited with the recognized International Standard
ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC Communiquedated January 2009).
FallTech Testing Laboratory utilizes the Simple Acceptance Rule and allows for a 5% tolerance on dynamic and static strength test results.

IAS ACCREDITED Testing Laboratory
Certificate# TL-594 Testing

**FallTech Testing Laboratory**
1306 S. Alameda Street,
Compton, CA 90221-4803
Tel: (323) 752-0060
www.falltech.com

# FallTech Test Report

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Test Report No.** | PC-3728 | **Rpt. Date** | 7/24/2026 | **Rpt. Rev** | | **Rev Date** | |
| **Report Prepared For** | FallTech | | | | | | |
| **Initiated By** | Zachary Winters | **Test Specification(s)** | | ANSI Z359.13-2013 (R2022)<br>4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3 | | | |
| **Part No.** | 82608 | | | **Part No. Revision** | E | | |
| **Part Description** | 6' SAL Y-Legs; ViewPack with Snap Hooks | | | | | | |
| **Test Request No.** | PC-3728 | | | **Date Complete** | 7/23/2026 | | |

## Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|---|---|---|---|---|
| ANSI Z359.13-2013 4.7.3 Between Legs | Static Strength | ≥ 5000 Lbf | 5030.7 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| ANSI Z359.13-2013 4.7.3 Between Legs | Static Strength | ≥ 5000 Lbf | 5021.6 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| ANSI Z359.13-2013 4.7.3 Between Legs | Static Strength | ≥ 5000 Lbf | 5023.4 Lbf | Pass |
| | Hold | ≥ 1 Minute | 1 Minute | Pass |
| ANSI Z359.13-2013 4.8 DPT Ambient | Arrest Distance | ≤ 48" | 40.6" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1053.7 Lbf | Pass |
| | Avg Arrest Force | ≤ 900 Lbf | 827.8 Lbf | Pass |
| ANSI Z359.13-2013 4.8 DPT Ambient | Arrest Distance | ≤ 48" | 39.9" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1254.3 Lbf | Pass |
| | Avg Arrest Force | ≤ 900 Lbf | 817.4 Lbf | Pass |
| ANSI Z359.13-2013 4.8 DPT Ambient | Arrest Distance | ≤ 48" | 38.3" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1106.8 Lbf | Pass |
| | Avg Arrest Force | ≤ 900 Lbf | 828.9 Lbf | Pass |
| ANSI Z359.13-2013 4.9 Dual Connection | Max Arrest Force | ≤ 1800 Lbf | 1215.2 Lbf | Pass |
| ANSI Z359.13-2013 4.9 Dual Connection | Max Arrest Force | ≤ 1800 Lbf | 1129.6 Lbf | Pass |
| ANSI Z359.13-2013 4.9 Dual Connection | Max Arrest Force | ≤ 1800 Lbf | 1188.9 Lbf | Pass |
| ANSI Z359.13-2013 4.13.1 DPT Wet | Arrest Distance | ≤ 48" | 37.7" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1296.0 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 836.5 Lbf | Pass |
| ANSI Z359.13-2013 4.13.1 DPT Wet | Arrest Distance | ≤ 48" | 40.5" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1118.9 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 810.5 Lbf | Pass |
| ANSI Z359.13-2013 4.13.1 DPT Wet | Arrest Distance | ≤ 48" | 40.2" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1175.9 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 798.1 Lbf | Pass |

This laboratory is accredited with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC Communiquedated January 2009).
FallTech Testing Laboratory utilizes the Simple Acceptance Rule and allows for a 5% tolerance on dynamic and static strength test results.

IAS ACCREDITED Testing Laboratory
Certificate# TL-594 Testing

**FallTech Testing Laboratory**
1306 S. Alameda Street,
Compton, CA 90221-4803
Tel: (323) 752-0060
www.falltech.com

# FallTech Test Report

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Test Report No.** | PC-3728 | **Rpt. Date** | 7/24/2026 | **Rpt. Rev** | | **Rev Date** | |
| **Report Prepared For** | FallTech | | | | | | |
| **Initiated By** | Zachary Winters | **Test Specification(s)** | | ANSI Z359.13-2013 (R2022)<br>4.7, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3 | | | |
| **Part No.** | 82608 | | | **Part No. Revision** | E | | |
| **Part Description** | 6' SAL Y-Legs; ViewPack with Snap Hooks | | | | | | |
| **Test Request No.** | PC-3728 | | | **Date Complete** | 7/23/2026 | | |

## Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|---|---|---|---|---|
| ANSI Z359.13-2013 4.13.2 DPT Cold | Arrest Distance | ≤ 48" | 32.8" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1185.4 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 881.1 Lbf | Pass |
| ANSI Z359.13-2013 4.13.2 DPT Cold | Arrest Distance | ≤ 48" | 33.9" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1264.0 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 869.4 Lbf | Pass |
| ANSI Z359.13-2013 4.13.2 DPT Cold | Arrest Distance | ≤ 48" | 29.0" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1218.4 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 1053.9 Lbf | Pass |
| ANSI Z359.13-2013 4.13.3 DPT Hot | Arrest Distance | ≤ 48" | 41.6" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1188.1 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 812.8 Lbf | Pass |
| ANSI Z359.13-2013 4.13.3 DPT Hot | Arrest Distance | ≤ 48" | 42.5" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1212.1 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 811.5 Lbf | Pass |
| ANSI Z359.13-2013 4.13.3 DPT Hot | Arrest Distance | ≤ 48" | 43.3" | Pass |
| | Max Arrest Force | ≤ 1800 Lbf | 1148.5 Lbf | Pass |
| | Avg Arrest Force | ≤ 1125 Lbf | 817.3 Lbf | Pass |

## Conclusion

Based upon the samples provided to the Lab:
FallTech P/N 82608 Rev. E meets the requirements of ANSI Z359.13-2013 (R2022)

## Report Signatories and Approval

| | | | |
|---|---|---|---|
| Lab Quality Manager | Jay Sponholz | Date | 7/24/2026 |

This laboratory is accredited with the recognized International Standard
ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC Communiquedated January 2009).
FallTech Testing Laboratory utilizes the Simple Acceptance Rule and allows for a 5% tolerance on dynamic and static strength test results.

IAS ACCREDITED Testing Laboratory
Certificate# TL-594 Testing