

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

D0621049

Declaration Date

6/21/2022

Tested Item #

7265CLE

60' Leading Edge 7/32" Galv Cable SRD DuraTech
w/Steel Swivel Snap Hook

Additional Items Conforming Under this Declaration:

7232XLE

7268CLE

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with
the requirements of the following product standard(s):

ANSI Z359.14-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2608

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

6/21/2022



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Material/Sample Identification

| Sample ID | Description |
|-----------|---|
| FT53794 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53773 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53830 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52566 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52563 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52543 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53817 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53842 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53779 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53808 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53133 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53791 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53822 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53772 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53791 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53840 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53745 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53774 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52561 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53087 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53137 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52592 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52587 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52641 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52613 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52629 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52611 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52642 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52636 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52571 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52591 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52628 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Material/Sample Identification (Continued)

| Sample ID | Description |
|-----------|---|
| FT52597 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52577 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52586 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52619 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52584 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52550 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52633 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52599 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52549 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT52602 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53809 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53814 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53799 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53809 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53814 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |
| FT53799 | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook |

Test Summary

| Test Specification | Test Criteria | Test Result | Pass/Fail |
|----------------------------|---|-------------|-----------|
| ANSI Z359.14-2021 4.2.1 | Static Strength ≥ 3600 Lbf for ≥ 60 Seconds | 3629.8 lbF | Pass |
| ANSI Z359.14-2021 4.2.1 | Static Strength ≥ 3600 Lbf for ≥ 60 Seconds | 3634.5 lbF | Pass |
| ANSI Z359.14-2021 4.2.1 | Static Strength ≥ 3600 Lbf for ≥ 60 Seconds | 3633.0 lbF | Pass |
| ANSI Z359.14-2021 4.4 | Energy Capacity > 1800 Lbf Max Arrest Force | 1233.7 lbF | Pass |
| ANSI Z359.14-2021 4.4 | Energy Capacity > 1800 Lbf Max Arrest Force | 1359.9 lbF | Pass |
| ANSI Z359.14-2021 4.4 | Energy Capacity > 1800 Lbf Max Arrest Force | 1270.2 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|------------------------------|------------------|--------------------------|----------------|-----------|
| ANSI Z359.14-2021 4.3.1 | Max Arrest Force | ≤ 1800 Lbf | 1304.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 952.8 lbF | Pass |
| | Arrest Distance | ≤ 42" | 41.8" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1 | Max Arrest Force | ≤ 1800 Lbf | 1367.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 998.6 lbF | Pass |
| | Arrest Distance | ≤ 42" | 41.1" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1 | Max Arrest Force | ≤ 1800 Lbf | 1608.2lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 931.4 lbF | Pass |
| | Arrest Distance | ≤ 42" | 34.9" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.7 | Max Arrest Force | ≤ 1800 Lbf | 1462.9 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 897.0 lbF | Pass |
| | Arrest Distance | ≤ 42" | 41.0" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.7 | Max Arrest Force | ≤ 1800 Lbf | 1523.4 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 881.2 lbF | Pass |
| | Arrest Distance | ≤ 42" | 42.6" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.7 | Max Arrest Force | ≤ 1800 Lbf | 1383.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 918.8 lbF | Pass |
| | Arrest Distance | ≤ 42" | 41.4" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|------------------------------|------------------|--------------------------|----------------|-----------|
| ANSI Z359.14-2021 4.3.1.8 | Max Arrest Force | ≤ 1800 Lbf | 1727.5 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 1149.7 lbF | Pass |
| | Arrest Distance | ≤ 42" | 41.3" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.8 | Max Arrest Force | ≤ 1800 Lbf | 1423.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 979.0 lbF | Pass |
| | Arrest Distance | ≤ 42" | 39.6" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.8 | Max Arrest Force | ≤ 1800 Lbf | 1756.6 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 1079.4 lbF | Pass |
| | Arrest Distance | ≤ 42" | 27.7" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.9 | Max Arrest Force | ≤ 1800 Lbf | 1484.2 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 1034.7 lbF | Pass |
| | Arrest Distance | ≤ 42" | 37.9" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.9 | Max Arrest Force | ≤ 1800 Lbf | 1550.9 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 929.0 lbF | Pass |
| | Arrest Distance | ≤ 42" | 35.6" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| ANSI Z359.14-2021 4.3.1.9 | Max Arrest Force | ≤ 1800 Lbf | 1619.3 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 918.9 lbF | Pass |
| | Arrest Distance | ≤ 42" | 39.8" | Pass |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | Test Result | Pass/Fail | |
|--|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1221.5 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 880.9 lbF | Pass |
| | Arrest Distance | Not Applicable | 105.8" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 711.4 lbF | Pass |
| ANSI Z359.14-2021 4.3.3 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1230.6 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 859.9 lbF | Pass |
| | Arrest Distance | Not Applicable | 103.3" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 700.4 lbF | Pass |
| ANSI Z359.14-2021 4.3.3 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1210.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 871.0 lbF | Pass |
| | Arrest Distance | Not Applicable | 103.4" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 699.1 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.8 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1220.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 874.1 lbF | Pass |
| | Arrest Distance | Not Applicable | 109.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 701.2 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|--|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3.8 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1315.4 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 876.6 lbF | Pass |
| | Arrest Distance | Not Applicable | 108.3" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 696.0 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.8 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1320.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 837.8 lbF | Pass |
| | Arrest Distance | Not Applicable | 110.1" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 702.1 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.9 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1461.5 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 1003.6 lbF | Pass |
| | Arrest Distance | Not Applicable | 93.5" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 716.4 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.9 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1443.6 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 988.4 lbF | Pass |
| | Arrest Distance | Not Applicable | 94.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 797.8 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|---|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3.9 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1470.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 979.9 lbF | Pass |
| | Arrest Distance | Not Applicable | 96.4" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 736.1 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1219.9 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 905.0 lbF | Pass |
| | Arrest Distance | Not Applicable | 101.8" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 742.2 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1224.0 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 869.3 lbF | Pass |
| | Arrest Distance | Not Applicable | 101.7" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 703.9 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Perpendicular) | Max Arrest Force | ≤ 1800 Lbf | 1199.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1575 Lbf | 882.2 lbF | Pass |
| | Arrest Distance | Not Applicable | 103.4" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 694.5 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | Test Result | Pass/Fail | |
|---|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1422.4 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 805.1 lbF | Pass |
| | Arrest Distance | Not Applicable | 120.5" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 705.7 lbF | Pass |
| ANSI Z359.14-2021 4.3.3 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1170.8 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 869.8 lbF | Pass |
| | Arrest Distance | Not Applicable | 110.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 856.8 lbF | Pass |
| ANSI Z359.14-2021 4.3.3 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1163.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 865.3 lbF | Pass |
| | Arrest Distance | Not Applicable | 126.5" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 695.2 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.8 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1435.6 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 897.7 lbF | Pass |
| | Arrest Distance | Not Applicable | 120.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 697.4 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|---|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3.8 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1446.1 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 889.7 lbF | Pass |
| | Arrest Distance | Not Applicable | 115.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 695.7 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.8 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1412.1 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 896.4 lbF | Pass |
| | Arrest Distance | Not Applicable | 116.9" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 698.6 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.9 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1814.8 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 1151.2 lbF | Pass |
| | Arrest Distance | Not Applicable | 111.3" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 695.3 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.9 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1559.3 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 1001.7 lbF | Pass |
| | Arrest Distance | Not Applicable | 112.3" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 698.7 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |

Test Summary (Continued)

| Test Specification | Test Criteria | Test Result | Pass/Fail | |
|--|---------------------------|-------------------------------|----------------|------------------|
| ANSI Z359.14-2021 4.3.3.9 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1585.6 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 870.3 lbF | Pass |
| | Arrest Distance | Not Applicable | 118.8" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 706.5 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1388.5 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 907.2 lbF | Pass |
| | Arrest Distance | Not Applicable | 115.3" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 697.7 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1607.7 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 932.2 lbF | Pass |
| | Arrest Distance | Not Applicable | 122.2" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 697.3 lbF | Pass |
| ANSI Z359.14-2021 4.3.3.10 (Lateral Offset) | Max Arrest Force | ≤ 1800 Lbf | 1193.9 lbF | Pass |
| | Avg Arrest Force | ≤ 1350 Lbf | 848.1 lbF | Pass |
| | Arrest Distance | Not Applicable | 112.6" | Information only |
| | Visual Indicator | Clear evidence of Impact | Clear Evidence | Pass |
| | Line Constituent Strength | > 675 Lbf for > 60 Seconds | 702.8 lbF | Pass |

FallTech Test Report

| | | | | | | | |
|----------------------------|---|------------------------------|--|-----------------|--|-----------------|--|
| Test Report No. | PC-2608 | Rpt. Date | 6/21/2022 | Rpt. Rev | | Rev Date | |
| Report Prepared For | FallTech | | | | | | |
| Initiated By | Dan Redden | Test Specification(s) | ANSI Z359.14-2021: 4.2.1, 4.2.3, 4.3.1 4.3.3, 4.5.1, 4.5.2 | | | | |
| Part No. | 7265CLE | Part No. Revision | K | | | | |
| Part Description | 60' Leading Edge 7/32" Galv Cable SRD DuraTech w/ Steel Swivel Snaphook | | | | | | |
| Test Request No. | PC-2608 | Date Complete | 6/20/2022 | | | | |
| Test Operator(s) | Yesbet Sierra / Jay Sponholz | | | | | | |


Test Summary (Continued)

| Test Specification | Test Criteria | | Test Result | Pass/Fail |
|----------------------------|--------------------------------------|-------------------------------------|-----------------------------|-----------|
| ANSI Z359.14-2021 4.5.1 | Retraction Tension 0% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 1.9 lbF | Pass |
| | Retraction Tension 50% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 1.6 lbF | Pass |
| | Retraction Tension 100% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 2.1 lbF | Pass |
| ANSI Z359.14-2021 4.5.1 | Retraction Tension 0% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 1.6 lbF | Pass |
| | Retraction Tension 50% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 2.2 lbF | Pass |
| | Retraction Tension 100% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 2.5 lbF | Pass |
| ANSI Z359.14-2021 4.5.1 | Retraction Tension 0% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 1.5 lbF | Pass |
| | Retraction Tension 50% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 2.0 lbF | Pass |
| | Retraction Tension 100% Extracted | 1.25 Lbf - 25 Lbf ≤ 48" Extended | 2.3 lbF | Pass |
| ANSI Z359.14-2021 4.5.2 | Horizontal Retraction | Retract without Stopping | No Hesitation in Retraction | Pass |
| ANSI Z359.14-2021 4.5.2 | Horizontal Retraction | Retract without Stopping | No Hesitation in Retraction | Pass |
| ANSI Z359.14-2021 4.5.2 | Horizontal Retraction | Retract without Stopping | No Hesitation in Retraction | Pass |

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 7265CLE Rev. K meets the requirements of ANSI Z359.14-2021

Report Signatories and Approval

| | | | |
|---------------------|---|------|-----------|
| Lab Quality Manager |  | Date | 6/21/2022 |
|---------------------|---|------|-----------|