

# TRIPLE ACTION SRD CONNECTOR 5073H

## Compact. Versatile. Durable.

Intuitive and simple to use, its compact design is easy to install and works with all thicknesses of webbings including coated webbing for universal use on a job site. The lightweight design does not add additional weight and it can be worn for extended hours without causing stress on the body allowing increased productivity on the job site. The Triple Action SRD Connector has a red locking indicator on the slide pin that when locked, is hidden in the connector as a visual indicator the connector is locked for added confidence to the user.



5073H

- **Quick and Simple** – Easy to use with full protection.
- **Dual-Locking** – The connector offers a dual locking mechanism whereby both release buttons must be depressed in order to deactivate and release locking bar.
- **Strength** – Greater than 5,000 lb. connector safely attaches the SRD to a harness for complete safety.
- **Durable** – The locking SRD Connector is constructed with zinc plated forged alloy steel.
- **Compact Size** – 4" x 1½", does not protrude from the harness nor creates a snag point.
- **Versatile Connection** – the connector can accommodate both single and twin leg Mini SRDs.
- **User Capacity** – OSHA 130 to 425 lbs.
- Complies with the following ANSI and OSHA requirements
  - ANSI: Z359.14-2014, - when connected to the Triple Action SRD Connector, the MINI SRDs are Z359.14-2014 Compliant
  - OSHA: 1926.502, 1910.66

To learn more visit us at:

[www.falltech.com](http://www.falltech.com)



 **FALLTECH**<sup>®</sup>  
Fall Protection. Precision Engineered.