

# 45' Technora® Rope DuraTech® SRL-R


The DuraTech® SRL-Rs are designed for long lasting performance in fall arrest applications that may require emergency rescue and retrieval functions in a single device.

## Technora® Rope:

- 8 times stronger than steel
- High temperature resistance (500 degrees F)
- UV-resistant urethane coating
- Negligible creep and elongation
- High chemical resistance

Powder coated aluminum alloy housing and zinc plated steel bracket for durable performance

1/4" Technora® Synthetic Rope Lifeline



Built-in carrying handle for easy transport and installation. Also functions as overhead anchorage connection point



Collapsible rescue/retrieval mode handle



Handle shown in closed position

ANSI Z359.12 compliant Load indicating swivel snaphook

## 45' Technora® Rope DuraTech® SRL-R



Technora® Rope DuraTech® SRL-R shown mounted on a Tripod System (7275)



Technora® Rope DuraTech® SRL-R shown mounted on Davit System (6050128)

### Material Specifications

<b>Housing</b>	Aluminum Alloy
<b>Lifeline Constituent</b>	1/4" Technora® Synthetic Rope Min. 4,500 lbs. Tensile Strength
<b>Bracket</b>	Zinc Plated Alloy Steel Min. 3,000 lbs. Tensile Strength
<b>Load Indicating Swivel Snaphook</b>	Zinc Plated Alloy Steel Min. 5,000 lbs. Tensile Strength with 3,600 lbs. Gate Strength

### Relevant Standards

<b>ANSI</b>	Z359.14-2014 Class B
<b>OSHA</b>	1910.140, 1926.502

### Performance Specifications

<b>ANSI SRL Class</b>	SRL-R Class B
<b>Average Arrest Force</b>	1,125 lbs. Maximum
<b>Maximum Arrest Force</b>	1,800 lbs.
<b>Maximum Arrest Distance</b>	54" or Less
<b>Static Strength</b>	3,000 lbs. Minimum
<b>ANSI User Capacity</b>	One User up to 310 lbs. Maximum

### Part Numbers & Lengths

<b>Part No.</b>	<b>7281DT</b>	<b>7281TT</b>
<b>Rope Length</b>	45'	