



The CTR™ is the latest addition to FallTech's lineup of industry-leading fall protection hardware.

Introducing the CTR, an ANSI Class 2 Self-Retracting Lifeline (SRL) that sets a new standard for safety and efficiency. Engineered for smooth and precise movement, the CTR features a lightweight yet robust design, offering exceptional durability at an outstanding value.

The CTR features a durable, lightweight, composite housing, a 7/32-inch galvanized steel cable capable of supporting workers up to 310 pounds, and a high-strength composite fabric handle. Engineered for tough conditions, this SRL delivers reliable performance in harsh environments. The CTR also prioritizes features for an exceptional end-user experience, using an innovative linear spring mechanism that ensures fluid motion, eliminating the jarring movement common in other SRLs.

Upgrade your safety equipment with the CTR—where strength, comfort, and value converge.

Available Options:

20'

30'

60'



723720LE



723730LE



723760LE

Please Contact Your FallTech Regional Sales Manager to Learn More.

The CTR is Available in the Following Lengths:

Part Number	SRL Length
723720LE	20'
723730LE	30'
723760LE	60'

The CTR Complies with the Following Standards:

- ANSI Z359.14-2021
- OSHA 1910.140
- OSHA 1926.502
- CSA Z259.2.2-2017

Below are Performance Specifications:

- **Max Arrest Force:** 1,800 lb
- **Average Arrest Force:** 1,575 lb or less
- **Max Arrest Distance:** 42 in. or less
- **Static Strength:** 3,600 lb min.
- **User Capacity:** 130 to 310 lb

Below are Material Specifications:

- **Lifeline:** 7/32" galvanized steel wire rope (3,600 lb min. strength)
- **Energy Absorber:** Polyester tear-away
- **Lifeline Connector:** Plated alloy steel (5,000 lb min. strength with 3,600 lb gate strength)
- **Anchorage Connector:** Plated alloy steel (5,000 lb min. strength with 3,600 lb gate strength)