

DURATECH[®] STAINLESS STEEL

SELF RETRACTING LIFELINES

ANSI Z359.14-2014 Compliant

DuraTech[®] SRLs deliver proven performance and reliability that users depend on every day and, the reduced activation and arresting distances deliver lower minimum required fall clearances. Built with precision machined aluminum alloy drums and housings, dual internal inertial brake discs, brass pawls, lightweight manganese ratchet centers, and aluminum main shafts, DuraTech SRLs are available in a variety of lengths from 20' to 60' to fit most overhead fall arrest applications.

DuraTech[®] SRLs feature a side-payout housing design for uniform operation and reduced wear on the orifice and provide a stackable function for easy storage. Furnished with an internal braking system that delivers positive deceleration, a load-indicating swivel snap hook and our Recoil Spring hand-grip assembly to help prevent accidental user lock-up.

DuraTech[®] CS-series SRLs include 3/16" stainless steel cable lifelines for longer service life compared to standard galvanized steel cable. Additionally, we also offer CSS-series SRLs with additional stainless steel components including the load-indicating swivel snap hook and the internal pressure plate. All CS and CSS-series SRLs deliver the



7268CSS
50' DuraTech Cable SRL



3/16" stainless steel cable featured on all CS and CSS-series



Stainless Steel Swivel Snap Hook and Pressure Plate included with CSS-series



Side-payout Housing featured on all CS and CSS-series



Unique housing design allows stackability among all sizes.

