



The Ultimate Safety Harness for the Women of General Industry

The **FT-1910 Fit™** redefines safety gear for women in general industry. Crafted with advanced materials and designed for a precision fit, this premium full-body harness tackles the demands of female maintenance professionals head-on.

This Premium Harness Features:

Tailored Hip Adjustability

Adjustable sub pelvic strap ensures a precise fit for women, eliminating the discomfort of one-size-fits-all harnesses.

UltraTech™ Webbing

Webbing has a moisture-resistant, antimicrobial treatment for durable protection against moisture, bacteria, and grime.

Unprecedented Mobility

Comes with lateral leg straps for maximum mobility and pinch-free movement.

Stainless Steel Grommets

Tongue-buckle leg closures have stainless steel grommets for corrosion resistance.

Available Options:

1D Standard Non-Belted



1910F



1910FQC



1910F3D



1910F3DQC

All options available with quick-connect or tongue-buckle leg closures and in sizes XS to 3XL.

Contact Your FallTech Regional Sales Manager to Learn More.



FT-1910 Fit™

The FT-1910 Fit will Launch with the Following Part Numbers:

Part Number	Model	Leg Closures
1910F	1D Standard Non-Belted	Tongue Buckle
1910FQC		Quick-Connect
1910F3D	3D Standard Non-Belted	Tongue Buckle
1910F3DQC		Quick-Connect

The FT-1910 Fit Complies with the Following Standards:

- ANSI Z359.11-2021
- OSHA 1910.140
- OSHA 1926.502

Performance Specifications:

- **Static Strength:** 3,600 lb min.
- **ANSI User Capacity:** 130 to 310 lb
- **OSHA User Capacity:** 130 to 425 lb

Material Specifications:

- **Webbing:** Polyester (5,000 lb min. strength)
- **D-Rings:** Aluminum alloy (5,000 lb min. strength)
- **Adjusters:** Aluminum alloy (3,372 lb min. strength)
- **Quick-Connect Buckles:** Plated alloy steel (3,372 lb min. strength)
- **Tongue Buckles:** Plated alloy steel (3,372 lb min. strength)

Contact Your FallTech Regional Sales Manager to Learn More.