



FT-One Fit™
**WOMENS
FULL BODY
HARNESS**

Patent Pending



The **FT-One Fit™** premium full-body harness allows every woman to create a customized fit for her shape. The exclusive hip adjustability ensures a proper fit for her hips. She is no longer forced to compromise and wear a harness that is not her optimal size. The new innovative **Comfort Legs™** straps reduce binding, chafing, and significantly improves mobility. The slip-resistant **ArrowGrip®** D-ring plate secures the D-ring in place, alleviating back discomfort. Personalized fit and comfort, all in one durable and lightweight premium harness.

Premium Body Harness

FT-One Fit™



Upgraded Lanyard Keepers

We installed durable lanyard keepers that provide robust functionality for single and double-leg lanyards. They add versatility and reusability while maintaining ANSI compliance.



Abrasion Resistant Shoulder Panels

Don't let your shoulder pads wear out prematurely from constant use and carrying heavy loads. Our industry-exclusive shoulder material helps alleviate excess wear, keeping your harness in service longer.



Suspension Trauma Relief Packs

Our suspension trauma relief system helps minimize the effect of being suspended while awaiting rescue. The adjustable length step-in loop design accommodates both of the user's feet to relieve pressure and improve balance.



Exclusive Comfort Legs™

These game-changing lateral leg straps greatly improve both mobility and comfort. Our revolutionary form-fitting straps wrap easily around your thighs – away from sensitive pinch points.



Front View

The **FT-One Fit™** premium full-body harness allows every woman to create a customized fit for her shape. The exclusive hip adjustability ensures a proper fit for her hips. She is no longer forced to compromise and wear a harness that is not her optimal size. The new innovative **Comfort Legs™** straps reduce binding, chafing, and significantly improves mobility. The slip-resistant **ArrowGrip®** D-ring plate secures the D-ring in place, alleviating back discomfort. Personalized fit and comfort, all in one durable and lightweight premium harness.

Premium Body Harness

FT-One Fit™



Slip-Resistant ArrowGrip® D-Ring Plate

Keeps your dorsal D-ring positioned correctly and keeps harness adjustments to a minimum throughout the day. Don't let D-ring slippage compromise your safety or comfort.



Neoprene Neck Guard

Say goodbye to painful neck irritation. The FT-One's neoprene-lined shoulder pad reduces neck abrasion, enhancing harness comfort all day long.



Hip Adjustability

Exclusive to the FT-One Fit, the patent pending adjustable sub-pelvic strap ensures a proper fit, allowing maximum comfort for all body types.



Updated SRL Attachment Point

Our convenient SRL attachment design lets you connect all types of single and twin SRLs – faster and easier than ever. No more fumbling with the harness webbing every time you connect.

Back View

Model 8129QC FT-One Fit™ 1D Standard Non-Belted Premium Full Body Harness with quick connect chest and leg closure is lightweight and provides you the maneuverability to get your job done right with legs straps for all day comfort.



Front



Back

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	ANSI Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Polyester 5,000 lbs. min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. min. Strength
Tongue Buckles	Plated Alloy Steel 3,372 lbs. min. Strength

Standard Non-Belted		
Part#	Sizes	Leg Closure
8129QCXS	Extra Small	Quick Connect
8129QCS	Small	
8129QCM	Medium	
8129QCL	Large	
8129QCXL	Extra Large	
8129QC2X	2X Large	
8129QC3X	3X Large	

Model 8129 FT-One Fit™ 1D Standard Non-Belted Premium Full Body Harness with quick connect chest and tongue buckle leg closure is lightweight and provides you the maneuverability to get your job done right with legs straps for all day comfort.



Front

Back

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	ANSI Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Polyester 5,000 lbs. min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. min. Strength
Tongue Buckles	Plated Alloy Steel 3,372 lbs. min. Strength

Standard Non-Belted		
Part#	Sizes	Leg Closure
8129XS	Extra Small	Tongue Buckle
8129S	Small	
8129M	Medium	
8129L	Large	
8129XL	Extra Large	
81292X	2X Large	
81293X	3X Large	

Model 81293DQC FT-One Fit™ 3D Standard Non-Belted Premium Full Body Harness with quick connect chest and leg closure is lightweight and provides you the maneuverability to get your job done right with legs straps for all day comfort.



Front



Back

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	ANSI Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Polyester 5,000 lbs. min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. min. Strength
Tongue Buckles	Plated Alloy Steel 3,372 lbs. min. Strength

Standard Non-Belted		
Part#	Sizes	Leg Closure
81293DQCXS	Extra Small	Quick Connect
81293DQCS	Small	
81293DQCM	Medium	
81293DQCL	Large	
81293DQCXL	Extra Large	
81293DQC2X	2X Large	
81293DQC3X	3X Large	

Model 81293D FT-One Fit™ 3D Standard Non-Belted Premium Full Body Harness with quick connect chest and tongue buckle leg closure is lightweight and provides you the maneuverability to get your job done right with legs straps for all day comfort.



Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	ANSI Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Polyester 5,000 lbs. min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. min. Strength
Tongue Buckles	Plated Alloy Steel 3,372 lbs. min. Strength

Standard Non-Belted		
Part#	Sizes	Leg Closure
81293DXS	Extra Small	Tongue Buckle
81293DS	Small	
81293DM	Medium	
81293DL	Large	
81293DXL	Extra Large	
81293D2X	2X Large	
81293D3X	3X Large	

Discover the full selection of all
our fall protection products at
www.FallTech.com



Tel / 323.752.0066

Fax / 323.752.5613

**©2021 Alexander Andrew, Inc
1306 S. Alameda St. Compton,
CA. 90221-4803**

Tools shown not included.

Product description and specifications
herein may change without notice.

U.S. and International Patents Pending.



@falltechsafety



@falltech



@falltechsafety



@falltech