



FALLTECH®

**FT-ONE
FIT**

Women's Full-Body Harness

Meet the **FT-One Fit™** –the first premium full-body harness made for women working at height. With patented hip adjustability, high-mobility lateral leg straps, and the gel cushioning throughout, this harness delivers comfort, mobility, and a secure fit without compromise. Available in belted and non-belted versions.

Tailored Hip Adjustability

Exclusive hip adjustment technology ensures a precise fit for women, eliminating the discomfort of one-size-fits-all harnesses.

Modular Belt System™

A modular belt-lacing system allows users to adjust tool pouch positions for optimal comfort and efficiency. (Belted versions only.)

Tool Tether Anchor Points

Four ANSI/ISEA 121-compliant tool tether anchor attachments, rated at 5 pounds each, ensure secure and convenient tool access around the waist. (Belted versions only.)

Comfort Gel Padding

Gel padding cushions while maintaining airflow, dispersing pressure, and reducing fatigue to sustain performance.

ArrowGrip® D-Ring Plate

Slip-resistant plate keeps dorsal D-ring positioned correctly, minimizing harness adjustments.

Available in Non-Belted and Belted versions



Front



Back



Front



Back

All options available with quick-connect or tongue buckle leg closures and in sizes XS to 3XL.

Please Contact Your FallTech Regional Sales Manager to Learn More.

FT-One Fit™ Full-Body Harness

| Part Number | Description |
|-------------|---|
| 8129 | 1D Standard Non-Belted, Tongue Buckle Leg Adjustments |
| 8129QC | 1D Standard Non-Belted, Quick-Connect Adjustments |
| 81293D | 3D Standard Non-Belted, Tongue Buckle Leg Adjustments |
| 81293DQC | 3D Standard Non-Belted, Quick-Connect Adjustments |
| 8130 | 3D Construction Belted, Tongue Buckle Leg Adjustments |
| 8130QC | 3D Construction Belted, Quick-Connect Adjustments |
| 8130FD | 4D Construction Climbing, Tongue Buckle Leg Adjustments |
| 8130FDQC | 4D Construction Climbing, Quick-Connect Adjustments |

Available in sizes from extra small to 3XL.

The FT-One Fit complies with the following standards:

- ANSI Z359.14-2021
- OSHA 1910.140
- OSHA 1926.502

Below are performance specifications:

- Static Strength: 3,600 lb min.
- ANSI User Capacity: One user up to 310 lb
- OSHA User Capacity: One user up to 425 lb

Below are material specifications:

- Webbing: Polyester (5,000 lb min. static strength)
- D-Rings: Aluminum Alloy (5,000 lb min. static strength)
- Buckles and Adjusters: Aluminum Alloy and Plated Alloy Steel (3,372 lb min. static strength)