

FALLTECH®




**FT-A**  
*SRL-A*  
Premium SRL-R

The FT-R SRL-R represents the best of FallTech engineering—built on the proven FT-R platform and enhanced for retrieval applications. It delivers the same lightweight design, smooth payout, and dependable operation users trust, with an intuitive transition from SRL to retrieval when the job demands it. This is premium performance, refined for confident entry and fast response.



**01 DUAL-MODE FUNCTIONALITY**

Simplified controls make switching from fall arrest to rescue fast and direct—just pull the plunger pin and shift the crank. No tools. No delays.



**02 OPTIMIZED MOVEMENT**

A refined internal system cuts down nuisance lockups, delivering smooth, natural motion every step.



**03 LIGHTWEIGHT & ROBUST DESIGN**

Engineered to be lighter than leading units without giving up an ounce of strength.



**04 EASY INSTALLATION**

Fast, secure mounting to tripods or modular davits ensures reliable performance in the tightest spaces.



**05 LOW-PROFILE SHOCK PACK**

A compact energy absorber built to support workers up to 310 pounds with confidence.



**06 PROTECTED LABELS**

UV- and scratch-resistant labels help keep key information legible—and units compliant—in tough work environments.





When rescue is on the line, there is no room for error. That's why the FT-R SRL-R is engineered and tested to the strictest ANSI standards, delivering the trusted performance workers expect and deserve. The FT-R SRL-R is Class 1 rated for anchoring at, above, or up to 5 feet below D-ring on worksites without edge exposure.



### RELEVANT STANDARDS

- ANSI Z359.14-2021
- OSHA 1910.140
- OSHA 1926.502

### MATERIAL SPECIFICATIONS

- **Housing:** Glass-Reinforced Nylon
- **Lifeline:** 7/32" Galvanized Steel Wire Rope (3,600 lb. min. strength)
- **Lifeline Connector:** Plated Alloy Steel (5,000 lb. min. strength with 3,600 lb. min. gate strength)
- **Anchorage Connector:** Plated Alloy Steel (5,000 lb. min. strength with 3,600 lb. min. gate strength)

### PERFORMANCE SPECIFICATIONS

- **Max Arrest Force:** 1,800 lbs.
- **Average Arrest Force:** 1,575 lbs. or less
- **Static Strength:** 3,600 lbs. (min.)
- **Max User Capacity (ANSI):** 310 lbs.
- **Max User Capacity (OSHA):** 420 lbs.

Part Number	Description
721560R	FT-R SRL-R (60')
7508B	8' Tripod Kit w/ FT-R SRL-R (721560R) + Storage Bags
7509B	8' Tripod Kit w/ FT-R SRL-R (721560R) and Personnel Winch (7297) + Storage Bags
7500B	11' Tripod Kit w/ FT-R SRL-R (721560R) + Storage Bags
7504B	11' Tripod Kit w/ FT-R SRL-R (721560R) and Personnel Winch (7297) + Storage Bags

---

# Find Our Full Selection of Fall Protection Products at FallTech.com

---



©2025 Alexander Andrew, Inc.  
1306 S. Alameda St.  
Compton, CA 90221-4803

Tel / 323.752.0066

Fax / 323.752.5613

Tools shown not included.

Product description and specifications  
herein may change without notice.

U.S. and International Patents Pending.

