

FALLTECH®

FT-R
SRL-R

Confined Space Safety—Redefined



When work takes you into tanks, tunnels, or vaults, your gear must do more than protect the entry—it must ensure a safe way out.

The **FT-R SRL-R** is purpose-built for the toughest confined space work: where safety, speed, and reliability can't be compromised. From tanks to tunnels to vaults, this dual-mode self-retracting lifeline goes beyond standard fall protection, combining entry protection with critical retrieval capability.

Built on the trusted FT-R platform, this SRL-R delivers lightweight handling, smooth lifeline payout, and compact energy absorption with integrated retrieval functionality. By pulling the release pin, the attendant can immediately engage the SRL-R handle and transition into rescue mode. Rotating clockwise lowers the worker in a controlled descent, while counterclockwise rotation raises them safely and steadily.

When every second counts, the **FT-R SRL-R** is your lifeline to rescue.

Features:

Dual-Mode Functionality

Dual-purpose functionality allows for quick, seamless transition from fall arrest to emergency retrieval. No extra tools or equipment needed.

Lightweight & Robust Design

Compact, rugged housing with UV- and scratch-resistant labeling—over 30% lighter than comparable SRL-Rs for easier transport and faster setup.

Versatile Mounting

Mounts to tripods or modular davit systems for dependable operation in even the tightest spaces.

ANSI Class 1

Compliant and safe for anchoring at or above the worker's D-ring, away from edge exposures.

Wherever the space, the **FT-R SRL-R** helps ensure that when workers go in, they can come back out.



Please Contact Your FallTech Regional Sales Manager to Learn More.

FT-R® SRL-R

This SRL-R will Launch with the Following Part Numbers:

Part Number	Description
721560R	FT-R SRL-R (60')
7508B	8' Tripod Kit w/ FT-R SRL-R (721560R) + Storage Bags
7509B	8' Tripod Kit w/ FT-R (721560R) and Personnel Winch (7297) + Storage Bags
7500B	11' Tripod Kit w/ FT-R SRL-R (721560R) + Storage Bags
7504B	11' Tripod Kit w/ FT-R SRL-R (721560R) and Personnel Winch (7297) + Storage Bags

Compliant with:

- ANSI Z359.14-2021
- OSHA 1910.140
- OSHA 1926.502

Performance Specifications:

- **Max Arrest Force:** 1,800 lbs.
- **Average Arrest Force:** 1,575 lbs. or less
- **Max Arrest Distance:** 42 in. or less
- **Static Strength:** 3,600 lbs. (min.)
- **Max User Capacity (ANSI):** 310 lbs.
- **Max User Capacity (OSHA):** 420 lbs.

Material Specifications:

- **Housing:** Glass-Reinforced Nylon
- **Cable:** 7/32" Galvanized Steel Wire Rope (3,600 lb. min. strength)
- **Lifeline Connector:** Plated Alloy Steel (5,000 lb. min. strength with 3,600 lb. min. gate strength)
- **Anchorage Connector:** Plated Alloy Steel (5,000 lb. min. strength with 3,600 lb. min. gate strength)