

 FALLTECH®



FT-X™

WEB

Patent Pending

FallTech® introduces the lightweight 11' Web FT-X™ Class 1 Self-retracting Lifeline engineered for those who will not compromise on safety, compliance, worker comfort, and worker efficiency when working at height.

8' Class 1

FT-X™ Web



Lightweight, Durable Housing

Engineered housing material provides durability at low weight. Light green color distinguishes the non-leading edge capability of Class 1 SRLs.




Optimized Lock-up Speed

Internal mechanism design minimizes unintentional lockups to keep you moving freely with no interruption in productivity.



Compact, Extended Capacity Energy Absorber

420 lb. worker rated extended capacity energy absorber is protected by abrasion resistant cover.



ANSI Z359.14-2021 Class 1 Compliant

Suitable for at or above D-ring tie-off within the scope of ANSI Z359. Outside the scope of ANSI Z359, suitable for below D-ring tie-off up to five feet without edge hazards.



Labels

Comprehensive fall clearance charts and tables included inside the energy absorber cover offer easy reference for safety at all times.



Dyneema Lifeline

Dyneema lifeline provides ultimate durability with industry proven strength.

84711SC1

Patent Pending

FallTech® introduces the lightweight 11' Web FT-X™ Class 1 Self-retracting Lifeline engineered for those who will not compromise on safety, compliance, worker comfort, and worker efficiency when working at height.

8' Class 1

FT-X™ Web



| 84711SC3



| 84711SG4



Steel Snap Hook



Steel Rebar Hook



Aluminum Snap Hook

Part #	Harness Connector	Leg-end Connector
84711SA1	Swivel Eye	Steel Snap Hook
84711SA3	Swivel Eye	Steel Rebar Hook
84711SA4	Swivel Eye	Aluminum Snap Hook
84711SC1	Steel Carabiner	Steel Snap Hook
84711SC3	Steel Carabiner	Steel Rebar Hook
84711SG4	Aluminum Carabiner	Aluminum Snap Hook

Performance Specifications	
ANSI SRL Class/Type	Class 1 SRL-P
Maximum Arrest Force	1,800 lb
Average Arrest Force	1,575 lb or less
Maximum Arrest Distance	42 in or less
Static Strength	3,600 lbs Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	One User up to 420 lbs. Max

Material Specifications	
Housing	Nylon
Lifeline	Dyneema (Min. 3,600 lbs)
Leg-end Connector	Variable (5,000 lb min. strength with 3,600 lb min. gate strength)
Dorsal Connector	Variable (5,000 lb min. strength)

Relevant Standards	
ANSI	ANSI Z359.14-2021 Class 1
OSHA	1926.502, 1910.140



Discover the full selection of all
our fall protection products at
www.FallTech.com



Tel / 323.752.0066

Fax / 323.752.5613

**©2023 Alexander Andrew, Inc
1306 S. Alameda St. Compton,
CA. 90221-4803**

Tools shown not included.

Product description and specifications
herein may change without notice.

U.S. and International Patents Pending.

Part #480-00053



@falltechsafety



@falltech



@falltechsafety



@falltech