



**FALLTECH**<sup>®</sup>

**FULL BODY  
HARNES**

*Patent Pending*

**TRADESMAN  
PRO**

The Tradesman® Pro full body harness series might be the perfect fit you're looking for. While prioritizing comfort and productivity, the Tradesman® Pro has premium features you use most in a refined harness, and includes a low-profile look with all-black plated alloy finish hardware.

Full Body Harness

Tradesman® Pro



### V-slot Locking D-ring Plate

V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day



### SRL Attachment Point

Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back reducing fatigue.



### Suspension Trauma Relief Straps

Includes low-profile suspension trauma relief straps that are easily accessible and deployable with a gloved hand



### Quick-connect Chest Buckle

Features quick-connect chest buckle with visual indicator showing positive connection



### Durable, Supportive Waist Pad

Durable, wide waist belt distributes tool or equipment loads evenly for improved support and comfort without folding

The Tradesman® Pro full body harness series might be the perfect fit you're looking for. While prioritizing comfort and productivity, the Tradesman® Pro has premium features you use most in a refined harness, and includes a low-profile look with all-black plated alloy finish hardware.



Front



Back

#### Performance Specifications

Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max

#### Relevant Standards

ANSI	Z359.11-2021
OSHA	1910.140, 1926.502

#### Material Specifications

Webbing	Polyester (5,000 lbs min. Strength)
D-Ring	Plated Alloy Steel (5,000 lbs min. strength)
Adjusters	Plated Alloy Steel (3,372 lbs min. strength)
Quick Connect Buckles	Plated Alloy Steel (3,372 lbs min. strength)
Tongue Buckles	Plated Alloy Steel (3,372 lbs min. strength)

#### Construction Belted

Part#	Sizes	Leg Closure
7078CSM	S/M	Tongue Buckle
7078CLX	L/XL	
7078C2X3X	2X/3X	

The Tradesman® Pro full body harness series might be the perfect fit you're looking for. While prioritizing comfort and productivity, the Tradesman® Pro has premium features you use most in a refined harness, and includes a low-profile look with all-black plated alloy finish hardware.



Front



Back

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	Z359.11-2021
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Polyester (5,000 lbs min. Strength)
D-Ring	Plated Alloy Steel (5,000 lbs min. strength)
Adjusters	Plated Alloy Steel (3,372 lbs min. strength)
Quick Connect Buckles	Plated Alloy Steel (3,372 lbs min. strength)
Tongue Buckles	Plated Alloy Steel (3,372 lbs min. strength)

Construction Belted		
Part#	Sizes	Leg Closure
7008CSM	S/M	Tongue Buckle
7008CLX	L/XL	
7008C2X3X	2X/3X	

Discover the full selection of all  
our fall protection products at  
[www.FallTech.com](http://www.FallTech.com)



Tel / 323.752.0066

Fax / 323.752.5613

©2023 Alexander Andrew, Inc  
1306 S. Alameda St. Compton,  
CA. 90221-4803

Tools shown not included.

Product description and specifications  
herein may change without notice.

U.S. and International Patents Pending.

