



Ref: BMH/049/2024

MAPEI UK LTD
HEAD OFFICE
Mapei House, Steel Park Road
Halesowen, B62 8HD
Tel: 0121 508 6970
Fax: 0121 508 6967
info@mapei.co.uk

MAPEI WORLD LONDON CITY
6 Great Sutton Street
London, EC1V 0BX
Tel: 0203 302 9610
clerkenwell@mapei.co.uk

www.mapei.co.uk

Outline Specification

Mapei Eco Prim T Plus Acrylic Primer for Absorbent and Non-Absorbent Substrates.

Introduction

This specification is for the application of Mapei Eco Prim T Plus acrylic primer onto prepared absorbent and non-absorbent subfloors.

Surface Preparation

Substrate must be of sound construction, clean, laitance and contamination free, smooth, flat, and contain an effective structural damp proof membrane.

Application

Applied neat onto non-absorbent substrates and applied diluted 1-2 with clean water onto absorbent substrates including not gypsum based screeds.

Coverage

0.2-0.4kg/m² per coat (approx. 50sqm per 5kg applied neat and 150sqm per kg applied diluted 1-2)

Unit size

10kg

Shelf life

Stored for 12 months, in its original, well-sealed packaging in a dry place protected from frost.

Application Temperature

+5°C to +35°C.

Additional system components

Latexplan Trade
Latexplan No Ammonia
Ultraplan Renovation
screed 3240
Mapeproof One Coat
Mapeproof 1K Turbo

Latexplan Trade Fast
Ultraplan Eco 3210
Mapeproof ESM

Additional information

Please consult Health & Safety, product and application data or contact our Technical Services Department on 0121 5086970 or email technical@mapei.co.uk.

If you require a full NBS, letter recommendation, further specification information or standard details, please email specifications@mapei.co.uk

Technical Information:

Mapei Eco Prim T Plus is an acrylic primer for internal use to improve the adhesion of Mapei smoothing compounds onto absorbent and non-absorbent subfloors. Mapei Eco Prim T Plus is used neat onto non-absorbent substrates, including Mapei surface applied damp proof membranes, and diluted 1-2 with clean water when used onto absorbent substrates.

CERTIFIED
MANAGEMENT SYSTEMS



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI ISO 45001:2018

TECHNICAL DATA

Consistency:	Fluid Liquid
Colour:	Light Blue
Unit Size:	5kg 20kg
Density: (g/m³):	1.02
Dry Solids Content (%):	43

APPLICATION DATA (at 23°C – 50% R.H.)

Application Temperature Range:	+5°C to +35°C
Application:	Neat onto non-absorbent substrates Diluted 1-2 with clean water onto absorbent substrates including gypsum based screeds
Drying Time:	Neat Application – approx. 30 – 60 minute (dependent on conditions) Diluted Application – approx. 30 minutes (dependent on conditions)

NOTICE

The information contained herein and any other advice, are given in good faith based on Mapei's current knowledge and experience, and are adequate when the products are properly stored, handled and applied under normal conditions, in accordance with Mapei's recommendations. The information only applies to the applications and products expressly referred to herein and are based on laboratory tests which do not replace practical tests and may not fully reflect actual performance on site where application and service conditions will be different. In case of changes in the parameters of the application, such as differences in substrates, temperature and ambient moisture, etc., or in case of different service conditions, consult your local Mapei Technical Assistance prior to using the products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The specialist contractor is responsible for strictly following the application recommendations contained in the available documentation. Users must always refer to the most recent local Technical Data Sheet for the product concerned which can be obtained from the web-site or local Mapei representative.

CERTIFIED
MANAGEMENT SYSTEMS



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI ISO 45001:2018