

To order now, call 1-800-845-3374

eOne MF

Product Specifications

The eOne MF is a microprocessor controlled, multifunction metering pump, suitable for applications which require proportional dosing. The pump operates at a high dosing frequency (up to 300 impulses/minute) and is equipped with backlit graphic display for correct setting of the various programming parameters.

eOne MF features are:

- Digital Manual Control
- Level Control
- Proportional Dosing Modes (1 x n; 1 : n; 1 x n M; ml x l; L x l; ml x m3; PPM)
- Flow Rate Calibration
- Flow Sensor Input
- 4-20 mA control
- Pump Output Display
- Relay Output
- Underload/Overload alarms

eOne Wetted Parts	
Pump Head	PVDF
Diaphragm	PTFE (Teflon®)
Seals	TFE/P (Aflas®)
Valves	Ceramic Ball
Discharge Tubing	PE (Polyethylene)
Suction Tubing	PVC



ETATRON

Version	Flow Rate		Pressure		Strokes Per Minute
0110	0.26 GPH	1 LPH	145 PSI	10 BAR	180
0216	0.53 GPH	2 LPH	232 PSI	16 BAR	300
0420	1.06 GPH	4 LPH	290 PSI	20 BAR	300
0607	1.59 GPH	6 LPH	101 PSI	7 BAR	300
0710	1.85 GPH	7 LPH	145 PSI	10 BAR	300
1012	2.64 GPH	10 LPH	174 PSI	12 BAR	300
1505	3.96 GPH	15 LPH	72 PSI	5 BAR	300
2007	5.28 GPH	20 LPH	101 PSI	7 BAR	300
3005	7.93 GPH	30 LPH	72 PSI	5 BAR	300

50 West Stoevers Ave. • Myerstown, PA 17067 • 1-800-845-3374

www.farmerboyag.com

Page 1 of 1

FARMER BOY®