



# S9978

15T8/LED/48-850/DR  
15 watt T8 LED; 5000K; Medium Bi Pin base; 50000 Average  
rated hours; 2200 Lumens

## Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Ballast required
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts\*
- All glass tube



S9978

\*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9978	045923099786	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-850/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	48"	1.00"	2200	50000	5000	Natural Light
CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
82	220	10	Box	Lawful for sale in California	PUK747TQ <a href="#">DLC Search</a>	Yes	Yes



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

