Intertek CE MSDS UN38.3 PASSED Transport Safety Certified CERTIFIED UL 1973 UL 9540A

Weight: 109kgs

Battery Type	LiFePO4 Battery
Battery Model	LNT051200A-B-GBP2
Battery Power	10.24KWh
Battery Voltage	51.2V
Capacity of Battery	200Ah
Charge Voltage	56V
Discharge Voltage	46V
Max Charge Current	≤150A
Max Discharge Current	≤150A
Short Circuit Protection Current	1652A (106mS)
Depth of Discharge	80% DOD
Charge Working Temperature Range	0~45℃
Discharge Working Temperature Range	-20~55℃
Display	LCD/LED
Communication	CANBUS/RS485
Degree of Protection	IP50
Certification	UL1973, IEC62619,CE-EMC, UN38.3, MSDS

Weight: 129kgs

Battery Type	LiFePO4 Battery
Battery Model	LNT051280A-B-GBP2
Battery Power	14.34KWh
Battery Voltage	51.2V
Capacity of Battery	280Ah
Charge Voltage	56V
Discharge Voltage	46V
Max Charge Current	≤100A
Max Discharge Current	≤150A
Short Circuit Protection Current	1652A (106mS)
Depth of Discharge	80% DOD
Charge Working Temperature Range	0~45℃
Discharge Working Temperature Range	-20~55℃
Display	LCD/LED
Communication	CANBUS/RS485
Degree of Protection	IP50
Installation Manual & More Information	www.liniotech.com

www.liniotech.com 832-627-9763