# **KEEP IT CLEAN**



## **XLERATOR® HAND DRYER WALL GUARDS**

MICROBAN<sup>®</sup> Wall Guards are designed specifically to fit securely underneath your XLERATOR hand dryers, protecting your walls from water droplets that can be blown off wet hands by the powerful air stream of the XLERATOR.

### XLERATOR<sup>®</sup> HAND DRYER WALL GUARDS



#### WALL GUARDS








PART #89W

PART #89B

PART #89S



**Recommended location of adhesive strips** 

Part ID	Description	List Price
ANTI-I	MICROBIAL WALL GUARDS	
89W	MICROBAN® Wall Guard-White	<b>\$120</b> /Set*
89B	MICROBAN Wall Guard-Black	<b>\$120</b> /Set*
89S	Wall Guard-Stainless	<b>\$200</b> /Set*
		*Set: 1 box of 2 wall guards

#### **SPECIFICATIONS**

Oty: 2 per set

Size: 31 ¾" x 15 ¾" x 1/16"

Weight: 89S: 11 lbs., 89W and 89B: 4 lbs.

#### **INSTALLATION:**

Mounted with 4 strips of construction grade 3M adhesive tape

#### MATERIALS

MICROBAN anti-microbial plastic: White or Black

or brushed stainless steel

#### INSTALLATION INSTRUCTIONS

1. Clean the wall surface with ISOPROPYL ALCOHOL prior to installation and make sure that the surface is dry and free of any dust and debris.

2. Center the Wall Guard underneath the hand dryer so that the top of the Wall Guard is 1" below the bottom of the dryer.

3. Carefully measure and mark the wall surface for placement of the Wall Guard with a pencil or temporary marker.

4. Four strips of double-sided adhesive are included for each panel. Apply the tape strips to textured side of black or white panel and smooth side of brushed stainless panel as follows:

Lay out tape strips according to illustration at left.

• Remove one strip and apply to either right or left side to start.

• Press each tape strip firmly onto the plastic as it is applied.

• Continue until all 4 strips are applied.

Note: Alignment is critical. Once placed on the wall, the Wall Guard cannot be re-positioned.

5. Align the top edge of the Wall Guard with the markings on the wall and firmly press into place against the entire surface of the Wall Guard.

6. Optional: After guard is applied to the wall you may add silicone sealant around the edge.

#### **CLEANING INSTRUCTIONS**

Clean the installed Wall Guard with mild soapy water and a soft cloth. Mild dish soap mixed with water in a spray bottle works best.

**D0 NOT USE** any cleaner that contains any ammonia or abrasive cleansers to clean the surface.

#### NATIONAL INSTALLATION SERVICES AVAILABLE CALL FOR DETAILS 800-255-9235





**IME TO THROW IN THE TOWEL**<sup>®</sup>