

KIT FOR RECESSED MACHFLOW STAINLESS STEEL AISI 304 SATIN FINISH

Code: **KT0009CS**

General Description

- Kit for recessed machflow® hand dryer (hand dryer not included).
- The kit for recessed machflow® makes the machflow® hand dryer suitable for the compliance of the ADAAG norm (US) – that limits to 4 inches (100mm) the horizontal projection of the devices installed in bathrooms for public use-, bestowing on that hand dryer the quality of “specific for the disabled”.
- Maximum robustness and vandal-proofness.
- Excellent integration and aesthetical level.

Components & Materials

- Wall box is fabricated of two welded parts. The dryer mounting area is fabricated of 18GA 18-8 type AISI304 stainless steel, it includes 4 M5 bolts welded on top of the base plate for fitting of the machflow® hand dryer. The frame is fabricated of 22GA 18-8 type AISI304 stainless steel with 4 screw holes of Ø 1/4” (6,5mm) for mounting on the wall.
- Nuts and bolts for the fitting of the hand dryer to the kit included: 4 nuts DIN 934 M5, 4 washers DIN 9021 M5 and 4 rubber silent blocks 8 x 18mm.
NOTE: The screws and wall plugs for the mounting of the cabinet to the wall are not included. The use of stainless steel screws is recommended.
- Overall Dimensions: 23 7/16” H x 14 3/4” W x 6 55/64” D (595 x 375 x 174 mm).
- Rough Wall Opening: 21 21/32” H x 13” W x 3 55/64” D (550 x 330 x 98 mm).
- Outer projection from the wall: 3 55/64” (98mm).
- Projection inside the wall: 3” (76mm).
- Weight: 6,6 lbs (3 Kg) without machflow® hand dryer.

Installation guide

When installed, bottom of hand dryer will be 7” ½ (190mm) above bottom of rough wall opening.

Operation

No specific instructions for its use required.

Certificates & Qualifications

ISO 9001:2008. Complies with ADA requirements.

Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without prior notice.

Revision 04-2013



Handy Washroom Direct
www.handywashroom.com

© mediclinics S.A.

