

# AT-E2CMKII

V-Mount adaptor plate for Canon's EOS C300 Mark II Camera



## Product Description

The AT-E2CMKII is specifically designed for Canon's EOS C300 Mark II camera. Equipped with a genuine Lemo connector and two D-Taps, DC power is available for direct power to the camera and peripheral 12V equipment. The AT-E2CMKII can integrate into 15mm mini-studio rod systems by using IDX's A-CP(A) cheese plate and 15mm & 19mm studio rod systems with third-party accessories. For powering the C300 Mark II with a V-Mount battery, the AT-E2CMKII is the universally preferred solution.

## Features

- V-Mount plate for Canon EOS C300 Mark II
- 12 inch cable (right side) with genuine Lemo connector for DC camera power
- (2) D-Tap DC outputs for 12V accessories (50W each)
- Flexible mounting with 3 mounting hole configurations

## IDX Battery Runtime Chart

DUO-150 CUE-D150	ELITE	DUO-95 CUE-D95	E-HL10DS	E-HL9	CUE-D75
7 hours 18 min	6 hours 48 min	4 hours 33 min	4 hours 48 min	4 hours 21 min	3 hours 39 min

Battery runtimes are based on theoretical runtime calculations with the camera body consumption only. Actual runtimes may vary.

## Technical Specifications

**DC Output Voltage (Lemo and D-Taps)**  
12~16.8V

**D-Tap Max Output**  
50W / 4.1A

**Cable Length**  
12 inch / 30cm

**Dimensions**  
3.24(w) x 5.59(h) x 0.47(d) inch.  
82.5(w) x 142(h) x 12(d) mm

**Weight**  
0.49 lbs. / 222 g.

**Included Accessories**  
(4) M3 x 8(mm) mounting screws

IDX reserves the right to change the specifications contained herein without notice.



IDX System Technology, Inc.  
19001 Harbortgate Way, Suite 105  
Torrance, CA 90501 USA

T: (310) 328-2850  
E: idx.usa@idx.tv

F: (310) 328-8202  
W: www.idxtek.com