

Micro, High-Load, Travel-Friendly

### Imicro-98 & Imicro-150

The **Imicro-98** and **Imicro-150** are capable of 14A draws with capacities of 97Wh, and 145Wh all while being over 30% smaller than our DUO-C98 battery. They're especially beneficial for users with small equipment and gimbal setups, rigs such as Steadicam for added stability, and anyone looking to use lighter, more compact battery packs for their cameras. Both batteries meet the IATA carry-on limit.



#### Imicro-98



<b>Capacity:</b>	97Wh
<b>Max Output Voltage</b>	16.8V
<b>Nominal Voltage:</b>	14.5V
<b>Max Draw:</b>	14A
<b>Power Outputs:</b>	(1) 100W D-Tap Advanced, (1) 100W D-Tap
<b>End Voltage:</b>	11V
<b>Additional Features:</b>	SMBus, 5 LED Power Indicator, V-Torch
<b>Protection:</b>	Over-charge, over-discharge, over-current, thermal protection
<b>Ambient Temperature:</b>	32°F ~ 104°F (Charge) -4°F ~ 113°F (Discharge) -4°F ~ 122°F (Storage)
<b>Dimensions:</b>	2.8(W) x 3.8(H) x 2.0(D) inches
<b>Weight:</b>	1.21 lbs

#### Imicro-150



<b>Capacity:</b>	145Wh
<b>Max Output Voltage</b>	16.8V
<b>Nominal Voltage:</b>	14.5V
<b>Max Draw:</b>	14A
<b>Power Outputs:</b>	(1) 100W D-Tap Advanced, (1) 100W D-Tap
<b>End Voltage:</b>	11V
<b>Additional Features:</b>	SMBus, 5 LED Power Indicator, V-Torch
<b>Protection:</b>	Over-charge, over-discharge, over-current, thermal protection
<b>Ambient Temperature:</b>	32°F ~ 104°F (Charge) -4°F ~ 113°F (Discharge) -4°F ~ 122°F (Storage)
<b>Dimensions:</b>	2.8(W) x 3.8(H) x 2.7(D) inches
<b>Weight:</b>	1.65 lbs

\*\*IDX reserves the right to change the specifications contained herein without notice.