

# TA-PV2J650

## V-Mount Adaptor for JVC GY-HM650/600

### Instruction Manual

Thank you for choosing the TA-PV2J650. Designed specifically for use with the JVC GY-HM650/600, the TA-PV2J650 attaches directly to the IDX A-CP(A) universal mounting plate, or other 3<sup>rd</sup> party manufactured mounting plates and shoulder mounts. Please check which fixing positions are required for 3<sup>rd</sup> party plates and use the appropriate location holes. The TA-PV2J650 incorporates an integral IDX V-Mount plate allowing direct mounting of any IDX ENDURA battery. To install, simply connect the DC power output cable to the DC-IN connector of the camera. The TA-PV2J650 has a D-Tap DC-OUT connector that supplies power directly from the battery allowing the use of professional on-board camera lights or other accessories. Please note, this is an unregulated output.

### Specifications

Dimensions: 82.5(w) x 142(h) x 12(d) mm  
Weight: 210g approx.  
Cable output voltage: 12V  
D-Tap output voltage: 12~17V (Unregulated)  
Maximum output for D-Tap: 50W  
Cable length: 1.7m approx.  
Included accessories: (4) M3 x 8 screws

### General Notes & Safety

- Do not attempt to open or modify this unit. All work should be carried out by IDX authorised service personnel only.
- Do not attach the TA-PV2J650 to any non-compatible video camera or equipment as it may cause defect, damage or other incidents. Please read this Instruction Manual carefully before use.
- When connecting a battery or adaptor to the TA-PV2J650, be sure to connect firmly. If it is not attached properly, it may result in loss or damage to the unit or even injury to the user.
- Do not expose to, use or place the unit in direct sunlight, extreme dust or other hazardous environments.
- A short between the plus (+) and minus (-) charge pins may cause fire, electrical shock or other incidents.
- Stop using immediately in case of abnormal smell, leak, color change or deformity during use.
- If you need any inspection or repairs, please contact your local IDX dealer or IDX office.



05032013

**IDX System Technology, Inc.**  
19001 Harborage Way, Suite 105 Torrance, CA 90501  
Tel: +1-310-328-2850  
Fax: +1-310-328-8202  
Email: idx.usa@idx.tv

05032013



# TA-PV2J650

## V-Mount Adaptor for JVC GY-HM650/600

### Instruction Manual

Thank you for choosing the TA-PV2J650. Designed specifically for use with the JVC GY-HM650/600, the TA-PV2J650 attaches directly to the IDX A-CP(A) universal mounting plate, or other 3<sup>rd</sup> party manufactured mounting plates and shoulder mounts. Please check which fixing positions are required for 3<sup>rd</sup> party plates and use the appropriate location holes. The TA-PV2J650 incorporates an integral IDX V-Mount plate allowing direct mounting of any IDX ENDURA battery. To install, simply connect the DC power output cable to the DC-IN connector of the camera. The TA-PV2J650 has a D-Tap DC-OUT connector that supplies power directly from the battery allowing the use of professional on-board camera lights or other accessories. Please note, this is an unregulated output.

### Specifications

Dimensions: 82.5(w) x 142(h) x 12(d) mm  
Weight: 210g approx.  
Cable output voltage: 12V  
D-Tap output voltage: 12~17V (Unregulated)  
Maximum output for D-Tap: 50W  
Cable length: 1.7m approx.  
Included accessories: (4) M3 x 8 screws

### General Notes & Safety

- Do not attempt to open or modify this unit. All work should be carried out by IDX authorised service personnel only.
- Do not attach the TA-PV2J650 to any non-compatible video camera or equipment as it may cause defect, damage or other incidents. Please read this Instruction Manual carefully before use.
- When connecting a battery or adaptor to the TA-PV2J650, be sure to connect firmly. If it is not attached properly, it may result in loss or damage to the unit or even injury to the user.
- Do not expose to, use or place the unit in direct sunlight, extreme dust or other hazardous environments.
- A short between the plus (+) and minus (-) charge pins may cause fire, electrical shock or other incidents.
- Stop using immediately in case of abnormal smell, leak, color change or deformity during use.
- If you need any inspection or repairs, please contact your local IDX dealer or IDX office.



05032013

**IDX System Technology, Inc.**  
19001 Harborage Way, Suite 105 Torrance, CA 90501  
Tel: +1-310-328-2850  
Fax: +1-310-328-8202  
Email: idx.usa@idx.tv

05032013

