
510 DL TANDEM INSTRUCTION MANUAL



KIT INCLUDES:

1x DL Tandem
1x DL Tandem Magnetic Connector
1x 14mm Water Pipe Adapter

TECHNICAL SPECIFICATIONS:

Battery: 650 mAh
Voltages: 1.8, 2.4, 2.8, 3.4, 3.8 V
Max Cartridge Size: 0.55" x 2.32" (14 x 59 mm)
Charging: USB-C
Resistance: ≥0.8 Ω
Display: Active cart selection, current voltage(s), battery %, preheat, charging status

FEATURES:

1. Activate cartridges independently or simultaneously with the push of a button.
2. Independent voltage control for both cartridges.
3. Removable magnetic mouthpiece.
4. Water pipe compatible (14 mm included, 19 mm optional purchase).
5. Compatible with up to 2 g cartridges.
6. Extra discreet, no lightbar.

HOW TO USE:

Prior to first use, fully charge the battery using a standard charging cable with a standard power brick. Once the device is fully charged, unplug the battery from the charging cord. Then, detach the magnetic connector from the bottom of the battery, screw in 1 or 2 cartridges to the 510 connection and reinsert.

Press the power button 5 times to turn on the device, by default, it will be set to the third setting (2.8 V). If you have 2 cartridges it will default to both of them being active, if there is only one cartridge attached it will automatically detect it and switch the settings so only that side is active.

With the cartridges in place and the device on you can now select your vaping experience. Use the shift button to select either one or both of your cartridges. Then use the power button to select the voltage for each cartridge. After you have selected your preferred voltage setting, you can start the preheat function by quickly inhaling on the device 2 times or double-clicking the power button. The L or R or both will flash while the preheat is active, you can stop the preheat at any time by pressing either button or inhaling on the device. Now the device is ready to vape, you can hold the power button down or simply inhale on the mouthpiece.

HOW TO CLEAN:

1. Remove the magnetic connector from the battery.
2. Wipe out the outside and inside of the bottom magnetic connector with an isopropyl alcohol pad. Use an alcohol swab to wipe any excess oil out of the 510 screw-in connector.
3. Clean inside the air pathways with an alcohol swab. Using a circular motion, work your way up and down the air pathways until you do not see any more oil. You can also remove the mouthpiece to clean the air pathways from the top.
4. With the mouthpiece off, separate the inner air path from the silicone. Use a cotton swab and alcohol to clean any build-up.
5. Do not submerge any part of the device in a cleaning solution. Allow all parts to air dry before reassembly.

WARNINGS:

Do not expose to extreme temperatures or direct sunlight. Do not drop the device or accessories. Do not drop or submerge in any liquid. Do not modify the electronics in any way. This device is intended for adults only. Do not sell or provide to minors. Keep all parts, concentrates, herbs, and liquids away from children and pets. This is not a medical device and is not intended to diagnose, treat, mitigate, cure, or prevent any ailment, disease, or other conditions. Consult a physician before use, especially if you suffer from heart disease or any other medical condition, or if you are pregnant or breastfeeding. Failure to follow any of these instructions could result in product damage, property damage, personal injury, and may void warranty. Visit PulsarShop.com for warranty information.

PULSAR®

PulsarShop.com