



# USB to 2-Port RS-422, RS-485 DB9 Serial Interface Adapter Kit

**Part:** 2202-TB2 | **Model:** SeaLINK+2/485 Kit

The 2202-TB2 kit includes two TB34 terminal blocks that simplify RS-422 and RS-485 field wiring. Each terminal block adapter includes a DB9 female connector and five screw terminals.

The SeaLINK® 2202 USB serial I/O adapter provides two RS-422 or RS-485 serial ports for USB connectivity to legacy or non-USB compliant devices. The 2202 supports standard PC data rates up to 921K bps.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, simply connect the 2202 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.

Do you know that adapter design can impact your application? Find out how in this USB Serial performance report.

## Features & Specifications

### USB to 2-Port RS-422, RS-485 DB9 Serial Interface Adapter Kit

**Part:** 2202-TB2 | **Model:** SeaLINK+2/485 Kit

#### Features

- Compliant with RoHS and WEEE directives
- Each port individually configurable for RS-422 or RS-485
- High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- Data rates to 921.6K bps
- Automatic RS-485 enable/disable
- Serial and USB activity LEDs
- Hot-swappable
- Powered by USB connection
- Sealevel software supports many versions of Windows and Linux operating systems
- DB-9M connectors
- Includes 6' USB device cable (Item# CA179)
- Kit includes two TB34 terminal block adapters

#### Specifications

<b>Family</b>	SeaLINK
<b>Communications Chip</b>	USB/UART
<b>Dimensions</b>	7.1 (L) x 5.3 (W) x 1.5 (H)
<b>Electrical Interface</b>	RS-422, RS-485
<b>High Retention USB</b>	Yes
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Host Interface(s)</b>	USB
<b>Max Data Distance</b>	4000 feet
<b>Max Data Rate</b>	921.6K bps
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b># of Ports</b>	2
<b>Power Requirement</b>	+5V @ 500mA
<b>RoHS Compliant</b>	Yes
<b>Serial Connector(s)</b>	DB9M
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)
<b>USB Powered</b>	Yes
<b>USB Specification</b>	1.1 Compliant 2.0 Compatible