



# RS-232 Modbus RTU Interface to 16 Form C Relay Outputs

**Part:** 450S | **Model:** Seal/O-450S

The Seal/O-450S provides 16 SPDT Form C relays. Connection to the host device is made via an RS-232 connection. The Seal/O-450S is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-450S using industry-standard Modbus RTU protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

## Features & Specifications

### RS-232 Modbus RTU Interface to 16 Form C Relay Outputs

Part: 450S | Model: Seal/O-450S

#### Features

- RS-232 Modbus RTU interface
- 16 SPDT Form C relays
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- DIN rail mount or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

#### Specifications

<b>Family</b>	Seal/O
<b>Contact Bounce Time</b>	7ms max.
<b>Contact Operate Time</b>	2ms max.
<b>Contact Release Time</b>	1ms max.
<b>Contact Voltage</b>	60VDC max. 50VAC max.
<b>Digital I/O</b>	Form C Relay Outputs
<b>Dimensions</b>	7.5 (L) x 5.1 (W) x 1.3 (H)
<b>Extended Temperature</b>	Call for Options
<b>Humidity Range</b>	10 – 90% Relative Humidity, Non-Condensing
<b>Host Interface(s)</b>	RS-232
<b>Number of Inputs/Outputs</b>	16 Outputs
<b>Operating Temperature</b>	0°C to 70°C (32°F to 158°F)
<b># of Ports</b>	16
<b>Power Requirement</b>	9-30 VDC @ 4.0W
<b>RoHS Compliant</b>	Yes
<b>Storage Temperature</b>	-50°C to 105°C (-58°F to 221°F)